according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Concrete Primer Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Primer, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Ireland Ltd

Sika House

Ballymun Industrial Estate

Dublin 11

Telephone : +353 1862 0709 E-mail address of person : EHS@UK.Sika.com

responsible for the SDS

1.4 Emergency telephone number

National Poisons Information Centre (NPIC) (01) 809 2166

(available 8am - 10pm every day)

Sika Ireland (01) 862 0709 (available during office hours)

### **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

#### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breath-

ing difficulties if inhaled.

H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smokina.

P261 Avoid breathing mist or vapours.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

# Hazardous components which must be listed on the label:

2-methoxy-1-methylethyl acetate

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

Diphenylmethanediisocyanate, isomeres and homologues

2,2'-methylenediphenyl diisocyanate

## **Additional Labelling**

"As from 24 August 2023 adequate training is required before industrial or professional use."

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

# Components

Components			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226	>= 25 - < 40
Contains:	203-603-9	STOT SE 3; H336	
2-methoxypropyl acetate <= 1 %	01-2119475791-29-		
	XXXX		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika ®

# Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373  specific concentration limit Eye Irrit. 2; H319 >= 5 %  specific concentration limit STOT SE 3; H335 >= 5 %  specific concentration limit SKin Irrit. 2; H315 >= 5 %  specific concentration limit Skin Irrit. 2; H315 >= 5 %  Acute toxicity estimate	>= 5 - < 10
		Acute inhalation toxicity (dust/mist): 1,5 mg/l	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# Sika® Concrete Primer Part A

Date of last issue: 22.04.2024

o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1 227-534-9 01-2119480143-45- XXXX	Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373  specific concentration limit Eye Irrit. 2; H319 >= 5 %  specific concentration limit STOT SE 3; H335 >= 5 %  specific concentration limit Skin Irrit. 2; H315 >= 5 %  specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 5 - < 10
propyl acetate	109-60-4 203-686-1 01-2119484620-39- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 5 - < 10

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika®

# Sika® Concrete Primer Part A

Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373  specific concentration limit Eye Irrit. 2; H319 >= 5 %	>= 1 - < 2,5
		specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
		specific concentration limit STOT SE 3; H335 >= 5 %	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

limit STOT SE 3; H335 >= 5 %  specific concentration limit Skin Irrit. 2; H315 >= 5 %  specific concentration limit Resp. Sens. 1; H33- >= 0,1 %	on on
Resp. Sens. 1; H33- >= 0,1 %	4
	specific concentration limit STOT SE 3; H335 >= 5 %  specific concentration limit Skin Irrit. 2; H315 >= 5 %  specific concentration limit Resp. Sens. 1; H334

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema
Dermatitis
Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of causing cancer.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

: Water

media

High volume water jet

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting

Do not use a solid water stream as it may scatter and spread

fire.

Hazardous combustion prod: :

No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible ab-Methods for cleaning up

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Advice on safe handling Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asth-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against :

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm	2000/39/EC
			550 mg/m3	
	Further information: Identifies the possibility of significant uptake			
	through the sk	n, Indicative		
		TWA	50 ppm	2000/39/EC
			275 mg/m3	
		OELV - 8 hrs	50 ppm	IE OEL
		(TWA)	275 mg/m3	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Date of last issue: 22.04.2024

Revision Date: 13.05.2025

	Further inform	ation: Substances	which have the c	apacity to pene
		n when they come		
	sorbed into the	e body		
		OELV - 15 min (STEL)	100 ppm 550 mg/m3	IE OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
	Further inform	ation: Chemical ac	ents which follow	ing exposure
	may cause se	nsitisation of the re	espiratory tract an	d lead to asth-
	ma, rhinitis or	extrinsic allergic a	lveolitis	
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	OELV - 8 hrs (TWA)	0,02 mg/m3 (NCO)	IE OEL
	Further inform	ation: Chemical ag	ents which follow	ing exposure
	may cause se	nsitisation of the re	espiratory tract an	d lead to asth-
		extrinsic allergic a		
	,	OELV - 15 min (STEL)	0,07 mg/m3 (NCO)	IE OEL
propyl acetate	109-60-4	OELV - 8 hrs (TWA)	100 ppm	IE OEL
		OELV - 15 min (STEL)	150 ppm	IE OEL
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	OELV - 8 hrs (TWA)	0,02 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure			
	may cause sensitisation of the respiratory tract and lead to asth-			
	ma, rhinitis or extrinsic allergic alveolitis			
	,	OELV - 15 min	0,07 mg/m3	IE OEL
		(STEL)	(NCO)	
		OELV - 8 hrs (TWA)	0,005 ppm (NCO)	IE OEL
2,2'-methylenediphenyl diisocyanate	2536-05-2	OELV - 8 hrs (TWA)	0,02 mg/m3 (NCO)	IE OEL
	Further information: Chemical agents which following exposure			
	may cause sensitisation of the respiratory tract and lead to asth-			
	ma, rhinitis or extrinsic allergic alveolitis			
		OELV - 15 min	0,07 mg/m3	IE OEL
		(STEL)	(NCO)	
		TWA	0,01 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		STEL	0,02 mg/m3 (NCO)	98/24/EC I

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

# 8.2 Exposure controls

# **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

## Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state : liquid Colour : light yellow

Odour : characteristic

Melting point/ range / Freez-

ing point

No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Date of last issue: 22.04.2024

Revision Date: 13.05.2025

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : 10,8 %(V)

per flammability limit

Lower explosion limit /

Lower flammability limit

: 1,5 %(V)

40 °C Flash point

Method: closed cup

Auto-ignition temperature 333 °C

Decomposition temperature No data available

рΗ substance/mixture is non-soluble (in water)

**Viscosity** 

Viscosity, kinematic > 7 mm2/s (40 °C)

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure 33 hPa

Density ca. 1,1 g/cm3 (20 °C)

Relative vapour density No data available

Particle characteristics No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

## 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

## 10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

Not classified due to lack of data.

## Components:

## 2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

#### 4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Date of last issue: 22.04.2024

Revision Date: 13.05.2025

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

## Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

# Serious eye damage/eye irritation

Causes serious eye irritation.

## Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

## Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified due to lack of data.

# Carcinogenicity

Suspected of causing cancer.

## Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure


May cause respiratory irritation. May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified due to lack of data.

# **Aspiration toxicity**

Not classified due to lack of data.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regula-

tion (EU) 2020/878

# Sika® Concrete Primer Part A



Date of last issue: 22.04.2024

Revision Date: 13.05.2025

### 11.2 Information on other hazards

## **Endocrine disrupting properties**

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

## **Components:**

## Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

: EC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

# 12.2 Persistence and degradability

No data available

## 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

## 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Date of last issue: 22.04.2024

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic sol-

vents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADR : UN 1263 IMDG : UN 1263 IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT RELATED MATERIAL IMDG : PAINT RELATED MATERIAL

IATA : Paint related material

14.3 Transport hazard class(es)

Class Subsidiary risks

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika®

# Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

 ADR
 : 3

 IMDG
 : 3

 IATA
 : 3

## 14.4 Packing group

**ADR** 

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

Remarks : Transport according to chapter 3.4 (LQ) possible

**IMDG** 

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

#### 14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

**REACH Information:** 

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

All substances contained in our Products are - registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 56:

: Not applicable

4,4'-methylenediphenyl diisocyanate, o-(p-isocyanatobenzyl)phenyl isocyanate, Diphenylmethanediisocyanate, isomeres and homologues, 2,2'-methylenediphenyl diisocyanate

Number on list 74:

4,4'-methylenediphenyl diisocyanate, o-(p-isocyanatobenzyl)phenyl isocyanate, Diphenylmethanediisocyanate, isomeres and homologues, 2,2'-methylenediphenyl diisocyanate

Number on list 75

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EU) No 2024/590 on substances that de: Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika® Concrete Primer Part A



Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

Not applicable

tants (recast)

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

Not applicable

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 33,86% w/w

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 33,86% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:  Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

# Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H225 : Highly flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika®

# Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

H226 : Flammable liquid and vapour.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

98/24/EC I : Europe. Chemical Agents Directive - Annex I: Binding occupa-

tional exposure limit values

IE OEL : Ireland. List of Chemical Agents and Carcinogens with Occu-

pational Exposure Limit Values - Code of Practice, Schedule 1

and 2

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 98/24/EC I / STEL : Limit values Short-term 98/24/EC I / TWA : Limit values 8 hours

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

(STEL) od)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sika ®

# Sika® Concrete Primer Part A

Revision Date: 13.05.2025 Version 3.0 Print Date 13.05.2025

Date of last issue: 22.04.2024

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

Classification of the mixture:		Classification procedure:	
Flam. Liq. 3	H226	Based on product data or assessment	
Skin Irrit. 2	H315	Calculation method	
Eye Irrit. 2	H319	Calculation method	
Resp. Sens. 1	H334	Calculation method	
Skin Sens. 1	H317	Calculation method	
Carc. 2	H351	Calculation method	
STOT SE 3	H336	Calculation method	
STOT SE 3	H335	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

IE / EN