



## PRODUCT DATA SHEET

# Sika® MultiSeal-500

Sika® MultiSeal-500 is a prefabricated self-adhering sheet-type waterproofing membrane.

### PRODUCT DESCRIPTION

Sika® MultiSeal-500 is a prefabricated self-adhering sheet-type waterproofing membrane. It is composed of a tough multi-layer cross-laminated film that is coated with a rubberized asphalt adhesive. A release liner protects the adhesive and is removed as the membrane is installed. Sika® MultiSeal-500 is intended as a multi-purpose waterproofing membrane for use in sub-grade applications and under siding, exterior plaster, as a through wall flashing or anywhere it will be protected from long-term ultraviolet exposure. Sika® MultiSeal-500 adheres aggressively to most clean, dry substrates including metal, wood vinyl, masonry and rigid insulation boards. Sika® MultiSeal-500 may be used to waterproof foundations and other below grade structures, plaza decks, balconies, under siding, and exterior plaster. This advanced system bonds to the substrate and self-seals around nails, staples and other fasteners to prevent damage caused by water penetration.

### USES

- Foundation wall, floor and planter waterproofing, under stucco and at head, sill chimney shoulder, pot shelves, parapets and pony walls
- Use for sealing SIPS building panels and around doors, windows and other potential leak areas
- Waterproofs and protects ICF foundations from damage
- Thru-wall flashing in cavity wall construction

### PRODUCT INFORMATION

#### Packaging

Carton contains 3 x 12", 2 x 18" wide rolls. (225 sf/ carton)

<b>Appearance / Color</b>	Black		
<b>Shelf Life</b>	1 Year		
<b>Storage Conditions</b>	Store upright in original, unopened and undamaged sealed packaging in dry conditions. Do not expose to direct sunlight or other heat sources.		
<b>Dimensions</b>	12", 18" wide x 75' long rolls.		
<b>Thickness</b>	40 Mils Nom.		(ASTM D 1970)
<b>Tensile Strength</b>	<u>Machine Direction</u>	<u>21 lbf/in</u>	(ASTM D 882)
	<u>Cross Machine Direction</u>	<u>28 lbf/in</u>	
<b>Low Temperature Bend</b>	Pass		(ICC-ES AC 38)
<b>Water Vapor Transmission</b>	0.02 g/m <sup>2</sup> in 24h Max		(ASTM E 96)
<b>Resistance to Water Penetration</b>	>30 hr.		(ASTM D 779)
<b>Self Sealability</b>	pass		(ASTM D 1970)

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	>50°F
<b>Substrate Temperature</b>	>50°F

### SUBSTRATE PREPARATION

- Apply in clear, dry weather
  - Surface must be clean, dry and free from oil
  - Masonry must be clean, fully cured and primed with an asphalt primer
  - Prime weathered surfaces and OSB as necessary
  - Clean, dry wood and metal surfaces do not require priming
- sealants
  - Do not install over flexible vinyl gaskets or uncured caulking
  - Do not expose installed product to direct sunlight for more than 90 days

### APPLICATION METHOD / TOOLS

- Use 3" side laps and 6" head laps
- When applying on vertical concrete surfaces, a termination bar is recommended around the top
- Apply uniform pressure with a 2-3" hand roller to entire surface

### LIMITATIONS

- Do not install over solvent-based sealants unless fully cured active solvents may liquefy bottom adhesive surface
- Installer is responsible for compatibility with caulks and

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

### LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD**

#### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

#### Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



#### Product Data Sheet

Sika® MultiSeal-500  
August 2018, Version 01.02  
020511090000000032

## BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

SikaMultiSeal-500-en-US-(08-2018)-1-2.pdf

