Revision Date 02/09/2022



SECTION 1. IDENTIFICATION

Product name	:	SikaControl [®] NS
Company name	:	Sika Corporation
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)			
Eye irritation	:	Category 2A	
GHS label elements			
Hazard pictograms	:		
Signal Word	:	Warning	
Hazard Statements	:	H319 Causes serious eye irritation.	
Precautionary Statements	:	Prevention: P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection.	
		Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ atten- tion.	



Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
magnesium oxide	1309-48-4		>= 70 - < 90
2-(2-butoxyethoxy)ethanol	112-34-5	Eye Irrit. 2A; H319	>= 1 - < 5
2-[2-(2-butoxyethoxy)ethoxy]ethanol	143-22-6	Eye Dam. 1; H318	>= 1 - < 5
sodium hydroxide	1310-73-2	Met. Corr. 1; H290	>= 1 - < 5
		Skin Corr. 1A; H314	
		Eye Dam. 1; H318	

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	:	Excessive lachrymation irritant effects Causes serious eye irritation.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES



Revision	Date	02/09/2022
1161131011	Date	02/03/2022

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Avoid breathing dust. Deny access to unprotected persons.
Environmental precautions	:	Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.
Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
Further information on stor- age stability	:	Keep in a dry place. No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters



Revision Date 02/09/2022

magnesium oxide	1309-48-4	TWA (Inhal- able particu- late matter)	10 mg/m3	ACGIH
		TWA (fume, total particu- late)	15 mg/m3	OSHA Z-1
		TWA (Fume - total particu- late)	10 mg/m3	OSHA P0
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhal- able fraction and vapor)	10 ppm	ACGIH
sodium hydroxide	1310-73-2	TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Particles of nuisance dust

Form of exposure	Value type	Control parameters	Basis
total dust	TWA	15 mg/m3	OSHA Z-3
respirable fraction	TWA	5 mg/m3	OSHA Z-3

Engineering measures	:	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend- ed or statutory limits.
Personal protective equipm	ent	
Respiratory protection	:	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
		The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe-



Revision Date 02/09/2022

	cific work-place.
Hygiene measures :	Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Avoid breathing dust.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	off-white, tan
Odor	:	slight
Odor Threshold	:	No data available
рН	:	> 11
Melting point/range	:	> 3,812 °F / > 2,100 °C
Boiling point/boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	2.71 g/cm3
Solubility(ies) Water solubility	:	slightly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	No data available
octanol/water Autoignition temperature	:	No data available
Decomposition temperature	:	No data available

Revision Date 02/09/2022



Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

2-(2-butoxyethoxy)ethanol:

Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): ca. 2,700 mg/kg

2-[2-(2-butoxyethoxy)ethoxy]ethanol:

Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity	:	LD50 Dermal	(Rabbit): 3,480 mg/kg
-----------------------	---	-------------	-----------------------

Skin corrosion/irritation

Not classified based on available information.

Product:

Revision Date 02/09/2022



Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Result

: Eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information. IARC Not applicable

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-[2-(2-butoxyethoxy)ethoxy]ethanol:

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 500 mg/l Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Revision Date 02/09/2022



Mobility in soil No data available		
Other adverse effects		
Product: Additional ecological infor- mation	Do not empty into drains; dispose of this material and its catainer in a safe way.	on-

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

Revision Date 02/09/2022

Print Date 02/09/2022

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

MARNING: This product can expose you to chemicals including nickel, which is known to the State of California to cause cancer, and lead compounds, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 02/09/2022

Revision Date 02/09/2022

100000013793 US / Z8

