SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

SECTION 1. IDENTIFICATION

Product name : SikaGrout-4316 Formerly MFlow 4316

Product code : 00000000050288115

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation : 2

Serious eye damage/eye

irritation

Category 1

Carcinogenicity (Inhalation) : 1A (Lung)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

2 (Kidney, Immune system)

Specific target organ toxicity

specific target org
 single exposure

3 (Respiratory system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.

H315 Causes skin irritation.

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

H335 May cause respiratory irritation.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated

exposure if inhaled.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P201 Obtain special instructions before use.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust or mist.

P202 Do not handle until all safety precautions have been read and understood.

P270 Do not eat, drink or smoke when using this product. P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P362 + P364 Take off contaminated clothing and wash it before reuse

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Cement, portland, chemicals	65997-15-1	>= 25 - < 75
calcium oxide	1305-78-8	>= 1 - < 7
Quartz (SiO2)	14808-60-7	>= 0 - < 3
Iron oxide	1309-37-1	>= 0 - < 10
magnesium oxide	1309-48-4	>= 0 - < 3





Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

Limestone	1317-65-3	>= 0 - < 7
Silicon dioxide	7631-86-9	>= 1 - < 5
Calcium sulphate	7778-18-9	>= 0 - < 7
Gypsum (Ca(SO4).2H2O)	13397-24-5	>= 0 - < 3

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Dry powder Water spray

Carbon dioxide (CO2)

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-:

tive equipment and emergency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Neutralize with acid.

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

Further information on stor-

age conditions

: Containers should be stored tightly sealed in a dry place.

Materials to avoid : Segregate from metals.

Segregate from acids and bases.

Segregate from oxidants.

Segregate from foods and animal feeds.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR
				1910.1000
				(Table Z-1)
		TWA value	5 mg/m3	29 CFR
				1910.1000
				(Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Iron oxide	1309-37-1	TWA value	5 mg/m3	ACGIHTLV
		(Respirable		
		fraction)		
		REL value	5 mg/m3	NIOSH
		(Dust and	(iron (Fe))	
		fume)		
		PEL	10 mg/m3	29 CFR
		(fumes/smok		1910.1000
		e)		(Table Z-1)
		TWA value	10 mg/m3	29 CFR
		(fumes/smok		1910.1000
		e)	- / 0	(Table Z-1-A)
		TWA (Res-	5 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)	E/ 0	NICOLLEGE
		TWA (dust	5 mg/m3	NIOSH REL
		and fume) TWA	(Iron) 10 mg/m3	OSHA Z-1
			10 1119/1113	USHA Z-1
		(Fumes)	15 m a/m 2	OSHA Z-1
		TWA (total dust)	15 mg/m3	USHA Z-1
		TWA (respir-	5 mg/m3	OSHA Z-1

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

		able fraction)		
		TWA (Fumes)	10 mg/m3	OSHA P0
magnesium oxide	1309-48-4	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		PEL (Total particulate)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total partic- ulate)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Inhal- able particu- late matter)	10 mg/m3	ACGIH
		TWA (fume, total particu- late)	15 mg/m3	OSHA Z-1
		TWA (Fume - total particu- late)	10 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Silicon dioxide	7631-86-9	REL value	6 mg/m3	NIOSH
		TWA value	6 mg/m3	29 CFR

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

TWA value	I	ſ	I	1	1910.1000
TWA value 20 millions of particles per cubic foot of air father 29 CFR 1910.1000 (Table 2-3) (Silica)					
Darticles per cubic foot of air 1910.1000 17able Z-3) 29 CFR 1910.1000 20 CFR 1			TWA value	20 millions of	
TWA value					
TWA value					(Table Z-3)
TWA (Dust) 20 Million particles per cubic foot (Silica) TWA (Dust) 80 mg/m3 / %SiO2 (Silica) TWA (Respirable dust) (Silica) TWA (Respirable fraction) TWA (Respirable) TWA (Respirable) TWA value (Total) TWA value (Respirable) TWA value (Total) TWA value (Respirable) TWA value (Total) TW			TWA value		
TWA (Dust) 20 Million particles per cubic foot (Silica) TWA (Dust) 80 mg/m3 / %SiO2 (Silica) OSHA Z-3 Willion particles per cubic foot (Silica) OSHA Z-1 Willion particles per cubic foot (Silica) OSHA Policit					1910.1000
TWA (Dust) 80 mg/m3 / %SiO2 (Silica) 10 mg/m3 / ms 10					
Silica TWA (Dust)			TWA (Dust)		OSHA Z-3
TWA (Dust)					
Nosh retails Nosh retails					
TWA (Respirable dust)			TWA (Dust)		OSHA Z-3
TWA (Respirable dust)					
Pirable dust) (Silica)					
TWA					NIOSH REL
Calcium sulphate					
Calcium sulphate 7778-18-9 TWA value (Inhalable fraction) 10 mg/m3 ACGIHTLV REL value (Respirable) REL value (Respirable) 5 mg/m3 NIOSH PEL (Respirable) 10 mg/m3 NIOSH PEL (Respirable fraction) 5 mg/m3 29 CFR 1910.1000 (Table Z-1) 29 CFR 1910.1000 (Table Z-1) 15 mg/m3 29 CFR 1910.1000 (Table Z-1) 15 mg/m3 29 CFR 1910.1000 (Table Z-1) 15 mg/m3 29 CFR 1910.1000 (Table Z-1-A) 15 mg/m3 29 CFR 1910.1000 (Table Z-1-A) 15 mg/m3 1910.1000 (Total dust) 15 mg/m3 NIOSH REL TWA (Respirable) 1910.1000 Table Z-1-A) TWA (total) 10 mg/m3 NIOSH REL TWA (total) 15 mg/m3 OSHA Z-1 TWA (respirable) 15 mg/m3 OSHA Z-1 TWA (respirable) 15 mg/m3 OSHA PO TWA (respirable) 5 mg/m3 OSHA PO TWA (respirable) 5 mg/m3 OSHA PO TWA (respirable)			IWA		NIOSH REL
(Inhalable fraction)	Calcium sulphate	7778-18-9	TWA value	,	ACGIHTLV
Fraction REL value (Respirable) REL value (Total) REL value (Total) PEL (Respirable) S mg/m3 NIOSH		1110100		101119/1110	7.00
REL value (Respirable)					
REL value (Total)				5 mg/m3	NIOSH
(Total) PEL (Respirable fraction) Fell (Respirable fraction) TWA (Inhalable fraction) 15 mg/m3 29 CFR 1910.1000 (Table Z-1) 15 mg/m3 29 CFR 1910.1000 (Table Z-1) 15 mg/m3 29 CFR 1910.1000 (Table Z-1-A) 15 mg/m3 29 CFR 1910.1000 (Table Z-1-A) 15 mg/m3 29 CFR 1910.1000 (Table Z-1-A) 15 mg/m3 15 mg/m3 NIOSH REL 15 mg/m3 NIOSH REL 15 mg/m3 OSHA Z-1 15 mg/m3 OSHA PO 15 mg/m3 15 mg/m3 OSHA PO 15 mg/m3 15			(Respirable)		
PEL (Respirable fraction) S mg/m3 29 CFR 1910.1000 (Table Z-1)			REL value	10 mg/m3	NIOSH
able fraction) 1910.1000 (Table Z-1)			(Total)		
Cable Z-1) PEL (Total dust) 15 mg/m3 29 CFR 1910.1000 (Table Z-1)				5 mg/m3	
PEL (Total dust)			able fraction)		
dust)					
TWA value (Respirable fraction)				15 mg/m3	
TWA value (Respirable fraction) TWA value (Respirable fraction) TWA value (Total dust) TWA value (Total dust) TWA (Respirable) TWA (Respirable) TWA (total) TWA (total) TWA (total) TWA (total) TWA (respirable fraction) TWA (Total dust) TWA (respirable fraction) TWA (Inhalable particulate matter) TWA (Inhalable particulate matter)			dust)		
(Respirable fraction) 1910.1000 (Table Z-1-A) TWA value (Total dust) 15 mg/m3 29 CFR 1910.1000 (Table Z-1-A) TWA (Respirable) 5 mg/m3 NIOSH REL TWA (total) 10 mg/m3 NIOSH REL TWA (total dust) 15 mg/m3 OSHA Z-1 TWA (respirable) 5 mg/m3 OSHA Z-1 TWA (respirable) 5 mg/m3 OSHA Z-1 TWA (respirable) 15 mg/m3 OSHA PO TWA (Total dust) 15 mg/m3 OSHA PO TWA (respirable) 5 mg/m3 OSHA PO TWA (Inhalable particulate matter) 10 mg/m3 ACGIH				_ , _	
Traction				5 mg/m3	
TWA value (Total dust) TWA (Respirable) TWA (total) TWA (respirable) TWA (Total) TWA (Total					
(Total dust) (Total dust) (Total dust) (Table Z-1-A) TWA (Respirable) TWA (total) TWA (total) TWA (total) TWA (total) TWA (respirable) TWA (respirable) TWA (Total) TWA (Total) TWA (respirable) TWA (Inhalable)				45/0	
TWA (Respirable) TWA (total) TWA (respirable) TWA (respirable) TWA (respirable) TWA (respirable) TWA (Total dust) TWA (Total dust) TWA (respirable) TWA (Inhalable)				15 mg/m3	
TWA (Respirable) TWA (total) TWA (total) TWA (total) TWA (total) TWA (total) TWA (respirable) TWA (respirable) TWA (respirable) TWA (Total) TWA (Total) TWA (Total) TWA (respirable) TWA (Inhalable)			(Total dust)		
pirable) TWA (total) 10 mg/m3 NIOSH REL TWA (total 15 mg/m3 OSHA Z-1 dust) TWA (respirable fraction) TWA (Total dust) TWA (Total dust) TWA (respirable dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) TWA (total 15 mg/m3 OSHA PO OSHA PO ACGIH			TWA (Pos	5 mg/m2	
TWA (total) 10 mg/m3 NIOSH REL TWA (total 15 mg/m3 OSHA Z-1 dust) TWA (respirable fraction) TWA (Total dust) TWA (respirable dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) TWA (total 15 mg/m3 OSHA PO OSHA PO OSHA PO ACGIH				J mg/ms	INIOGITAEL
TWA (total dust) TWA (respirable fraction) TWA (Total dust) TWA (Total dust) TWA (respirable dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) TWA (total dust) TWA (total dust) TWA (Total dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) TWA (total dust)			' '	10 mg/m3	NIOSH RFI
dust) TWA (respirable fraction) TWA (Total dust) TWA (respirable dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) S mg/m3 OSHA PO OSHA					
TWA (respirable fraction) TWA (Total dust) TWA (respirable dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) 5 mg/m3 OSHA PO OS					
able fraction) TWA (Total dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) able fraction) TWA (Inhalable particulate matter)				5 mg/m3	OSHA Z-1
TWA (Total dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) 15 mg/m3 OSHA P0 OSHA PO					
dust) TWA (respirable dust fraction) TWA (Inhalable particulate matter) TWA (Inhalable particulate matter)				15 mg/m3	OSHA P0
able dust fraction) TWA (Inhalable particulate matter) ACGIH					
fraction) TWA (Inhalable particulate matter) fraction TWA (Inhalable particulate matter) ACGIH				5 mg/m3	OSHA P0
TWA (Inhal- able particu- late matter) 10 mg/m3 ACGIH					
able particu- (Calcium) late matter)					
late matter)					ACGIH
				(Calcium)	
Gynsum (Ca(SOA) 2H2O)	(2 (2 2))	1.25			
	Gypsum (Ca(SO4).2H2O)	13397-24-5	TWA value	10 mg/m3	ACGIHTLV
(Inhalable			(Inhalable		

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

	1	fraction)		
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhal- able particu- late matter)	10 mg/m3 (Calcium)	ACGIH
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir- able dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Res-	0.025 mg/m3	ACGIH

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

		pirable par- ticulate mat- ter)	(Silica)	
			0.05/0	00114 04 00
		PEL (respir- able)	0.05 mg/m3	OSHA CARC
		TWA (Res-	0.05 mg/m3	NIOSH REL
		pirable dust)	(Silica)	
Cement, portland, chemicals	65997-15-1	TWA value (Respirable fraction)	1 mg/m3	ACGIHTLV
			10	NIOCLI
		REL value (Total)	10 mg/m3	NIOSH
		REL value (Respirable)	5 mg/m3	NIOSH
		PEL (Total	15 mg/m3	29 CFR
		dust)	To mg/mo	1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	50 millions of	29 CFR
		I WA Value	particles per cubic	1910.1000
			foot of air	(Table Z-3)
		TMA (Dec		ACGIH
		TWA (Respirable particulate matter)	1 mg/m3	ACGIN
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total) dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Dust)	50 Million parti- cles per cubic foot	OSHA Z-3
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA value	0.05 mg/m3	29 CFR

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

	(Respirable dust)	1910.1001- 1050
OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
TWA (Res- pirable dust)	0.05 mg/m3	OSHA Z-1
TWA (respir- able)	10 mg/m3 / %SiO2+2	OSHA Z-3
TWA (respir- able)	250 mppcf / %SiO2+5	OSHA Z-3
TWA (respir- able dust fraction)	0.1 mg/m3	OSHA P0
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respirable)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : Provide local exhaust ventilation to maintain recommended

P.E.L.

Personal protective equipment

Respiratory protection : Breathing protection if dusts are formed.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : gray

Odor Threshold : Not determined due to potential health hazard by inhalation.

pH : 13 (68 °F / 20 °C)

(as aqueous solution)

Boiling point : No applicable information available.

Flash point : does not flash

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Lower explosion limit / Lower

flammability limit

As a result of our experience with this product and our

knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance

with the intended use.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Bulk density : 1.25 g/m3

Solubility(ies)

Water solubility : insoluble (59 °F / 15 °C)

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

: No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong bases

Strong acids

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Chromate in this product has been reduced. Sensitization due

to chromate within stated shelf-live is unlikely.

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statement has been

derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Remarks: not applicable

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to

its consistency and insolubility in water.

Components:

Cement, portland, chemicals:

Partition coefficient: n- : GLP: no

octanol/water Remarks: not applicable

SikaGrout-4316 Formerly MFlow 4316



Version **Revision Date:** SDS Number: Date of last issue: -

000000539831 Date of first issue: 07/27/2020 1.0 07/27/2020

calcium oxide:

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

Quartz (SiO2):

Partition coefficient: n-

octanol/water

Remarks: not applicable

Iron oxide:

Partition coefficient: n-

octanol/water

Remarks: Study scientifically not justified.

magnesium oxide:

Partition coefficient: n-

octanol/water

Remarks: No data available.

Silicon dioxide:

Partition coefficient: n-

octanol/water

Remarks: not applicable

Calcium sulphate:

Partition coefficient: n-

octanol/water

GLP: no

Remarks: The value has not been determined because the

substance is inorganic.

Gypsum (Ca(SO4).2H2O):

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

Mobility in soil

Product:

Distribution among environ-

mental compartments

Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater

is not expected.

The substance will not evaporate into the atmosphere from

the water surface.

Other adverse effects

Product:

Results of PBT and vPvB

assessment

This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Additional ecological infor-

mation

Observe allowable values of impurities of effluents discharged

in water and soil (according regulation of ministry of the environment from November, 18th, 2014, law gazette pos. 1800

14/18

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

(Poland)

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

calcium oxide	1305-78-8
Iron oxide	1309-37-1
magnesium oxide	1309-48-4
Limestone	1317-65-3
Silicon dioxide	7631-86-9
Calcium sulphate	7778-18-9
Gypsum (Ca(SO4).2H2O)	13397-24-5
Quartz (SiO2)	14808-60-7





14808-60-7

Version	Revision Date:	SDS Number:	Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

07/27/2020	000000539831	Date of first issue: 07/27/2020	
Cement, por Quartz (SiO	rtland, chemicals 2)	65997-15-1 14808-60-7	
New Jersey Right To	Know		
calcium oxid	le	1305-78-8	
magnesium	oxide	1309-48-4	
Limestone		1317-65-3	
Calcium sulphate		7778-18-9	
Cement, por	tland, chemicals	65997-15-1	

California Prop. 65

Quartz (SiO2)

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as


active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

SECTION 16. OTHER INFORMATION


Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

1) 1910.1000

29 CFR 1910.1000 (Table Z- : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

3)

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

3) / TWA value

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Admin-

SikaGrout-4316 Formerly MFlow 4316



Version Revision Date: SDS Number: Date of last issue: -

1.0 07/27/2020 000000539831 Date of first issue: 07/27/2020

istration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/27/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE, NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN