

PRODUCT DATA SHEET

SikaProof® ExTape-150

SELF-ADHESIVE TAPE

PRODUCT DESCRIPTION

SikaProof® ExTape-150 is a self-adhesive tape, consisting of a film with a butyl rubber adhesive that is covered with a protective divided release liner.

SikaProof® ExTape-150 is used to adhere and seal joints and overlaps of the SikaProof® A sheet membrane system, as well as to execute details and connections where required on the smooth membrane surface side of the system.

USES

SikaProof® ExTape-150 may only be used by experienced professionals.

SikaProof® ExTape-150 is applied to the light yellow membrane surface of the SikaProof® A Membrane.

CHARACTERISTICS / ADVANTAGES

- Easy and fast to install
- High Adhesion of the butyl rubber adhesive
- Divided release liner

PRODUCT INFORMATION

Packaging

4 rolls, packed in one cardboard box. Each roll is 150 mm (.49 ft) x 20 mm (65.62 ft).

Coverage:

150 (.49 ft) x 20 m (65.6 lf) roll

Appearance / Color

White release liner over black butyl rubber adhesive, on a yellow film.

Shelf Life

SikaProof® ExTape-150 rolls have a shelf-life of 12 months from date of production if stored properly in unopened, undamaged, original packaging, in a horizontal position, in dry conditions and at temperatures between +5°C (+40°F) and +30°C (+85°F).

Storage Conditions

SikaProof® ExTape-150 rolls must be protected from direct sunlight, rain, snow and ice, etc. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.

| | |
|-------------------|---|
| Dimensions | Width: 150 mm (5.9") Length: 20 m (65.3 ft.) |
| Thickness | 1,10 mm |

SYSTEM INFORMATION

System Structure

System Components

SikaProof® ExTape-150 and SikaProof® Tape-150 are self-adhesive tapes to adhere joints, connections and details in the SikaProof® A sheet membrane waterproofing system. SikaProof® A-05, membrane in rolls of widths 1.0 or 2.0 m SikaProof® A-08, membrane in rolls of widths 1.0 or 2.0 m SikaProof® A-12, membrane in rolls of widths 1.0 or 2.0 m SikaProof® Tape-150, self-adhesive tape for internal jointing, based on butyl rubber, in 150 mm width SikaProof® ExTape-150, self-adhesive tape for external jointing, based on butyl rubber, in 150 mm width

APPLICATION INFORMATION

| | |
|--------------------------------|---|
| Ambient Air Temperature | +5°C min. / + 35 °C max. (+40°F min./ +95°F max.) |
| Substrate Temperature | +5°C min. / + 35°C max. (+40°F min./ +95°F max.) |

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface of the SikaProof® A membrane is the light yellow surface, which must be dry, clean, and free of any materials that could impair adhesion.

APPLICATION METHOD / TOOLS

SikaProof® ExTape-150 is a coldapplied self-adhesive tape to securely adhere joints and overlaps as well as to execute details and connections on the membrane surface side of the SikaProof® A membrane system. SikaProof® ExTape-150 is used together with SikaProof® Tape-150 for easy, fast and secure double adhering of joints and connections. The only tool required to press the tapes firmly onto the yellow membrane surface side of the SikaProof® A membrane system is a pressure roller (i.e. Leister silicone roller). Please refer to the SikaProof® A Method Statement available at usa.sika.com for further information regarding the installation procedure.

LIMITATIONS

SikaProof® A membranes must be installed by trained and approved Sika contractors.

SikaProof® ExTape-150 are not permanently UV stabilized and therefore cannot be installed on structures or areas permanently exposed to UV light and external weathering. The maximum UV light exposure during installation or in the final stage of SikaProof® A system is 7 weeks.

Do not apply SikaProof® ExTape-150 during continuous or prolonged rainfall.

SikaProof® ExTape-150 is not suitable for use in direct contact with PVC, asphalt, hot bitumen, wood preservatives with substances containing oil, solvents or any other debonding agents.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its

subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet
SikaProof® ExTape-150
December 2018, Version 01.01
020704210220000002

SikaProofExTape-150-en-US-(12-2018)-1-1.pdf

