Revision Date 04/09/2019



#### **SECTION 1. IDENTIFICATION**

| Product name  | : | SikaQuick <sup>®</sup> Patch Part B                                |
|---|---|--|
| Company name  | : | Sika Corporation   |
|   |   | 201 Polito Avenue<br>Lyndhurst, NJ 07071<br>USA<br>www.sikausa.com |
| Telephone   | : | (201) 933-8800   |
| Telefax   | : | (201) 804-1076   |
| E-mail address  | : | ehs@sika-corp.com  |
| Emergency telephone                                     | : | CHEMTREC: 800-424-9300<br>INTERNATIONAL: 703-527-3887              |
| Recommended use of the chemical and restrictions on use | : | For further information, refer to product data sheet.              |

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### GHS classification in accordance with 29 CFR 1910.1200

| Skin corrosion  | : | Category 1C                                   |
|---|---|---|
| Serious eye damage  | : | Category 1                                    |
| Skin sensitization  | : | Category 1                                    |
| Carcinogenicity (Inhalation)  | : | Category 1A                                   |
| Specific target organ system-<br>ic toxicity - single exposure        | : | Category 3 (Respiratory system)               |
| Specific target organ system-<br>ic toxicity - repeated expo-<br>sure | : | Category 1 (Lungs)                            |
| GHS label elements  |   |   |
| Hazard pictograms   | : |   |
| Signal Word   | : | Danger  |
| Hazard Statements   | : | H314 Causes severe skin burns and eye damage. |

Revision Date 04/09/2019



|                            | H317 May cause an allergic skin reaction.<br>H335 May cause respiratory irritation.<br>H350i May cause cancer by inhalation.<br>H372 Causes damage to organs (Lungs) through prolonged or<br>repeated exposure.   |
|----------------------------|---|
| Precautionary Statements : | <ul> <li>Prevention:</li> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been read and understood.</li> <li>P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.</li> <li>P270 Do not eat, drink or smoke when using this product.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P272 Contaminated work clothing must not be allowed out of the workplace.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P281 Use personal protective equipment as required.</li> </ul>  |
|                            | <ul> <li>Response:</li> <li>P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</li> <li>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</li> <li>P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P308 + P313 IF exposed or concerned: Get medical advice/attention.</li> <li>P310 Immediately call a POISON CENTER/doctor.</li> <li>P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.</li> <li>P363 Wash contaminated clothing before reuse.</li> </ul> |
|                            | <b>Storage:</b><br>P403 + P233 Store in a well-ventilated place. Keep container<br>tightly closed.<br>P405 Store locked up.   |
|                            | <b>Disposal:</b><br>P501 Dispose of contents/ container to an approved waste disposal plant.  |
| Additional Labeling        | known acute toxicity used in a mixture at a concentration >= $1\%$  |

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### Other hazards

None known.

Revision Date 04/09/2019



#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures

#### Components

| Chemical name       | CAS-No.    | Classification   | Concentra-<br>tion (% w/w) |
|---------------------|------------|--|----------------------------|
| Quartz (SiO2)       | 14808-60-7 | Carc. 1A; H350i<br>STOT RE 1; H372<br>STOT SE 3; H335                            | >= 30 - < 50               |
| Portland cement     | 65997-15-1 | Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1; H317<br>STOT SE 3; H335 | >= 10 - < 20               |
| magnesium carbonate | 546-93-0   |  | >= 1 - < 5                 |
| calcium sulfate     | 7778-18-9  |  | >= 1 - < 5                 |

Actual concentration is withheld as a trade secret

#### SECTION 4. FIRST AID MEASURES

| General advice  | <ul> <li>Move out of dangerous area.</li> <li>Consult a physician.</li> <li>Show this material safety data sheet to the doctor in attendance.</li> </ul>  |
|---|---|
| If inhaled  | : Move to fresh air.<br>Consult a physician after significant exposure.   |
| In case of skin contact   | <ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.</li> </ul>  |
| In case of eye contact  | <ul> <li>Small amounts splashed into eyes can cause irreversible tissue damage and blindness.</li> <li>In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li> <li>Continue rinsing eyes during transport to hospital.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> </ul> |
| If swallowed  | <ul> <li>Clean mouth with water and drink afterwards plenty of water.</li> <li>Do not induce vomiting without medical advice.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>Take victim immediately to hospital.</li> </ul>  |
| Most important symptoms<br>and effects, both acute and<br>delayed | : Health injuries may be delayed.<br>corrosive effects<br>irritant effects<br>sensitizing effects   |

Revision Date 04/09/2019



|                    | carcinogenic effects<br>Prolonged exposure can cause silicosis.<br>May cause an allergic skin reaction.<br>Causes serious eye damage.<br>May cause respiratory irritation.<br>May cause cancer by inhalation.<br>Causes damage to organs through prolonged or repeated<br>exposure.<br>Causes severe burns.<br>Cough<br>Respiratory disorder<br>Allergic reactions<br>Dermatitis |
|--------------------|--|
| Notes to physician | : Treat symptomatically.   |

#### **SECTION 5. FIRE-FIGHTING MEASURES**

| Suitable extinguishing media                   | : | Use extinguishing measures that are appropriate to local cir-<br>cumstances and the surrounding environment.  |
|--|---|---|
| Further information                            | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.  |

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protec-<br>tive equipment and emer-<br>gency procedures | : | Use personal protective equipment.<br>Avoid breathing dust.<br>Deny access to unprotected persons.  |
|---|---|---|
| Environmental precautions   | : | Do not flush into surface water or sanitary sewer system.<br>If the product contaminates rivers and lakes or drains inform<br>respective authorities.<br>Local authorities should be advised if significant spillages<br>cannot be contained. |
| Methods and materials for containment and cleaning up                         | : | Pick up and arrange disposal without creating dust.<br>Keep in suitable, closed containers for disposal.  |

#### **SECTION 7. HANDLING AND STORAGE**

| Advice on protection against fire and explosion | : | Avoid dust formation.<br>Provide appropriate exhaust ventilation at places where dust is formed. |
|---|---|--|
| Advice on safe handling                         | : | Avoid formation of respirable particles.   |

Revision Date 04/09/2019



|   |   | <ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Follow standard hygiene measures when handling chemical products.</li> </ul> |
|---|---|---|
| Conditions for safe storage                   | : | Prevent unauthorized access.<br>Store in original container.<br>Keep in a well-ventilated place.<br>Observe label precautions.<br>Store in accordance with local regulations.   |
| Materials to avoid                            | : | Explosives<br>Oxidizing agents<br>Poisonous gases<br>Dangerous when wet<br>Flammable solids<br>Organic peroxides<br>Poisonous liquids<br>Spontaneously Combustible Substances   |
| Further information on stor-<br>age stability | : | Keep in a dry place.  |

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components    | CAS-No.    | Value type<br>(Form of<br>exposure)    | Control parame-<br>ters / Permissible<br>concentration | Basis    |
|---------------|------------|--|--|----------|
| Quartz (SiO2) | 14808-60-7 | TWA (Res-<br>pirable frac-<br>tion)    | 0.025 mg/m3  | ACGIH    |
|               |            | TWA (Res-<br>pirable dust)             | 0.05 mg/m3   | OSHA Z-1 |
|               |            | TWA (respir-<br>able)                  | 10 mg/m3 /<br>%SiO2+2                                  | OSHA Z-3 |
|               |            | TWA (respir-<br>able)                  | 250 mppcf /<br>%SiO2+5                                 | OSHA Z-3 |
|               |            | TWA (respir-<br>able dust<br>fraction) | 0.1 mg/m3  | OSHA P0  |
|               |            | TWA (Res-<br>pirable frac-<br>tion)    | 0.025 mg/m3<br>(Silica)                                | ACGIH    |

Revision Date 04/09/2019



|                     |            | I  |  |  |
|---------------------|------------|--|--|--|
|                     |            | TWA (respir-   | 0.1 mg/m3                                  | OSHA P0                                    |
|                     |            | able dust  |  |  |
|                     |            | fraction)  |  |  |
|                     |            | TWA (Res-  | 0.025 mg/m3                                | ACGIH                                      |
|                     |            | pirable frac-  |  |  |
|                     |            | tion)  |  |  |
|                     |            | TWA (Res-  | 0.025 mg/m3                                | ACGIH                                      |
|                     |            | pirable frac-  | (Silica)                                   |  |
|                     |            | tion)  |  |  |
| Portland cement     | 65997-15-1 | TWA (Res-  | 1 mg/m3                                    | ACGIH                                      |
|                     |            | pirable frac-  | Ŭ  |  |
|                     |            | tion)  |  |  |
|                     |            | TWA (total   | 15 mg/m3                                   | OSHA Z-1                                   |
|                     |            | dust)  | 10 1119/1110                               | 001//21                                    |
|                     |            | TWA (respir-   | 5 mg/m3                                    | OSHA Z-1                                   |
|                     |            | able fraction)   | 5 mg/m5                                    | 0317 2-1                                   |
|                     |            |  |  | OSHA P0                                    |
|                     |            | TWA (Total   | 10 mg/m3                                   | USHA PU                                    |
|                     |            | dust)  | - / -                                      | 0.0114 50                                  |
|                     |            | TWA (respir-   | 5 mg/m3                                    | OSHA P0                                    |
|                     |            | able dust  |  |  |
|                     |            | fraction)  |  |  |
|                     |            | TWA (Dust)   | 50 Million parti-                          | OSHA Z-3                                   |
|                     |            |  | cles per cubic foot                        |  |
|                     |            | TWA (Total)  | 10 mg/m3                                   | OSHA P0                                    |
|                     |            | TWA (Res-  | 5 mg/m3                                    | OSHA P0                                    |
|                     |            | pirable frac-  |  |  |
|                     |            | tion)  |  |  |
| magnesium carbonate | 546-93-0   | TWA (total   | 15 mg/m3                                   | OSHA Z-1                                   |
| 5                   |            | dust)  | 5  |  |
|                     |            | TWA (respir-   | 5 mg/m3                                    | OSHA Z-1                                   |
|                     |            | able fraction)   | o  |  |
|                     |            |  |  |  |
|                     |            | TWA (Total   | 15 ma/m3                                   | OSHA PO                                    |
|                     |            | TWA (Total   | 15 mg/m3                                   | OSHA P0                                    |
|                     |            | dust)  |  |  |
|                     |            | dust)<br>TWA (respir-  | 15 mg/m3<br>5 mg/m3                        | OSHA P0<br>OSHA P0                         |
|                     |            | dust)<br>TWA (respir-<br>able dust   |  |  |
|                     | 7770.40.0  | dust)<br>TWA (respir-<br>able dust<br>fraction)  | 5 mg/m3                                    | OSHA P0                                    |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total  |  |  |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)   | 5 mg/m3<br>15 mg/m3                        | OSHA P0<br>OSHA Z-1                        |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-   | 5 mg/m3                                    | OSHA P0                                    |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-<br>able fraction)   | 5 mg/m3<br>15 mg/m3<br>5 mg/m3             | OSHA P0<br>OSHA Z-1<br>OSHA Z-1            |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-<br>able fraction)<br>TWA (Total                                       | 5 mg/m3<br>15 mg/m3                        | OSHA P0<br>OSHA Z-1                        |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-<br>able fraction)<br>TWA (Total<br>dust)                              | 5 mg/m3<br>15 mg/m3<br>5 mg/m3<br>15 mg/m3 | OSHA P0<br>OSHA Z-1<br>OSHA Z-1<br>OSHA P0 |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-<br>able fraction)<br>TWA (Total                                       | 5 mg/m3<br>15 mg/m3<br>5 mg/m3             | OSHA P0<br>OSHA Z-1<br>OSHA Z-1            |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-<br>able fraction)<br>TWA (Total<br>dust)                              | 5 mg/m3<br>15 mg/m3<br>5 mg/m3<br>15 mg/m3 | OSHA P0<br>OSHA Z-1<br>OSHA Z-1<br>OSHA P0 |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-<br>able fraction)<br>TWA (Total<br>dust)<br>TWA (respir-              | 5 mg/m3<br>15 mg/m3<br>5 mg/m3<br>15 mg/m3 | OSHA P0<br>OSHA Z-1<br>OSHA Z-1<br>OSHA P0 |
| calcium sulfate     | 7778-18-9  | dust)<br>TWA (respir-<br>able dust<br>fraction)<br>TWA (total<br>dust)<br>TWA (respir-<br>able fraction)<br>TWA (Total<br>dust)<br>TWA (respir-<br>able dust | 5 mg/m3<br>15 mg/m3<br>5 mg/m3<br>15 mg/m3 | OSHA P0<br>OSHA Z-1<br>OSHA Z-1<br>OSHA P0 |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Particles of nuisance dust

Print Date 04/09/2019

Revision Date 04/09/2019

| Form of exposure                           |                        | Value type   | Control parameters  | Basis                                       |
|--|------------------------|--|---|---|
| total dust                                 |                        | TWA  | 50Million particles<br>per cubic foot   | OSHA Z-3                                    |
| total dust                                 |                        | TWA  | 15 mg/m3  | OSHA Z-3                                    |
| respirable fraction<br>respirable fraction |                        | TWA  | 5 mg/m3   | OSHA Z-3                                    |
|  |                        | TWA  | 15Million particles<br>per cubic foot   | OSHA Z-3                                    |
| Engineering measures                       | r<br>c<br>ii           | vorker exposure to ai<br>product generates du<br>cess enclosures, loca   | ilation should be sufficient t<br>rborne contaminants. If the<br>st, fumes, gas, vapor or mis<br>I exhaust ventilation or othe<br>orker exposure below any i  | use of this<br>st, use pro-<br>er engineer- |
| Personal protective equip                  | ment                   |  |   |   |
| Respiratory protection                     | r<br>s<br>ii<br>(<br>c | espirator complying v<br>sessment indicates th<br>The filter class for the<br>mum expected conta<br>gas/vapor/aerosol/pa<br>lling the product. If th | VIOSH approved air-purifyir<br>with an approved standard i<br>is is necessary.<br>respirator must be suitable<br>minant concentration<br>irticulates) that may arise w<br>is concentration is exceede<br>pparatus must be used. | f a risk as-<br>for the max-<br>hen han-    |
| Hand protection<br>Remarks                 | a<br>C                 | approved standard sh   | npervious gloves complying<br>ould be worn at all times w<br>risk assessment indicates  | hen handling                                |
| Eye protection                             |                        | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.                                |   |   |
| Skin and body protection                   | t                      |  | on in relation to its type, to t<br>dangerous substances, and   |   |
| Hygiene measures                           | V<br>ti<br>F<br>b      | Vash hands before b<br>he product.   |   | -   |

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### Revision Date 04/09/2019



| Appearance  | : | powder                        |
|---|---|-------------------------------|
| Color   | : | gray                          |
| Odor  | : | odorless                      |
| Odor Threshold                                      | : | No data available             |
| рН  | : | Not applicable                |
| Melting point/range / Freezing point                | : | No data available             |
| Boiling point/boiling range                         | : | No data available             |
| Flash point   | : | Not applicable                |
| Evaporation rate                                    | : | No data available             |
| Flammability (solid, gas)                           | : | No data available             |
| Upper explosion limit / Upper<br>flammability limit | : | No data available             |
| Lower explosion limit / Lower flammability limit    | : | No data available             |
| Vapor pressure                                      | : | No data available             |
| Relative vapor density                              | : | No data available             |
| Density   | : | ca. 2.3 g/cm3 (73 °F / 23 °C) |
| Solubility(ies)<br>Water solubility                 | : | insoluble                     |
| Solubility in other solvents                        | : | No data available             |
| Partition coefficient: n-<br>octanol/water          | : | No data available             |
| Autoignition temperature                            | : | No data available             |
| Decomposition temperature                           | : | No data available             |
| Viscosity<br>Viscosity, dynamic                     | : | No data available             |
| Viscosity, kinematic                                | : | Not applicable                |
| Explosive properties                                | : | No data available             |
| Oxidizing properties                                | : | No data available             |

Revision Date 04/09/2019



Volatile organic compounds : 2 g/l (VOC) content A+B Combined

#### SECTION 10. STABILITY AND REACTIVITY

| Reactivity                              | : | No dangerous reaction known under conditions of normal use. |
|---|---|---|
| Chemical stability                      | : | The product is chemically stable.                           |
| Possibility of hazardous reac-<br>tions | : | Stable under recommended storage conditions.                |
| Conditions to avoid                     | : | No data available   |
| Incompatible materials                  | : | No data available   |

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### **Components:**

#### calcium sulfate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

#### Skin corrosion/irritation

Causes severe burns.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

May cause cancer by inhalation.

| IAŔC | Group 1: Carcinogenic to humans |            |
|------|---------------------------------|------------|
|      | Quartz (SiO2)                   | 14808-60-7 |
|      | (Silica dust, crystalline)      |            |

**OSHA** Not applicable

#### Revision Date 04/09/2019

NTP



14808-60-7

### Reproductive toxicity

Not classified based on available information.

Quartz (SiO2)

Known to be human carcinogen

(Silica, Crystalline (Respirable Size))

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure. Prolonged exposure can cause silicosis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Aspiration toxicity

Not classified based on available information.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

#### **SECTION 12. ECOLOGICAL INFORMATION**

| <b>Ecotoxicity</b><br>No data available                   |  |
|---|--|
| <b>Persistence and degradability</b><br>No data available |  |
| <b>Bioaccumulative potential</b><br>No data available     |  |
| <b>Mobility in soil</b><br>No data available              |  |
| Other adverse effects                                     |  |
| Product:<br>Additional ecological infor- :<br>mation      | Do not empty into drains; dispose of this material and its con-<br>tainer in a safe way. |

#### SECTION 13. DISPOSAL CONSIDERATIONS

| Disposal methods       |   |   |
|------------------------|---|---|
| Waste from residues    | : | Disposal of this product, solutions and any by-products should<br>at all times comply with the requirements of environmental<br>protection and waste disposal legislation and any regional<br>local authority requirements. |
| Contaminated packaging | : | Empty containers should be taken to an approved waste han-  |

Revision Date 04/09/2019



#### dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

IATA-DGR Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### **Domestic regulation**

**49 CFR** Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

#### TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

#### EPCRA - Emergency Planning and Community Right-to-Know

#### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

 $\mathbb{A}$ 

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

| SARA 311/312 Hazards : | Skin corrosion or irritation<br>Serious eye damage or eye irritation<br>Respiratory or skin sensitization<br>Carcinogenicity<br>Specific target organ toxicity (single or repeated exposure) |
|------------------------|--|
| SARA 313 :             | This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.            |

#### **Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**California Prop 65** 

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Revision Date 04/09/2019



#### **SECTION 16. OTHER INFORMATION**

| ons |   |
|-----|---|
| :   | USA. ACGIH Threshold Limit Values (TLV)   |
| :   | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000                         |
| :   | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-<br>its for Air Contaminants |
| :   | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts                    |
| :   | 8-hour, time-weighted average   |
| :   | 8-hour time weighted average  |
| :   | 8-hour time weighted average  |
| :   | 8-hour time weighted average  |
|     | ::  |

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 04/09/2019

10000015425

US / Z8