

Sikaflex®-102 EverFlash Membrane

LIQUID FLASHING FOR DOOR AND WINDOW ROUGH OPENINGS

- For a complete system use Sikaflex WS-295, Skaflex 15LM, Sikaflex 2c, Sikaflex 1a, and SikaHyflex 150 LM as the window perimeter sealant
- All-in-one joint flashing adhesive, joint and seam filler
- Excellent long term weathering
- Fast skin time allows window sealant placement in 2 hours
- Window replacements completed same day

Packaging available 20 fl.oz. Unipack (600ml)





Sikaflex®-102 EverFlash Membrane LIQUID FLASHING FOR DOOR AND WINDOW ROUGH OPENINGS

WHERE TO USE

- Floor moldings and door sills
- Wood or metal window and door frames
- Seal exterior perimeter of window nailing flanges
- CMU, poured in place or precast concrete
- Sheathing joints
- Gaskets at openings in walls or floors for ducts, piling, etc.
- Sealing perimeter rough openings of wall penetrations

FEATURES AND BENEFITS

- Excellent weathering and water resistance
- Good UV Stability
- Non-corrosive, Non-Staining, Non-Shrinking
- Can be used for multiple situations (static cracks less than 34", 90° details, sealing fasteners, buck embedment & flashing)

- High durability
- Excellent unprimed adhesion on all cement-based materials, brick, ceramics, glass, metals, wood, epoxy, polyester and acrylic resin
- Can be used with direct applied stucco applications
- Single source system warranty available when used in cojunction with Sikaflex, SikaHyflex or Sikasil weatherseal or perimeter sealants, Sikagard Air Barrier Systems, or Sika BMI Stucco Systems
- Can be painted over with water, oil, and rubber-based paints. (Preliminary tests recommended)
- Fast Cure system (can apply perimeter sealant in as quickly as 2 hours)
- Allows for same day installation of windows and doors

*Always refer to Current Product data Sheet and SDS for detailed performance specifications prior to use.





FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.usa.sika.com

Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071 Phone: 201-933-8800

