

Sikaflex® 2cNS Fact Sheet Premium-grade, two-part polyurethane

sealant mortar



Product Information

Professional-grade, two-part polyurethane sealant

APPLICATIONS

- ▲ Buidling facades
- ▲ Balconies
- ▲ Parking structures
- ▲ Civil structures
- ▲ Plazas
- Barrier walls

ADVANTAGES

- ▲ Easy to mix
- ▲ Long pot life
- ▲ Excellent adhesion
- ▲ Potable Water
- ▲ Creamy consistency
- ▲ Easy to tool
- ▲ Fast cure
- Excellent resistance to weathering
- ▲ Water immersible
- Color versatility
- ▲ Non-sag, self-levelling, and traffic grades available
- ▲ Pre-pigmented limestone color available (no Color-pak)

KEY DATA

- ▲ Pot life at 73 F 3+ hours ▲ Pot life at 95 F 2+ hours ▲ Final cure 3 days +/- 50% ▲ Joint movement 650% ▲ Elongation
- ▲ Service range -40 F to 170 F ▲ Specification conformance ASTM C 920;

Federal specifications TT-S-00227E; CRD C 506

- ▲ Sealant, Waterproofing and Restoration Institute (SWRI) certified
- ▲ Meets ASTM C-920, Type M, Grade NS, Class 25, use T, NT, M, G, A, O and Federal Specification TT-S-00227E, Type II, Class A. Meets CAN/CGSB 19.24 - M90
- ▲ NSF certified to ANSI/NSF 60 approval for contact with potable water







Packaged in 2-gallon pails which includes catalyst. Yield-1.5 gallons. Color-paks and traffic grade components added separately. Special order-3 gallon units.







SIKA CORPORATION

201 Polito Avenue Lyndhurst, NJ 07071 Phone: 201.933.8800 Fax: 201.933.6225 Toll Free: 800.933.SIKA Fax: 514.694.2792 usa.sika.com

SIKA CANADA INC.

601 Delmar Avenue Pointe Claire Ouebec H9R 4A9 Phone: 514.697.2610

SIKA MEXICANA S.A. DE C.V.

Carretera Libre Celaya Km. 8.5 Fracc. Industrial Balvanera Corregidora, Queretaro C.P. 76920

Phone: 52.442.238.5800 Fax: 52.442.225.0537

