



Sikaflex[®] Mortar Fix

One-component, textured polyurethane sealant



A moisture-cured, 1-component, polyurethane- based, non-sag elastomeric sealant capable of $\pm 25\%$ joint movement. Meets Federal specification TT-S-00230C, Type II. Meets ASTM C-920, Type S, Grade NS. Ideal for weatherproofing of joints between brickwork, blockwork, masonry, concrete or metal frames.



Advantages

- Permanently elastic & non-stainig
- Textured for mortar appearance
- Will not shrink or crack
- Paintable, stainable, sandable
- Waterproof & water immersible after cure
- Super adhesion and durability
- Hides imperfections unlike smooth sealants

Typical Data

Shelf Life : 1 year in original unopened packaging

Storage Conditions : Store at 40°-95°F (4°-35°C).

Condition material to 65°-75°F (18°-24°C) before using.

Color : Textured Gray

Application Temperature : -40°F -100°F .

Sealant should be installed when joint is at midrange of its anticipated movement.

Service Range : -40° to 170°F.

Curing Rate : Tack-free time : <5 hrs. Final cure : 7 days

Shore A Hardness : 35 \pm 5

Adhesion in Peel (ASTM C-794) :

Concrete : Meets ASTM C-920

Aluminium : Meets ASTM C-920

Glass : Meets ASTM C-920

Weathering Resistance : Excellent

Chemical Resistance : Good resistance to water, diluted acids, and diluted alkalines.

Consult Technical Service for specific data



SIKA CORPORATION
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225
Toll Free : 800.933.SIKA
usa.sika.com

SIKA CANADA INC.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

SIKA MEXICANA S.A. DE C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

BUILDING TRUST

