

Sikaflex Remover

Fast drying solvent cleaner

Description Aliphatic petroleum distillate cleaner for use with Sikaflex® products.

Where to Use For removal of cured and uncured Sikaflex® polyurethane sealants and adhesives, where a cleaner is needed.

Advantages

- Ideal for Sikaflex® polyurethane sealants and adhesives, during and soon after curing (1 to 2 days).
- Does not leave “ghosting” on wood floor finish
- Leaves no residue
- Low odor
- Fast drying

Areas of Application Wood floors, Tile Floors, Walls, Pastics, Glass, etc.

Packaging 16oz bottles (1 pint); 6 per case

Application Details

Method Use full strength on a dry surface. Apply sparingly to the surface or apply to a rag/ sponge and wipe on. Agitate with a rag or non-abrasive scrub pad to remove contaminants. Wipe dry or allow to dry by natural air convection. No rinse needed. Wear chemical resistant gloves, eye protection and clothing.

Limitations

- Test first, especially on plastics, painted surfaces, rubber and other sensitive substrates. This will prevent any damage.
- For most effective clean up, use Sikaflex® Remover before Sikaflex® product is fully cured.

Storage Store dry at 40°-95°F (4°-35°C)

Product Shelf Life 2 years



Use: Full strength on a dry surface. Apply sparingly to the surface or apply to a rag/sponge and wipe on. Agitate with a rag or non-abrasive scrub pad to remove contaminants. Wipe dry or allow to dry by natural air convection. No rinse needed.

Limitations: Test first, especially on plastics, painted surfaces, rubber and other sensitive substrates. Danger Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled. Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to an approved waste disposal plant. Contains: Stoddard solvent (CAS:8052-41-3).



Sale of Sika products are subject to Sika's Terms and Conditions of Sale available at <http://usa.sika.com/> or by calling 201-933-8800.

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

VOC: 770 g/l. (exempt According to SCAQMD's Rule Paragraph 1171.(g)(2)(G))

HMIS: *3, 2, 0, X.

Store dry at 40°-95°F (4°-35°C)

www.usa.sika.com

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at www.sikausa.com or by calling 800-933-7452.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at usa.sika.com/retail or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.

LIMITED WARRANTY: Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKASHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Visit our website at usa.sika.com

1-800-933-SIKA NATIONWIDE

Regional Information and Sales Centers. For the location of your nearest Sika sales office, contact your regional center.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225

Sika Canada Inc.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



RESPONSIBLE CARE
OUR COMMITMENT TO EXCELLENCE



Sika and Sikacryl are registered trademarks.
Made in the USA.