



Sikagard® High Gloss Sealer

Acrylic surface sealer



An acrylic sealer for concrete and masonry that dries to a clear, glossy finish and provides protection against moisture and mild corrosives. Ideal for retaining walls.



Advantages

- Roll, brush or spray applied
- Improves dirt resistance
- Protects from mild corrosives
- Protects from de-icing salts
- Adds sheen to surface appearance
- Keeps substrates looking new longer

Typical Data

Shelf Life : 1 year in original unopened packaging

Storage Conditions : Store dry at 45°-90°F (7°-32°C). Keep from freezing.
Condition material to 65-75F (18-24C) before using.

Color : White (dries clear)

VOC : 41 g/l

Dry Time : Approximately 4-8 hrs. Wait 24 hrs. before exposing to foot/car traffic.
Approximately 72 hrs. for maximum water repellency, depending on surface



SIKA CORPORATION
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225
Toll Free : 800.933.SIKA
usa.sika.com

SIKA CANADA INC.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

SIKA MEXICANA S.A. DE C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

BUILDING TRUST

