

# Sikagard® Natural Look Clear Sealer

## Water-repellent sealer

<b>Description</b>	Sikagard Natural Look Sealer is a commercial grade water repellent sealer that penetrates an absorbent surface to form a seal against the elements, such as water and chlorides. on concrete, masonry, mortar, brick and stone. Penetrates surface to form a seal against the elements such as water and chlorides, which can cause freeze thaw damage to the surface. Will not change the surface appearance and resists the growth of fungi and moss.
<b>Where To Use</b>	Sikagard Natural Look Sealer water repellent sealer can be used on concrete, masonry, mortar, brick and stone.
<b>Advantages</b>	<ul style="list-style-type: none"><li>■ Will not alter the appearance of your surface</li><li>■ Improves resistance to dirt penetration</li><li>■ Resistant to mold and fungus</li><li>■ For vertical and horizontal applications</li><li>■ Protects against freeze-thaw damage</li></ul>
<b>Coverage</b>	1 gallon jug covers 100 – 250 sq. ft, depending on porosity of substrate.
<b>Packaging</b>	1 gallon jug
<b>How to Use</b>	
<b>Surface Preparation</b>	Surface must be clean, sound, dust-free and dry. Remove all dust, dirt, loose concrete, grease, curing compounds, paint and other particles by mechanical means (i.e. pressure wash, blast clean, etc.).
<b>Mixing</b>	Shake product thoroughly before applying.
<b>Application</b>	Apply to surface by brushing, rolling or spraying over entire area moving in one direction uniformly. Avoid puddling of product in any area. A maximum of two coats may be required, depending on porosity of surface. Recommended application temperature is 45°-95°F (7°-35°C) ambient and substrate. <b>Note:</b> Preliminary site test application is recommended (preferably on a small, prepped, inconspicuous surface) to determine satisfactory appearance and surface slip resistance.
<b>Limitations</b>	<ul style="list-style-type: none"><li>■ Substrate must be dry prior to application (minimum 48 hrs)</li><li>■ Do not apply if rain is in the forecast (48 hrs. prior to or after application)</li><li>■ Cannot seal visible cracks. Repair all cracks or surface defects before sealing.</li><li>■ Do not use on concrete under 7 days old</li><li>■ Avoid puddling; apply even coats</li><li>■ Do not attempt to build up thickness</li><li>■ Does not contain a antimicrobial additive</li><li>■ Not recommended for stained concrete</li><li>■ For outdoor use only</li><li>■ To penetrate denser surfaces, rinsing surface off with water may be necessary</li></ul>

### Typical Data (Material and curing conditions at 73°F (23°C) and 50% R.H.)

<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	Store dry at 45°-90°F (7-32°C). Keep from freezing. Condition material to 65-75°F (18-24°C) before using.
<b>Color</b>	Milky white when applied but dries clear
<b>VOC</b>	39 g/l
<b>Dry Time</b>	Approximately 4-8 hrs, depending on temperature. Wait 24 hrs. before exposing to foot/car traffic. Approximately 72 hrs. for maximum water repellency, depending on surface and atmospheric conditions.

Residential



# Residential

## Health & Safety

Not a hazardous substance or mixture. Contains: Silane, triethoxyoctyl (CAS: 2943-75-1). This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

**HMIS:** 1, 1, 0, X. **VOC:** 39 g/l.

Wash skin thoroughly after handling. Use personal protective equipment as required. IF INHALED: Move to fresh air. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. If eye irritation persists: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash before reuse.



**Sika**®

### KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at [www.sikausa.com](http://www.sikausa.com) or by calling 800-933-7452.

**Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available online at [www.sikausa.com](http://www.sikausa.com) or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.**

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALLNOTBELIABLEUNDERANYLEGALTHEORYFORSPECIALORCONSEQUENTIALDAMAGES.SIKASHALLNOTBERESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Visit our website at [www.sikausa.com](http://www.sikausa.com)

1-800-933-SIKA NATIONWIDE

**Regional Information and Sales Centers.** For the location of your nearest Sika sales office, contact your regional center.

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 800-933-7452  
Fax: 201-933-6225

**Sika Canada Inc.**  
601 Delmar Avenue  
Pointe Claire  
Quebec H9R 4A9  
Phone: 514-697-2610  
Fax: 514-694-2792

**Sika Mexicana S.A. de C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



RESPONSIBLE CARE  
FOR ENVIRONMENT & SOCIETY



Sika and Sikagard are registered trademarks.  
Made in the USA.