



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

### SECTION 1. IDENTIFICATION

Product name : Sikalastic® Clearglaze

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Eye irritation : Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 1B

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

Aspiration hazard : Category 1

#### GHS label elements



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H360 May damage fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements

:

### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P284 Wear respiratory protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

| Chemical name                                                              | CAS-No.    | Classification                                                                                               | Concentration (% w/w) |
|----------------------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------------------------|-----------------------|
| solvent naphtha (petroleum), light arom.                                   | 64742-95-6 | Flam. Liq. 3; H226<br>STOT SE 3; H335, H336<br>Asp. Tox. 1; H304                                             | $\geq 20 - < 30$      |
| Isophorondiisocyanate homopolymer                                          | 53880-05-0 | Skin Sens. 1B; H317<br>STOT SE 3; H335                                                                       | $\geq 10 - < 20$      |
| Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexane- 1,2-diylbiscarbamate | 59719-67-4 | Eye Irrit. 2A; H319<br>Skin Sens. 1B; H317                                                                   | $\geq 10 - < 20$      |
| xylene                                                                     | 1330-20-7  | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319 | $\geq 1 - < 5$        |



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

|                                                         |            |                                                                                                                               |              |
|---------------------------------------------------------|------------|-------------------------------------------------------------------------------------------------------------------------------|--------------|
|                                                         |            | STOT SE 3; H335<br>STOT RE 2; H373<br>Asp. Tox. 1; H304                                                                       |              |
| 1,2,4-trimethylbenzene                                  | 95-63-6    | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>STOT SE 3; H335                     | >= 1 - < 5   |
| ethylbenzene                                            | 100-41-4   | Flam. Liq. 2; H225<br>Acute Tox. 4; H332<br>STOT RE 2; H373<br>Asp. Tox. 1; H304<br>Eye Irrit. 2A; H319                       | >= 1 - < 5   |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9  | Acute Tox. 1; H330<br>Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>STOT SE 3; H335 | >= 0.1 - < 1 |
| Pentamethyl piperidylsebacate                           | 41556-26-7 | Skin Sens. 1A; H317<br>Repr. 2; H361                                                                                          | >= 0.1 - < 1 |
| Dibutyltin dilaurate                                    | 77-58-7    | Eye Irrit. 2A; H319<br>Skin Sens. 1; H317<br>Muta. 2; H341<br>Repr. 1B; H360<br>STOT SE 1; H370<br>STOT RE 1; H372            | >= 0.1 - < 1 |

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

|                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                             | Never give anything by mouth to an unconscious person.<br>Take victim immediately to hospital.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Most important symptoms and effects, both acute and delayed | : Risk of serious damage to the lungs (by aspiration).<br>irritant effects<br>sensitizing effects<br>toxic effects for reproduction<br>Aspiration may cause pulmonary edema and pneumonitis.<br>Asthmatic appearance<br>Cough<br>Respiratory disorder<br>Allergic reactions<br>Excessive lachrymation<br>Loss of balance<br>Vertigo<br>May be fatal if swallowed and enters airways.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br>May cause respiratory irritation.<br>May cause drowsiness or dizziness.<br>May damage fertility or the unborn child.<br>May cause damage to organs through prolonged or repeated exposure if inhaled. |
| Notes to physician                                          | : Treat symptomatically.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

---

### SECTION 5. FIRE-FIGHTING MEASURES

|                                                |                                                                                                                                                                                                                                                                           |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                   | : Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical                                                                                                                                                                                             |
| Unsuitable extinguishing media                 | : Water<br>High volume water jet                                                                                                                                                                                                                                          |
| Specific hazards during fire fighting          | : Do not use a solid water stream as it may scatter and spread fire.                                                                                                                                                                                                      |
| Further information                            | : Use water spray to cool unopened containers.<br>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.                                                                                                                                                                                                          |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

- |                                                                     |   |                                                                                                                                                                                                                                 |
|---------------------------------------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Remove all sources of ignition.<br>Deny access to unprotected persons.<br>Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.             |
| Environmental precautions                                           | : | Prevent product from entering drains.<br>If the product contaminates rivers and lakes or drains inform respective authorities.<br>Local authorities should be advised if significant spillages cannot be contained.             |
| Methods and materials for containment and cleaning up               | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

---

### SECTION 7. HANDLING AND STORAGE

- |                                                 |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advice on protection against fire and explosion | : | Use explosion-proof equipment.<br>Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.<br>Take precautionary measures against electrostatic discharges.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Advice on safe handling                         | : | Avoid formation of aerosol.<br>Do not breathe vapors or spray mist.<br>Avoid exceeding the given occupational exposure limits (see section 8).<br>Do not get in eyes, on skin, or on clothing.<br>For personal protection see section 8.<br>Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Take precautionary measures against static discharge.<br>Open drum carefully as content may be under pressure.<br>Pregnant women or women of child-bearing age should not be exposed to this product.<br>Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).<br>Follow standard hygiene measures when handling chemical products. |
| Conditions for safe storage                     | : | Store in original container.<br>Keep in a well-ventilated place.<br>Containers which are opened must be carefully resealed and kept upright to prevent leakage.<br>Observe label precautions.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

Store in accordance with local regulations.

Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Poisonous liquids

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components                                              | CAS-No.    | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis    |
|---------------------------------------------------------|------------|----------------------------------|------------------------------------------------|----------|
| solvent naphtha (petroleum), light arom.                | 64742-95-6 | TWA                              | 500 ppm<br>2,000 mg/m <sup>3</sup>             | OSHA Z-1 |
|                                                         |            | TWA                              | 400 ppm<br>1,600 mg/m <sup>3</sup>             | OSHA P0  |
| xylene                                                  | 1330-20-7  | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA Z-1 |
|                                                         |            | TWA                              | 20 ppm                                         | ACGIH    |
|                                                         |            | STEL                             | 150 ppm<br>655 mg/m <sup>3</sup>               | OSHA P0  |
|                                                         |            | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA P0  |
| 1,2,4-trimethylbenzene                                  | 95-63-6    | TWA                              | 25 ppm                                         | ACGIH    |
|                                                         |            | TWA                              | 25 ppm<br>125 mg/m <sup>3</sup>                | OSHA P0  |
|                                                         |            | TWA                              | 10 ppm                                         | ACGIH    |
| ethylbenzene                                            | 100-41-4   | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA Z-1 |
|                                                         |            | TWA                              | 100 ppm<br>435 mg/m <sup>3</sup>               | OSHA P0  |
|                                                         |            | STEL                             | 125 ppm<br>545 mg/m <sup>3</sup>               | OSHA P0  |
|                                                         |            | TWA                              | 20 ppm                                         | ACGIH    |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9  | TWA                              | 0.005 ppm                                      | OSHA P0  |
|                                                         |            | STEL                             | 0.02 ppm                                       | OSHA P0  |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

### Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : colorless
- Odor : characteristic
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

|                                                  |                                          |
|--------------------------------------------------|------------------------------------------|
| Flash point                                      | : 104 °F / 40 °C<br>(Method: closed cup) |
| Evaporation rate                                 | : No data available                      |
| Flammability (solid, gas)                        | : No data available                      |
| Upper explosion limit / Upper flammability limit | : 7 %(V)                                 |
| Lower explosion limit / Lower flammability limit | : 0.8 %(V)                               |
| Vapor pressure                                   | : 7.9993 hpa                             |
| Relative vapor density                           | : No data available                      |
| Density                                          | : ca. 1 g/cm3 (68 °F / 20 °C)            |
| Solubility(ies)                                  |                                          |
| Water solubility                                 | : insoluble                              |
| Solubility in other solvents                     | : No data available                      |
| Partition coefficient: n-octanol/water           | : No data available                      |
| Autoignition temperature                         | : > 842 °F / > 450 °C                    |
| Decomposition temperature                        | : No data available                      |
| Viscosity                                        |                                          |
| Viscosity, dynamic                               | : No data available                      |
| Viscosity, kinematic                             | : > 7 mm2/s (104 °F / 40 °C)             |
| Explosive properties                             | : No data available                      |
| Oxidizing properties                             | : No data available                      |
| Volatile organic compounds (VOC) content         | : 360 g/l                                |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |                                                                                               |
|------------------------------------|-----------------------------------------------------------------------------------------------|
| Reactivity                         | : No dangerous reaction known under conditions of normal use.                                 |
| Chemical stability                 | : The product is chemically stable.                                                           |
| Possibility of hazardous reactions | : Stable under recommended storage conditions.<br>Vapors may form explosive mixture with air. |
| Conditions to avoid                | : Heat, flames and sparks.                                                                    |



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

Incompatible materials : No data available

Hazardous decomposition products : No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

##### **Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexane- 1,2-diylbiscarbamate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

##### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

##### **ethylbenzene:**

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

##### **3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Acute oral toxicity : LD50 Oral (Rat): 4,814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.031 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

##### **Dibutyltin dilaurate:**

Acute oral toxicity : LD50 Oral (Rat): 2,071 mg/kg

#### **Skin corrosion/irritation**

Not classified due to lack of data.



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

|             |                                                           |          |
|-------------|-----------------------------------------------------------|----------|
| <b>IARC</b> | Group 2B: Possibly carcinogenic to humans<br>ethylbenzene | 100-41-4 |
|-------------|-----------------------------------------------------------|----------|

|             |                |
|-------------|----------------|
| <b>OSHA</b> | Not applicable |
|-------------|----------------|

|            |                |
|------------|----------------|
| <b>NTP</b> | Not applicable |
|------------|----------------|

### Reproductive toxicity

May damage fertility or the unborn child.

### STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### Aspiration toxicity

May be fatal if swallowed and enters airways.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **solvent naphtha (petroleum), light arom.:**

|                                  |   |                                                                 |
|----------------------------------|---|-----------------------------------------------------------------|
| Toxicity to algae/aquatic plants | : | (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9 mg/l |
|----------------------------------|---|-----------------------------------------------------------------|

#### **Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexane- 1,2-diylbiscarbamate:**

|                                                     |   |                                                                     |
|-----------------------------------------------------|---|---------------------------------------------------------------------|
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 87.1 mg/l<br>Exposure time: 48 h |
|-----------------------------------------------------|---|---------------------------------------------------------------------|



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 18.6 mg/l  
Exposure time: 72 h

### **xylene:**

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia): 1.17 mg/l  
Exposure time: 7 d

### **Dibutyltin dilaurate:**

Toxicity to fish : LC50 (Fish): 3.1 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1 - 10 mg/l  
Exposure time: 72 h

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

#### **Product:**

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.

---

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : Paint related material  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
(solvent naphtha)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

#### Domestic regulation

##### 49 CFR

UN/ID/NA number : UN 1263  
Proper shipping name : Paint related material  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

DOT: For Limited Quantity exceptions reference 49 CFR 173.150 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

### SECTION 15. REGULATORY INFORMATION



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### CERCLA Reportable Quantity

| Components | CAS-No.   | Component RQ (lbs) |
|------------|-----------|--------------------|
| xylene     | 1330-20-7 | 100                |

### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Respiratory or skin sensitization  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

|                        |           |              |
|------------------------|-----------|--------------|
| xylene                 | 1330-20-7 | >= 1 - < 5 % |
| 1,2,4-trimethylbenzene | 95-63-6   | >= 1 - < 5 % |
| ethylbenzene           | 100-41-4  | >= 1 - < 5 % |

### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

|              |           |              |
|--------------|-----------|--------------|
| xylene       | 1330-20-7 | >= 1 - < 5 % |
| ethylbenzene | 100-41-4  | >= 1 - < 5 % |

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including ethylbenzene, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16. OTHER INFORMATION

Full text of other abbreviations



## Sikalastic® Clearglaze

Revision Date 08/09/2023

Print Date 08/09/2023

|                |   |                                                                                  |
|----------------|---|----------------------------------------------------------------------------------|
| ACGIH          | : | USA. ACGIH Threshold Limit Values (TLV)                                          |
| OSHA P0        | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)               |
| OSHA Z-1       | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| ACGIH / TWA    | : | 8-hour, time-weighted average                                                    |
| OSHA P0 / TWA  | : | 8-hour time weighted average                                                     |
| OSHA P0 / STEL | : | Short-term exposure limit                                                        |
| OSHA Z-1 / TWA | : | 8-hour time weighted average                                                     |

### **Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 08/09/2023

000000605169  
US / Z8