

## PRODUCT DATA SHEET

# Sarnabar® stainless steel

---

SARNABAR IS A HEAVY-DUTY, 'U'-SHAPED, ROLL-FORMED BAR

---

### PRODUCT DESCRIPTION

Sarnabar® stainless steel is a heavy-duty, 'U'-shaped, roll-formed stainless steel bar used to secure the waterproofing membrane at the base of walls, transitions, and penetrations.

### USES

Used with Sarnafasteners® to clamp membrane to the roof deck in Mechanically Attached, Ballasted, or Adhered roof systems.

#### Areas of Application

- Hurricane Prone Areas
- Additional Enhancement

### CHARACTERISTICS / ADVANTAGES

- Easy to install

## PRODUCT INFORMATION

<b>Packaging</b>	<ul style="list-style-type: none"><li>▪ Individual</li><li>▪ 10 per bundle</li></ul>
<b>Appearance / Color</b>	Gray
<b>Shelf Life</b>	N/A
<b>Storage Conditions</b>	N/A
<b>Dimensions</b>	Length: 10' (3.05 m) Width: 1" (25 mm) Thickness: 0.0785" (2 mm) Weight: 4.7 lb. (2.13 kg)

## APPLICATION INSTRUCTIONS

### APPLICATION

Sarnabars SS is normally mechanically attached through the waterproofing membrane as close to the base of the walls, curbs, transitions and penetrations as possible. The Sarnabar and fasteners effectively clamp the membrane to the substrate or the structural deck.

### MAINTENANCE

Standard maintenance of roofs should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

## AVAILABILITY/WARRANTY

### Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

### Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



### Product Data Sheet

Sarnabar® stainless steel  
February 2020, Version 04.02  
020945051100000005

Sarnabarstainlesssteel-en-US-(02-2020)-4-2.pdf

