

PRODUCT DATA SHEET

Sarnafil® Decor Profile (US)

SARNAFIL DECOR PROFILE IS A PVC EXTRUDED ACCESSORY

PRODUCT DESCRIPTION

Sarnafil® Decor Profile (US) is a durable, PVC extruded accessory designed to emulate the appearance of a standing seam metal rib, with heat weldable flanges for securement onto a Sarnafil® Membrane.

USES

Standing seam metal alternative.

Areas of Application

- Domed Roofs
- Pitched Roofs
- Flat Roofs

CHARACTERISTICS / ADVANTAGES

- Color Match to Sarnafil® Membrane
- Hot-Air Weldable

PRODUCT INFORMATION

Chemical Base	The Decor Profile is made of the same high quality ingredients used to manufacture Sarnafil membrane.
Packaging	<ul style="list-style-type: none">▪ 25 Decor Profiles per tube▪ 30 rigid PVC connectors per tube▪ Tube Length: 10' 4" (3.1 m)▪ Tube Weight: 57 lb (25.9 kg)
Appearance / Color	White, Tan, Reflective Gray, Patina Green, Copper Brown, Evergreen, Lead Gray, or Custom
Shelf Life	N/A
Storage Conditions	N/A
Dimensions	Length: 10' (3.04 m) Height: 1" (25 mm) Profile Width: ½" (13 mm) Base Width: 1-3/8" (35 mm) Weight: 1.93 lb (876 g)

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Welding area of the Sarnafil® Membrane to receive the Decor Profile shall be clean and dry.

APPLICATION

1. Using a chalk line and removable chalk, mark out a line for laying the Decor Profile.
2. Pre-assemble the Decor Profile sections, to create the required length, by inserting a provided connector into one end of a profile section then with the exposed portion of the connector into a second profile section butting the two sections together.
3. Using a hand welder, hot-air weld the ends of adjoining Decor Profiles together.
4. Align the Decor Profiles along the chalk line. Decor Profiles should generally line up with edge of Sarnafil® Membrane overlap. Do not cover overlap.
5. If using the Sarnamatic® automatic welding machine with the Decor Profile adapter kit, position machine to start the weld. Regularly check the Decor Profile guide. If hand welding, a 2 x 8" (50 x 203 mm) nailer may be needed to keep Decor Profiles straight.
6. Hand weld the Decor Profiles in areas where the Sarnamatic® cannot be used. If required, a piece of Sarnafil® Membrane is heat welded over the exposed end and trimmed to give a clean finish.

MAINTENANCE

Standard maintenance of roofs should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

AVAILABILITY/WARRANTY

Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Sarnafil® Decor Profile (US)
February 2020, Version 04.02
020945012150000007

SarnafilDecorProfileUS-en-US-(02-2020)-4-2.pdf

