



PRODUCT DATA SHEET

Sarnastop

Extruded aluminum bar

PRODUCT DESCRIPTION

Sarnastop is a flat aluminum bar used with approved fasteners to terminate Sarnafil® or Sikaplan® membrane to the roof deck, walls, curbs, and other details.

USES

Sarnastop distributes the loads uniformly across a series of fastening points, maximizing fastener pullout and backout resistance.

Areas of Application

- Base of walls
- Curbs
- Transitions

CHARACTERISTICS / ADVANTAGES

- Convenient punched 1/4" x 3/8" (6.4 mm x 9.5 mm) oval holes spaced 6" (15.2 cm) on center

PRODUCT INFORMATION

Chemical Base	Extruded aluminum (6063 T6 alloy) with a mill finish
Packaging	25 – 10 ft (3.05 m) bars per tube (250 ft, 76.2 m), 40 lbs (18.2 kg) per tube, 10 tubes per pallet (2500 ft, 762 m)
Shelf Life	N/A
Storage Conditions	N/A
Appearance / Color	Gray
Dimensions	Width: 1" (25.4 mm) Length: 10 ft (3 m) Thickness: 0.125" (3.2 mm)

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

AVAILABILITY/WARRANTY

Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator in compliance with Sika requirements, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

ENVIRONMENTAL, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Sarnastop is positioned over the top of the membrane and fastened to the substrate with approved fasteners. Fastener spacing is determined by Sika technical requirements. The fasteners are set to a depth to clamp the membrane in place without damaging the substrate. Depending on the specific detail, a membrane coverstrip is welded over the Sarnastop for watertightness.

COVERAGE

10 linear feet (3.05 m) per bar

MAINTENANCE

Standard maintenance of Sarnafil® or Sikaplan® systems should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF**

MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Sarnastop
July 2022, Version 03.01
020945051100000017

Sarnastop-en-US-(07-2022)-3-1.pdf

