



Sikaplan

Sikaplan is a single ply PVC roofing membrane designed for low-slope and steep-slope roofing applications. The membrane has an internal polyester scrim reinforcement to provide the tear resistance required for mechanically-attached roof systems.

Sikaplan is ideally suited for applications that require a quality, cost-effective roofing membrane from a trusted supplier. The product has a successful track record of more than 20 years of use on buildings throughout the world.

Sikaplan's white color reflects the sun's solar energy and helps to lower building cooling costs. The product meets the cool

roofing requirements of USGBC's LEED® program, Green Globes, Energy Star® and California Title 24.

Like all Sika Sarnafil membranes, Sikaplan is thermoplastic; allowing seams and flashings to be hot-air welded using the Sarnamatic automatic hot-air welder. When welded together, the sheets of membrane become one monolithic layer of material impervious to water and moisture infiltration.

To learn more about Sikaplan, please call 1-800-576-2358 or visit www.sikacorp.com ... or in Canada, call 800-268-0479 or visit www.sika.ca.

Sikaplan Product Specifications

Color	White
Systems	Sikaplan mechanically-attached
Thickness	Available in 45 and 60 mil nominal
Roll Size 45 mil	5 ft. x 150 ft. and 10 ft. x 150 ft.
Roll Size 60 mil	5 ft. x 100 ft. and 10 ft. x 100 ft.
Reflectivity	0.81
Emissivity	0.85
SRI	101

Please consult the Product Data Sheet prior to any use and processing. Our most current General Sales Conditions shall apply.

