

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET



1. Identification

Product Identification

Product Identifier: CI-LV FS
Recommended Use: Fast Setting Low-Viscosity Structural Injection Epoxy
Use Restrictions: To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada)
1-352-323-3500 (International)

For most current SDS, please visit our website at www.strongtie.com/sds

2. Hazard Identification

General Information

CI-LV FS is a two component (2:1) system packaged as a single unit in a dual cartridge or separately in 1 or 5 gallon containers. The two parts of this product have been individually assessed according to the Globally Harmonized System (GHS). The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. The final cured product will be amber and can be considered nonhazardous. Some hazards may apply upon grinding or cutting through the hardened product. This Safety Data Sheet covers the hazards and responses for the safe use of this product.

Resin (Clear Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Skin Corrosion/Irritation	Category 2	H315: Causes skin irritation
	Serious Eye Damage/Irritation	Category 2	H319: Causes serious eye irritation
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Chronic Aquatic Hazard	Category 2	H411: Toxic to aquatic life with long lasting effects

Main Symptoms: Irritation of eyes and skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin.

GHS Label Elements



Exclamation Point Environmental Hazard

Contains:	Epoxy Resins, Neopentyl glycol diglycidyl ether
Signal Word:	WARNING!
Hazard Statements:	H315: Causes skin irritation. H319: Causes serious eye irritation. H317: May cause an allergic skin reaction. H411: Toxic to aquatic life with long lasting effects.
Precautionary Statements:	
Prevention:	P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P261: Avoid breathing mist or vapor. P264: Wash thoroughly after handling. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection.

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET



Response:	P302+P352:	IF ON SKIN: Wash with plenty of water.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364:	Take off contaminated clothing and wash before re-use.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
Storage:	P391:	Collect Spillage.
	P403:	Store in a well-ventilated place.
	P405:	Store locked up.
Disposal:	P501:	Dispose of contents/container in accordance with local regulations.

Supplemental Label Information: None known.

Hardener (Clear Amber Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Acute Toxicity, Oral	Category 4	H302: Harmful if swallowed
	Acute Toxicity, Dermal	Category 4	H312: Harmful in contact with skin
	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns
	Serious Eye Damage/Irritation	Category 1	H318: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
	Germ Cell Mutagenicity	Category 2	H341: Suspected of causing genetic defects
	Reproductive Toxicity	Category 2	H361: Suspected of damaging fertility or the unborn child
	STOT, Repeated Exposure	Category 2	H373: May cause damage to organs through prolonged or repeated exposure
Environmental Hazards:	Acute Aquatic Hazard	Category 1	H400: Very toxic to aquatic life
	Chronic Aquatic Hazard	Category 1	H410: Very toxic to aquatic life with long lasting effects

Main Symptoms: Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin.

GHS Label Elements



Contains: Amines, Phenols

Signal Word: DANGER!

Hazard Statements:	H302:	Harmful if swallowed.
	H312:	Harmful in contact with skin.
	H314:	Causes severe skin burns and eye damage.
	H318:	Causes serious eye damage.
	H317:	May cause an allergic skin reaction.
	H341:	Suspected of causing genetic defects.
	H361:	Suspected of damaging fertility or the unborn child.
	H373:	May cause damage to organs through prolonged or repeated exposure.
	H400:	Very toxic to aquatic life.
	H410:	Very toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention:	P102:	Keep out of reach of children.
	P103:	Read label before use.

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET



	P201:	Obtain special instructions before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P260:	Do not breathe dust, mist, or vapor.
	P264:	Wash thoroughly after handling.
	P272:	Contaminated work clothing must not be allowed out of the workplace.
	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P301+P330+P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P310:	Immediately call a POISON CENTER/doctor.
	P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P363:	Wash contaminated clothing before reuse.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P308+P313:	If exposed or concerned: Get medical advice/attention.
	P391:	Collect spillage.
Storage:	P403+P233:	Store in a well-ventilated place. Keep container tightly closed.
	P405:	Store locked up.
Disposal:	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classification: Global Harmonized System Classifications

The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

Resin (Clear Side)

Chemical Name	Weight %	CAS Number	EC Number
Phenolic Novolac Resin	20-60	28064-14-4	608-164-0
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, STOT SE 3: H335, Aquatic Chronic 2: H411			
Bisphenol-A Based Epoxy Resin	20-60	25068-38-6	500-033-5
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, STOT SE 3: H335, Aquatic Chronic 2: H411			
Neopentyl Glycol Diglycidyl Ether	20-60	17557-23-2	241-536-7
Classifications: Skin Irrit. 2: H315, Skin Sens. 1: H317			

Hardener (Clear Amber Side)

Chemical Name	Weight %	CAS Number	EC Number
2-Piperazinyll-1-ethylamine	10-20	140-31-8	205-411-0
Classifications: Flam. Liq. 4: H227, Acute Tox. 4: H302+H312, Skin Corr. 1: H314, Eye Corr. 1: H318			
Bisphenol-A	10-20	80-05-7	201-245-8
Classifications: Eye Corr. 1: H318, Skin Sens. 1: H317, Repr. 2: H361, STOT SE 3: H335			
Benzyl Alcohol	1-10	100-51-6	202-859-9
Classifications: Acute Tox. 4: H302+312+332, Skin Corr. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317			
Isophorone Diamine	1-10	2588-13-2	220-666-8
Classifications: Acute Tox. 4: H302, Skin Irrit. 1: H314, Eye Dam. 1: H318, Skin Sens. 1: H317, Aquatic Acute 3: H402			
p-tert-butylphenol	1-10	98-54-4	202-679-0
Classifications: Skin Irrit. 2: H315, Eye Corr. 1: H318, Repr. 1B: H360, Aquatic 2: H401+H411			
Diethylenetriamine	1-5	111-40-0	203-865-4
Classifications: Acute Tox. 4: H302+312, Skin Irrit. 1: H314, Skin Sens. 1: H317			

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET

SIMPSON**Strong-Tie**

Benzene-1,3-Dimethaneamine	1-5	1477-55-0	216-032-5
Classifications: Acute Tox. 4: H302, Skin Corr. 1: H314, Eye Dam. 1: H318, Skin Sens. 1: H317, Aquatic 3: H402+H412			
Nonyl Phenol	1-5	84852-15-3	284-325-5
Classifications: Acute Tox. 4: H302, Skin Corr. 1: H314, Repr. 2: H361, Aquatic 1: H400+H410			
Phenol	1-5	108-95-2	203-632-7
Classifications: Acute Tox. 3: H301+311+331, Skin Corr. 1: H314, GCM 2: H341, STOT RE 2: H373			

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

- Eye Contact:** Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, **consult a physician immediately.**
- Skin Contact:** Remove contaminated clothing and product, immediately wash affected area with soap and water. Chemical burns must be treated by a **physician.**
- Ingestion:** Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. **Consult a physician immediately.**
- Inhalation:** Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

Most Important Symptoms

Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. Permanent eye damage, including blindness, may result. Rash/dermatitis. May cause severe irritation or burns to the gastrointestinal tract and respiratory system.

5. Fire-Fighting Measures

- Suitable Extinguishing Media:** Extinguish with foam, carbon dioxide, dry powder, or water fog.
- Additional Information:** None known.
- Hazards during Fire-Fighting:** Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C). Irritating and toxic gases/fumes may be released during a fire. Do not allow run-off from fire-fighting to enter drains or water courses.
- Fire-Fighting Procedures:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Non-emergency personnel: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

- Small spills (uncured):** Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination. If desired, approved solvents, such as ketones (MEK, acetone, etc.), lacquer thinner or adhesive remover can be used. Do NOT use solvents to clean adhesives from skin. Take appropriate precautions when handling flammable solvents. Solvents may damage surfaces to which they are applied.
- Large spills (uncured):** Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET

SIMPSON

Strong-Tie

containers. Seal tightly for proper disposal. Following product recovery, flush area with water. Keep combustibles away from spilled material.

Cured Material:

Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measures; do not allow dust to build up.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Do not breathe dust, mist, or vapor. Use only in well-ventilated places. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products and to achieve maximum allowable design load, the products must be properly installed and used in accordance with the installation instructions and design limits provided by Simpson Strong-Tie.

Storage

Full Unused Cartridges and Bulk Containers: Keep away from incompatible materials (See section 10 of the SDS). Keep in original container. Keep container tightly closed. Store in a dry, well-ventilated place out of direct sunlight, between 45-90°F (7-32°C). Keep away from heat and sources of ignition. Protect container from physical damage. Keep out of reach of children.

Partially Used Cartridges: To store partially used cartridge temporarily replace cap or leave hardened nozzle in place. To re-use, attach new nozzle. Do not try to dispense after adhesive hardens in nozzle. CAUTION: Adhesive will start to gel in the nozzle. Adhesive will gel faster at higher temperatures. Material under pressure can blowout the back of the cartridge if the adhesive in the nozzle hardens. Use only an appropriate Simpson Strong-Tie® mixing nozzle in accordance with Simpson Strong-Tie instructions. Modification or improper use of mixing nozzle may impair adhesive performance. Keep out of reach of children.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure: Wear appropriate personal protective equipment.

Eye Protection: Wear chemical splash goggles or safety glasses with side shield.

Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.

Skin and Body Protection: Wear long sleeve shirt/long pants and other clothing as required to minimize contact.

Respirator Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If grinding or cutting cured product the use of an approved respirator is recommended.

General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended, ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Benzyl Alcohol (CAS 100-51-6)	N/E	N/E	10 ppm (WEEL)
Isophorone Diamine (CAS 2855-13-2)	10 ppm	10 ppm	N/E
Diethylenetriamine* (CAS 111-40-0)	N/E	1 ppm	1 ppm

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET

SIMPSON

Strong-Tie

Phenol (CAS 108-95-2)	5 ppm	5 ppm	5 ppm
--------------------------	-------	-------	-------

*Skin Designation: Material can be absorbed through skin.

9. Physical and Chemical Properties

Property	Resin	Hardener
Physical State:	Liquid	Liquid
Color:	Clear	Clear Amber
Odor:	No data	No data
pH:	No data	No data
Flammability limit – lower %:	No data	No data
Flammability limit – upper %:	No data	No data
Vapor Pressure:	Non-Volatile	No data
Vapor Density:	No data	No data
Solubility:	Insoluble in water	Slightly soluble in water
Freezing/Melting Point:	No data	No data
Boiling Point:	No data	No data
Flash Point:	>199°F (93°C)	>199°F (93°C)
Evaporation Rate:	No data	No data
Specific Gravity:	1.140	1.024
VOC (after cure):	13 g/L	13 g/L
Kow:	No data	No data
Viscosity:	625 cP	580 cP
Corrosiveness:	No data	No data

10. Stability and Reactivity

Reactivity:	This product is stable and non-reactive under normal conditions. Resin unstable when exposed to heat.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Oxidizing and reducing agents, peroxides, phenols, and acids.
Hazardous Reactions:	Hazardous polymerization does not occur. The product is stable if stored and handled as prescribed/indicated.
Decomposition Products:	Resin decomposes with heat. Combustion may produce oxides of carbon, aldehydes and smoke. Fire or high temperature with the hardener can create carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion:	Corrosive material; causes severe irritation or burns to the gastrointestinal tract and respiratory tract.
Inhalation:	If this material is heated or misted, coughing and mild irritation may occur. Do not inhale dust from cutting/grinding cured product.
Skin contact:	Causes severe skin burns. May cause an allergic skin reaction.
Eye contact:	Causes serious eye damage.
Symptoms:	Burns, redness, itching, tearing, swelling, and blurred vision. Rash/dermatitis. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. Shortness of breath, discomfort in chest, or coughing.

Information on Toxicological Effects

Toxicity:	May be harmful if swallowed or in contact with skin.
-----------	--

Component	Estimate
CI-LV FS Resin Toxicity Estimate	
Acute, Oral, LD50	3500
Acute, Dermal, LD50	> 2000

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET



CI-LV FS Hardener Toxicity Estimate		
	Acute, Oral, LD50	1250
	Acute, Dermal, LD50	1900

Skin corrosion/irritation: Causes severe skin irritation and burns.
Eye damage/eye irritation: Causes serious eye irritation and damage.
Respiratory sensitization: No data available.
Skin sensitization: May cause an allergic skin reaction.
Aspiration hazard: Due to the physical form of this product it is not an aspiration hazard.
**Specific target organ toxicity
Single exposure:** May cause respiratory irritation.

Chronic Effects

Germ cell mutagenicity: No data available.
Carcinogenicity: No data available.
Reproductive toxicity: No data available.
**Specific target organ toxicity
Repeated exposure:** May cause damage to organs (kidney, liver, lung, nervous system, skin) through prolonged or repeated exposure.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Bisphenol-A (CAS 80-05-7)	1-10	---	---	---	CA65
Phenol (CAS 108-95-2)	1-5	3	---	A4	in vitro tests show limited mutagenic properties in human cells
Nonyl Phenol (CAS 84852-15-3)	1-5	---	---	---	Limited evidence of reproductive toxicity (NOAEL >2000 ppm)

IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic
 NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen
 ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected
 CA65 – California Prop 65

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. CI-LV FS Resin is classified as toxic to aquatic life with long lasting effects. CI-LV FS Hardener is classified as very toxic to aquatic life with long lasting effects. Avoid release to the environment.

Supporting Data

Component	Estimate
CI-LV FS Resin Toxicity Estimate	Aquatic, Fish, LC50 1.3 mg/l, 96 hours
	Aquatic, Crustacea, EC50 3 mg/l, 48 hours
	Aquatic, Algae, EC50 > 10 mg/l, 72 hours
CI-LV FS Resin Toxicity Estimate	Aquatic, Fish, LC50 < 0.05 mg/l, 96 hours
	Aquatic, Crustacea, EC50 < 0.05 mg/l, 48 hours

Persistence and degradability: This product is not expected to be readily biodegradable.
Bioaccumulative potential: No data available for this product.
Mobility in soil: This product is non-volatile.

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET

SIMPSON

Strong-Tie

Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Consideration

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal of Cured Product: Chip or grind off surface. Solid material does not need special disposal consideration.

14. Transportation Information

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or nation regulations.

	Resin (Clear Side)	Hardener (Clear Amber Side)
UN number:	UN3082	UN2735
UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant	AMINES, LIQUID, CORROSIVE, N.O.S. (Aminoethyl (piperazine, 1-(2), Isophorone Diamine), 8, II
Transportation Class:	9	8
Packing Group:	III	II
Environment Hazard:	Yes	No
Required Labels:	9	8
ERG Code (IATA):	9L	8L
EmS (IMDG):	F-A, S-F	F-A, S-B
Special Precautions for Users:	Read safety instructions, SDS and emergency procedures before handling.	

Based on packaging size, Limited Quantity exemptions may apply. Please consult the 49 CFR HMR, IATA DGR, and IMDG Code to ensure that shipments comply with these regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):
Nonyl Phenol (CAS 84852-15-3) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4):
Phenol (CAS 108-95-2) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:	Immediate	Delayed	Fire	Pressure	Reactivity
Resin	Yes	No	No	No	No
Hardener	Yes	Yes	No	No	No

SARA 302 Extremely hazardous substance:

Component	CAS	Reportable Quant.	Threshold Planning Quant. Lower Value	Threshold Planning Quant. Upper Value
Phenol	108-95-2	1000	500 lbs	10000 lbs

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET



SARA 311/312 Hazardous chemical: Yes
SARA 313 (TRI reporting):

Chemical	CAS Number	% In Blend (approx.)
Phenol	108-95-2	1-5
Nonyl Phenol	84852-15-3	1-5
Bisphenol-A	80-05-7	10-20

California Proposition 65:

WARNING: This product can expose you to chemicals including epichlorohydrin and bisphenol-A which are known to the State of California to cause cancer, reproductive harm, or other birth defects. For more information, go to www.P65Warnings.ca.gov.

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
China	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)
Europe	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
Japan	All components in this product are listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	All components of this product are included on the Existing Chemicals List (ECL)
New Zealand	All components of this product are included on the New Zealand Inventory.
Philippines	All components of this product are included on the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

16. Other Information

Date Prepared or Revised: November 2019
Supersedes: September 2019
Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com.

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HPR:	Hazardous Product Regulations (Canada)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code

CI-LV FS Fast Setting Low-Viscosity Structural Injection Epoxy

SAFETY DATA SHEET

NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Full Text of H – Phrases Under Section 3

H227:	Combustible liquid.
H303:	Toxic if swallowed.
H311:	Toxic in contact with skin.
H331:	Toxic if inhaled.
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation.
H360:	May damage fertility or the unborn child.
H401:	Toxic to aquatic life.
H402:	Harmful to aquatic life.

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2019 Simpson Strong-Tie Company Inc.

Internal

FOR INTERNAL USE ONLY

CI-LV FS Resin:	CI-LV FS Hardener:
XCOM3B – 66% Cartridge	XCOM3B – 33% Cartridge
	XCORR – 33% Cartridge