SAFETY DATA SHEET



1.	Identification				
Produ	Product Identification				
	Product Identifier: Recommended Use: Use Restrictions:	Simpson Strong-Tie [®] Mechanical Anchors Mechanical anchors for use with concrete, masonry, and other solid, base materials. Tampering with product can compromise the integrity of the product and create health hazards.			
Comp	pany Identification				
	Company:	Simpson Strong-Tie Company Inc.			
	Address:	5956 W. Las Positas Blvd. Pleasanton, CA 94588			
	Phone:	1-800-999-5099			
	Website:	www.strongtie.com			
	Emergency:	1-800-535-5053 (US/Canada) 1-352-323-3500 (International)			
	For most current SDS, please	visit our website at www.strongtie.com/sds			

2. Hazard Identification

General Information

As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, this product is considered an article and does not require an SDS. Although these products are not subject to the OSHA Standard or GHS labeling elements, Simpson Strong-Tie would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. In its manufactured and shipped state, this product is considered to present a low hazard. Under normal use conditions, this product is not expected to create any health or safety hazards. However, individual customer processes (welding, sawing, grinding, brazing, abrasive blasting) could result in the formation of fumes, dust, and/or particulate matter that may present the following hazards.

GHS Classification


Under normal conditions, this product is not expected to pose any health or safety hazards and does not meet the criteria for GHS Classification. However, processes associated with this product (welding, sawing, grinding, brazing, abrasive blasting) may result in the formation of dust/particles that pose health hazards. Improper use of mechanical anchors may result in safety hazards. Ensure that good work practices and the necessary precautionary measures are taken to maintain safe use of the product.

Hazards Not Otherwise Classified (HNOC)

Possible safety hazards associated with processing dust potentially created during customer use of this product.

Physical Hazards:	Not Classified		
Health Hazards:	Skin Corrosion/Irritation	Category 3	H316: Causes mild skin irritation
	Serious Eye Damage/Irritation	Category 2	H319: Causes serious eye irritation
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
	STOT, Single Exposure	Category 3	H335: May cause respiratory irritation
	STOT, Repeated Exposure	Category 2	H373: May cause damage to organs (lungs)
Environmental Hazards	: Not Classified.		

Main Symptoms: Irritation to the eyes and skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin. May cause shortness of breath or other respiratory distress/irritation. Long term exposure may cause chronic effects.



Mechanical Anchors SAFETY DATA SHEET



	P261:	Avoid breathing dust.
	P264:	Wash hands thoroughly after handling.
	P271:	Use only outdoors or in a well-ventilated area.
	P272:	Contaminated clothing should not be allowed out of the workplace.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P363:	Wash contaminated clothing before reuse.
	P304+340:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P314:	Get medical advice/attention if you feel unwell.
Storage:	P420:	Store away from incompatible materials.
Disposal:	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

3. Composition Information

Composition

This product is composed of various metals, and may have ferrous or non-ferrous plating.

ral Information	as and treat symptometically. Symptome may be delayed. Ensure that medical personnal are sylvere
	es and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware recautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash .
es of Exposure	
Eye Contact:	If experiencing eye irritation due to dust, flush eyes with plenty of cool water for at least 15 minu while holding the eyes open. Remove contact lenses if present and easy to do. If you experience redness, burning, blurred vision, or swelling, consult a physician.
Skin Contact:	If experiencing skin irritation, wash affected area with soap and water. Do not apply greases or ointments. If rash or irritation occurs consult a physician.
Ingestion:	Rinse mouth immediately. Do not induce vomiting. Consult a physician.
Inhalation:	Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to
	experience difficulty breathing, consult a physician.
Important Symptoms	experience difficulty breathing, consult a physician.
Irritant effects. Symptoms include it coughing.	ching, burning, redness, tearing, and blurred vision; discomfort in the chest, shortness of breath,
Irritant effects. Symptoms include it coughing. Fire-Fighting Measures	ching, burning, redness, tearing, and blurred vision; discomfort in the chest, shortness of breath,
Irritant effects. Symptoms include it coughing.	
Irritant effects. Symptoms include it coughing. Fire-Fighting Measures	ching, burning, redness, tearing, and blurred vision; discomfort in the chest, shortness of breath, Mechanical Anchors do not pose a fire hazard. In event of a fire, choose extinguishing media
Irritant effects. Symptoms include it coughing. Fire-Fighting Measures Suitable Extinguishing Media:	ching, burning, redness, tearing, and blurred vision; discomfort in the chest, shortness of breath, Mechanical Anchors do not pose a fire hazard. In event of a fire, choose extinguishing media appropriate for packaging or surrounding material. Customer use can possibly result in the formation of explosive air-dust mixtures; avoid creating
Irritant effects. Symptoms include it coughing. Fire-Fighting Measures Suitable Extinguishing Media: Additional Information:	ching, burning, redness, tearing, and blurred vision; discomfort in the chest, shortness of breath, Mechanical Anchors do not pose a fire hazard. In event of a fire, choose extinguishing media appropriate for packaging or surrounding material. Customer use can possibly result in the formation of explosive air-dust mixtures; avoid creating dust. Dusts may present a fire or explosion hazard under rare favoring conditions of particle size, dispersion and strong ignition source. However, this is not expected to be a problem under no

Wear appropriate personal protection equipment for Mechanical Anchor use.

Solid material does not pose a spill hazard. Avoid processes that result in the creation of dust. In the event of dust creation, avoid dry sweeping. Use water spraying/flushing or ventilated or HEPA filtered vacuum cleaning system. If not possible, gently moisten dust before collection with shovel or broom. Dispose of in closed containers.

Environmental Precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Handling

Wear appropriate personal protective equipment. Avoid generating dust. If grinding or cutting, use work methods which minimize dust production. Avoid inhalation of dust. Ensure adequate ventilation. When using, do not eat, drink, or smoke. Wash hands thoroughly after handling. Use good housekeeping, and observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products, the products must be properly installed and used in accordance with the installation instructions and design limits provided by Simpson Strong-Tie.

Storage

Store in a closed container away from incompatible materials.

8. Exposure Controls / Personal	Exposure Controls / Personal Protection			
Personal Protective Equipment				
Protective Measure:	Wear appropriate personal protective equipment. Protective coatings are used on some mechanical anchors. Typically this will be commercial zinc, zinc plating with chromate conversion coating, hot dipped galvanizing, ceramic plating, or mechanically galvanized plating. This information should be considered when evaluating employee personal protective equipment.			
Eye Protection:	Wear goggles or safety glasses.			
Hand Protection:	Gloves recommended.			
Skin and Body Protection:	Wear long sleeve shirt/long pants and other clothing as required to minimize contact. In case of dust production, wear dust-proof clothing.			
Respirator Protection:	Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of dust are expected to exceed exposure limits.			
General Hygiene:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			

Engineering Controls

Use outdoors or ensure good ventilation when working indoors. Provide eyewash station and emergency shower.

Exposure Limits

No exposure limits noted for ingredients.

	•	0		
9.	Physical and Chemi	cal Properties		
	Physical State:	Solid	Freezing/Melting Point	: 2600-2700°F (1426-1482°C)
	Form:	Solid	Boiling Point:	N/A
	Color:	Gray/Various Co	ors Flash Point:	N/A
	Odor:	None	Evaporation Rate:	N/A
	Odor Threshold:	N/A	Specific Gravity:	N/A
	pH:	N/A	VOC:	N/A
	Flammability:	N/A	U/L Flammability:	N/A
	Vapor Pressure:	N/A	Vapor Density:	N/A
	Solubility:	N/A	Kow:	N/A
	Decomposition:	N/A	Viscosity:	N/A
10.	Stability and Reactiv	ity		
	Reactivity:StableChemical Stability:StableCondition to Avoid:None kSubstances to Avoid:Strong		able and non-reactive under normal condi able and non-reactive under normal condi one known. rong oxidizers. Strong acids and bases. azardous polymerization will not occur.	

Strong-I

Mechanical Anchors

SAFETY DATA SHEET

Decomposition Products:

Carbon dioxide, carbon monoxide, oxides of nitrogen, other organic compounds. Thermal oxidative decomposition of galvanized steel products can produce fumes containing oxides of zinc, iron, manganese, as well as other elements.

Strong-T

11. Toxicological Information	
Likely Routes of Exposure	
Ingestion: Inhalation: Skin contact:	Do not place anchors in mouth. Not expected to be an ingestion hazard. May cause respiratory tract irritation if process dust is inhaled. Sharp edges of anchors may cause abrasions or cuts if not handled properly. May cause mild skin irritation or sensitization.
Eye contact: Symptoms:	May cause eye irritation. Particles resulting from processing can cause corneal abrasion. Irritant effects. Symptoms include itching, burning, redness, tearing, swelling, and blurred vision.
Information on Toxicological Effects	initiant enects. Symptoms include itching, burning, redness, tearing, swelling, and burred vision.
Acute Effects	
Toxicity: Skin corrosion/irritation:	Not expected to be acutely toxic. May cause mild skin irritation. Sharp edges of anchors may cause abrasions or cuts if not handled properly.
Eye damage/eye irritation: Respiratory sensitization: Skin sensitization: Aspiration hazard:	May cause serious eye irritation. Not a respiratory sensitizer. May cause sensitization by skin contact. Not applicable.
Specific target organ toxicity Single exposure:	May cause respiratory tract irritation.
Chronic Effects	
Germ cell mutagenicity: Carcinogenicity: Reproductive toxicity:	No data available. This product is not a carcinogen. This product may contain small amounts of compounds which are listed carcinogens. These compounds are bound in the product and exposure to these compounds is highly unlikely during normal product use. Exposure to these compounds is possible only if the product is ground or cut. Exposure to oxides of component metals is possible if product is welded or exposed to excessive heat. Ensure good work practice and use appropriate personal protective equipment as needed to control exposure. No data available.
Specific target organ toxicity Repeated exposure:	May cause damage to organs (lungs) through prolonged or repeated exposure (inhalation of dust).

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material or processing dust generated.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. This material is not classified as environmentally hazardous. Large or frequent spills can have a harmful or damaging effect on the environment, but is unlikely due to the nature of the product.

Supporting Data

Persistence and degradability: Bioaccumulative potential: Mobility in soil: Not readily biodegradable. Not expected to bioaccumulate. Not applicable.

Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

Disposal Consi	derations	
Waste Disposal	of Substance:	Do not allow material into sewers/water supplies. Do not contaminate ponds, waterways or ditor Dispose of contents/container in accordance with local/regional/national/international regulation Steel scrap should be recycled whenever possible.
Container Dispo	osal:	Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be disposed of in accordance with local/regional/national/international regulations.
Transportation	Information	
DOT:		Mechanical Anchors are not regulated for transport.
IMDG/IATA:		Mechanical Anchors are not regulated for transport.
onal Information		
Special precauti Transport in bul		Read safety instructions, SDS and emergency procedures before handling. nex II of MARPOL 73/78 and the IBC Code: Not applicable.
		pecific regulatory or operational requirements of this product. The classifications for transportation regional or national regulations.
Regulatory Info	rmation	
States		
Federal Regulat	2(b) Export Notifica	This product is an "Article" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. ation (40 CFR 707, Subpt. D): Not regulated. Substances (29 CFR 1910 1001-1050): Not listed
Federal Regulat TSCA Section 12 US. OSHA Spect CERCLA Hazard Superfund Ame Hazard Categ	2(b) Export Notifica ifically Regulated S lous Substance Lis <u>ndments and Reau</u> jories:	1910.1200. ation (40 CFR 707, Subpt. D): Not regulated. Substances (29 CFR 1910.1001-1050): Not listed. st (40 CFR 302.4): Not listed. Ithorization Act of 1986 (SARA)
Federal Regulat TSCA Section 12 US. OSHA Speci CERCLA Hazard S <u>uperfund Ame</u>	2(b) Export Notifica ifically Regulated S lous Substance Lis <u>ndments and Reau</u> jories:	1910.1200. ation (40 CFR 707, Subpt. D): Not regulated. Substances (29 CFR 1910.1001-1050): Not listed. st (40 CFR 302.4): Not listed. hthorization Act of 1986 (SARA) Fire Fire Pressure Reactivity
Federal Regulat TSCA Section 12 US. OSHA Speci CERCLA Hazard Superfund Ameri Hazard Categ Immediate No SARA 302 Extre SARA 311/312 H SARA 313 (TRI r Chemical Nar	2(b) Export Notifica ifically Regulated S lous Substance Lis <u>ndments and Reau</u> jories: <u>Delayed</u> <u>No</u> mely hazardous su lazardous chemica reporting):	1910.1200. ation (40 CFR 707, Subpt. D): Not regulated. Substances (29 CFR 1910.1001-1050): Not listed. st (40 CFR 302.4): Not listed. httprization Act of 1986 (SARA) Fire Pressure Reactivity No No Jobstance: No No Li: No CAS Number
Federal Regulat TSCA Section 12 US. OSHA Speci CERCLA Hazard Superfund Amer Hazard Categ Immediate No SARA 302 Extre SARA 311/312 H SARA 313 (TRI r	2(b) Export Notifica ifically Regulated S lous Substance Lis <u>ndments and Reau</u> jories: <u>Delayed</u> <u>No</u> mely hazardous su lazardous chemica reporting):	1910.1200. ation (40 CFR 707, Subpt. D): Not regulated. Substances (29 CFR 1910.1001-1050): Not listed. st (40 CFR 302.4): Not listed. ithorization Act of 1986 (SARA) Fire Pressure Reactivity No No Ibstance: No No No
Federal Regulat TSCA Section 12 US. OSHA Speci CERCLA Hazard Superfund Ameri Hazard Categ Immediate No SARA 302 Extre SARA 311/312 H SARA 313 (TRI r Chemical Nar	2(b) Export Notifica ifically Regulated S lous Substance Lis <u>ndments and Reau</u> jories: <u>Delayed</u> <u>No</u> mely hazardous su lazardous chemica reporting):	1910.1200. ation (40 CFR 707, Subpt. D): Not regulated. Substances (29 CFR 1910.1001-1050): Not listed. st (40 CFR 302.4): Not listed. ithorization Act of 1986 (SARA) Fire Pressure Reactivity No No ubstance: No No I: No CAS Number

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

International Inventories

Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

Mechanical Anchors

SAFETY DATA SHEET

16. Other Information

Date Prepared or Revised:	May 2020
Supersedes:	July 2016
Contact Simpson Strong-Tie Env	ironmental Health and Safety at EHS@strongtie.com.

Abbreviations

AC	GIH:	American Conference of Governmental Industrial Hygienists
CA	S No.:	Chemical Abstract Service Registry Number
CE	RCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HP	R:	Hazardous Product Regulations (Canada)
DO)T:	Department of Transportation (U.S.)
GH	IS:	Globally Harmonized System of Classification and Labeling of Chemicals
HE	PA:	High-Efficiency Particulate Air
HN	IIS:	Hazardous Materials Identification System
IAF	RC:	International Agency for Research on Cancer
IAT	Γ Α :	International Air Transport Association
IMI	DG:	International Maritime Dangerous Goods code
NIC	OSH:	National Institute of Occupational Safety and Health (U.S.)
NF	PA:	National Fire Protection Association (US)
NT	P:	National Toxicology Program (US)
OS	SHA:	Occupational Safety and Health Administration (U.S.)
PE	L:	Permissible Exposure Limit
SA	RA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
ST	EL:	Short Term Exposure Limit (15 minute Time Weighted Average)
ST	OT:	Specific Target Organ Toxicity (GHS Classification)
TL	V:	Threshold Limit Value
TS	CA:	Toxic Substances Control Act (U.S.)
ТМ	/A:	Time Weighted Average (exposure for 8-hour workday)
VO	C:	Volatile Organic Compounds
WH	HMIS:	Canadian Workplace Hazardous Materials Information System

Disclaimer

Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2020 Simpson Strong-Tie Company Inc.

Internal

FOR INTERNAL USE ONLY XNA