

**1. Identification**

**Product Identification**

**Product Identifier:** **A Component RPS-70-9**  
**Recommended Use:** RPS-70-9 Epoxy Coating is a protective coating for use with steel, concrete and wood.  
**Use Restrictions:** For industrial use only. To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at [strongtie.com](http://strongtie.com).

**Company Identification**

**Company:** Simpson Strong-Tie Company Inc.  
**Address:** 5956 W. Las Positas Blvd.  
 Pleasanton, CA 94588 USA  
**Phone:** 1-800-999-5099  
**Website:** [www.strongtie.com](http://www.strongtie.com)  
**Emergency:** 1-800-535-5053 (US/Canada)  
 1-352-323-3500 (International)

For most current SDS, please visit our website at [www.strongtie.com/sds](http://www.strongtie.com/sds)

**2. Hazard Identification**

**General Information**

RPS-70-9 Epoxy Coating is a 100% solids, two part system (2A:1B mix) designed to protect steel, wood, and concrete surfaces in commercial and industrial settings. It is available in brown, limestone, light gray, brick red, and white. The two parts of this product have been assessed individually according to the Globally Harmonized System (GHS). The mixed product can be assumed to carry the hazards of each component until the product has been fully cured. This Safety Data Sheet covers hazards and responses for Component A. See Component B Safety Data Sheet for complete product information.

**Component A GHS Classification**

**Classification according to HazCom 2012 (GHS)**

<b>Physical Hazards:</b>	Not Classified.		
<b>Health Hazards</b>	Skin Corrosion/Irritation	Category 2	H315: Causes skin irritation
	Serious Eye Damage/Irritation	Category 2	H319: Causes serious eye irritation
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
<b>Environmental Hazards:</b>	Chronic Environmental Hazard	Category 2	H411: Toxic to aquatic life with long lasting effects
<b>Main Symptoms:</b>	Irritation of eyes and skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin.		

**GHS Label Elements**



**Contains:** Bisphenol-A Based Epoxy Resin, Titanium Dioxide, Castor Oil Glycidyl Ether

**Signal Word:** **WARNING!**

**Hazard Statements:**

H315:	Causes skin irritation.
H319:	Causes serious eye irritation.
H317:	May cause an allergic skin reaction.
H411:	Toxic to aquatic life with long lasting effects.

**Precautionary Statements:**

**Prevention:**

P201:	Obtain special instructions before use.
P202:	Do not handle until all safety precautions have been read and understood.
P261:	Avoid breathing dust, mist, or vapor.
P264:	Wash thoroughly after handling.
P272:	Contaminated clothing should not be allowed out of the workplace.
P273:	Avoid release to the environment.
P280:	Wear protective gloves/clothing/eye protection/face protection.
<b>Response:</b>	P302+P352: IF ON SKIN: Wash with plenty of water.

**RPS-70-9 Epoxy Coating**  
SAFETY DATA SHEET



	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364:	Take off contaminated clothing and wash before reuse.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P308+P313:	If exposed or concerned: Get medical advice/attention.
	P391:	Collect spillage.
<b>Storage:</b>	P403:	Store in a well-ventilated place.
	P405:	Store locked up.
<b>Disposal:</b>	P501:	Dispose of contents/container in accordance with local/regional regulations.

**Supplemental Label Information:** None known.

**Hazards Not Otherwise Classified (HNOC)**

The above hazards are for the uncured A component of RPS-70-9. Upon combination with the B component, an innocuous solid which does not present any immediate hazards is formed. Upon grinding or cutting through the cured product, the following hazards may apply. Ensure that good work practices, and the necessary precautionary measures, are taken to maintain safe use of the product.



Chronic Health

<b>Health Hazard:</b>	Carcinogenicity	Category 1A
<b>OSHA Hazard:</b>	Combustible Dust	
<b>Hazard Statements:</b>	May cause cancer. Can form explosive air-dust mixtures, avoid creating dust.	
<b>Precautionary Statements:</b>	Do not breathe dust. Do not allow dust to build up on surfaces.	

**3. Composition Information**

**General Information**

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

**List of abbreviations and symbols:**

Classification: Global Harmonized System Classifications

*The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.*

**Composition – All concentrations are in percent by weight unless otherwise indicated.**

Chemical Name	Weight %	CAS Number	EC Number
Bisphenol-A Based Epoxy Resin	65-85	25068-38-6	500-033-5
<b>Classification:</b> Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, Aquatic Chronic 2: H411			
Titanium Dioxide	< 20	13463-67-7	236-675-5
<b>Classification:</b> Carc. 2: H351			
Castor Oil Glycidyl Ether	1-10	74398-71-3	616-085-8
<b>Classification:</b> Skin Irrit. 2: H315, Skin Sens. 1: H317			

**4. First-Aid Measures**

**General Information**

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

**Routes of Exposure**

<b>Eye Contact:</b>	Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, <b>consult a physician immediately.</b>
<b>Skin Contact:</b>	Remove contaminated clothing and product; wash affected area with soap and water. Do not apply greases or ointments. If redness, burning, or swelling persists, <b>consult a physician.</b>
<b>Ingestion:</b>	Rinse mouth. If you feel unwell, <b>consult a physician.</b>
<b>Inhalation:</b>	Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, <b>consult a physician.</b>

**Most Important Symptoms**

# RPS-70-9 Epoxy Coating

## SAFETY DATA SHEET



Irritation of eyes and skin. Symptoms include rash, redness, itching, burning, tearing, swelling, and blurred vision.

### 5. Fire-Fighting Measures

**Suitable Extinguishing Media:** Extinguish with foam, carbon dioxide, dry powder, or water fog.  
**Additional Information:** None known.  
**Hazards during Fire-Fighting:** Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C).  
**Fire-Fighting Procedures:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

### 6. Accidental Release Measures

#### Personal Precautions

**Non-emergency personnel:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

**Emergency personnel:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

#### Clean-Up Methods

**Small spills (uncured):** Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.  
**Large spills (uncured):** Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water.  
**Cured Material:** Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measures; do not allow dust to build up.

#### Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and Storage

#### Handling

Wear appropriate personal protective equipment. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid prolonged exposure. Provide adequate ventilation. Avoid breathing fumes or vapors. When in use do not eat, drink, or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact during pregnancy/while nursing. Do not empty into drains, avoid release to the environment. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products, the products must be properly installed and used in accordance with the installation instructions and design limits provided by Simpson Strong-Tie.

#### Storage

Store in a closed container away from incompatible materials (Section 10 of the SDS). Keep in original container. Keep container tightly closed. Store in a cool, dry place out of direct sunlight, between 40-95°F (4-35°C). Keep away from heat and sources of ignition. Protect from physical damage.

### 8. Exposure Controls / Personal Protection

#### Personal Protective Equipment

**Protective Measure:** Wear appropriate personal protective equipment.  
**Eye Protection:** Wear chemical splash goggles or safety glasses with side shield.  
**Hand Protection:** Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.  
**Skin and Body Protection:** Wear long sleeve shirts/long pants and other clothing as required to minimize contact.  
**Respirator Protection:** The use of a respirator is not required during normal use of this product. An approved respirator should be worn whenever workplace conditions warrant respirator use, or when grinding or cutting cured product.

**RPS-70-9 Epoxy Coating**  
**SAFETY DATA SHEET**

**General Hygiene:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Engineering Controls**

Mechanical ventilation or local exhaust ventilation is recommended. Ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

**Exposure Limits**

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Titanium Dioxide (CAS 13463-67-7)	15 mg/m <sup>3</sup> (total dust)	10 mg/m <sup>3</sup>	N/E

**9. Physical and Chemical Properties**

<b>Physical State:</b>	Liquid	<b>Freezing/Melting Point:</b>	N/E
<b>Form:</b>	Liquid	<b>Boiling Point:</b>	N/E
<b>Color:</b>	Various	<b>Flash Point:</b>	>200°F (>93°C)
<b>Odor:</b>	Slight	<b>Evaporation Rate:</b>	N/E
<b>Odor Threshold:</b>	N/E	<b>Specific Gravity:</b>	1.26
<b>pH:</b>	N/E	<b>VOC (A+B):</b>	12 g/L
<b>Flammability:</b>	N/E	<b>U/L Flammability:</b>	N/E
<b>Vapor Pressure:</b>	N/E	<b>Vapor Density:</b>	N/E
<b>Solubility:</b>	Insoluble	<b>Kow:</b>	N/E
<b>Decomposition:</b>	N/E	<b>Viscosity:</b>	N/E

**10. Stability and Reactivity**

<b>Reactivity:</b>	This product is stable and non-reactive under normal conditions.
<b>Chemical Stability:</b>	Stable under normal storage conditions.
<b>Condition to Avoid:</b>	High heat and open flame.
<b>Substances to Avoid:</b>	Oxidizing agents, acids, organic bases, and amines.
<b>Hazardous Reactions:</b>	Hazardous polymerization will not occur.
<b>Decomposition Products:</b>	Carbon dioxide, carbon monoxide, oxides of nitrogen and other organic compounds.

**11. Toxicological Information**

**Likely Routes of Exposure**

<b>Ingestion:</b>	Expected to be a low ingestion hazard.
<b>Inhalation:</b>	Prolonged exposure may cause respiratory irritation.
<b>Skin contact:</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact:</b>	Causes serious eye irritation.
<b>Symptoms:</b>	Rash, redness, itching, burning, tearing, swelling, and blurred vision.

**Information on Toxicological Effects**

**Acute Effects**

**Toxicity:** Not expected to be acutely toxic.

Component	Estimate
RPS-70-9 Component A Toxicity Estimate	
<b>Acute, Oral, LD50</b>	<b>&gt; 9000</b>

<b>Skin corrosion/irritation:</b>	Causes skin irritation.
<b>Eye damage/eye irritation:</b>	Causes serious eye irritation.
<b>Respiratory sensitization:</b>	No data available.
<b>Skin sensitization:</b>	May cause skin sensitization by contact.
<b>Aspiration hazard:</b>	No data available.
<b>Specific target organ toxicity</b>	
<b>Single Exposure:</b>	No data available.

**Chronic Effects**

**Germ cell mutagenicity:** No data available

**RPS-70-9 Epoxy Coating**  
**SAFETY DATA SHEET**

**Carcinogenicity:** RPS-70-9 contains chemicals which are considered carcinogens in respirable form. Ensure good work practice and use personal protective equipment as needed to control exposure to processing dust.

**Reproductive toxicity:** No data available.

**Specific target organ toxicity**

**Repeated Exposure:** No data available.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Titanium Dioxide (CAS 13463-67-7)	< 20	2B	---	---	CA65
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 - Not classifiable as to carcinogenicity 4 - Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH - A1 - Confirmed carcinogen A2 - Suspected carcinogen A3 - Animal carcinogen A4 - Not classified A5 - Not suspected CA65 - California Prop 65					

**Further Information**

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

**12. Ecological Information**

**General Information**

Information given is based on data on the components and the ecotoxicology of similar products. The product is classified as toxic to aquatic life with long lasting effects. Avoid release to the environment.

**Supporting Data**

Component	Estimate
RPS-70-9 Component A Toxicity Estimate	
<b>Aquatic, Fish, LC50</b>	10 mg/l, 96 hours
<b>Aquatic, Crustacea, EC50</b>	3 mg/l, 48 hours

**Persistence and degradability:** No data available.

**Bioaccumulative potential:** No data available for the product.

**Mobility in soil:** No data available.

**Other Adverse Effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

**13. Disposal Considerations**

**Waste Disposal of Substance:** Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

**Container Disposal:** Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**Disposal of Cured Product:** Chip or grind off surface. Solid material does not need special disposal consideration.

**14. Transportation Information**

RPS-70-9 Component A is not regulated for ground transportation by the US DOT; check specific requirements for other regions and other shipping methods.

**UN number:** UN3082

**UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin Resin), 9, III, Marine Pollutant

**Required Labels:** 9

**ERG Code (IATA):** 9L

**EmS (IMDG):** F-A, S-F

**Additional Information**

**Special precautions for user:** Read safety instructions, SDS and emergency procedures before handling.

**RPS-70-9 Epoxy Coating**  
**SAFETY DATA SHEET**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

This substance/mixture is not intended to be transported in bulk.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

**15. Regulatory Information**

**United States**

**Federal Regulations:** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):** Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

Toluene (CAS 108-88-3) LISTED  
Zinc Sulfide (CAS 1314-98-3) LISTED

**Superfund Amendments and Reauthorization Act of 1986 (SARA):**

Hazard Categories:				
Immediate	Delayed	Fire	Pressure	Reactivity
Yes	No	No	No	No

**SARA 302 Extremely hazardous substance:** No

**SARA 311/312 Hazardous chemical:** Yes

**SARA 313 (TRI reporting):**

Component	CAS Number	% In Blend (approx.)
Toluene	108-88-3	Trace
Zinc Sulfide	1314-98-3	< 2

**US. California Proposition 65:**

**WARNING:** This product can expose you to chemicals which are known to the State of California to cause cancer, reproductive harm, or other birth defects. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Titanium Dioxide (CAS 13463-67-7)	< 20	2B	---	---	CA65 (Carcinogenic)
Toluene (CAS 108-88-3)	Trace	3	---	---	CA65 (Developmental)
Quartz (CAS 14808-60-7)	Trace	1	KNOWN	A2	CA65 (Carcinogenic)
Carbon Black (CAS 1333-86-4)	< 0.1	2B	---	---	CA65 (Carcinogenic)

IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 - Not classifiable as to carcinogenicity 4 - Probably not carcinogenic  
NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen  
ACGIH - A1 - Confirmed carcinogen A2 - Suspected carcinogen A3 - Animal carcinogen A4 - Not classified A5 - Not suspected  
CA65 - California Prop 65

**Canada**

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

**International**

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

**International Inventories**

<b>Australia</b>	One or more components of this product are not listed on the Australian Inventory of Chemical Substances (AICS).
<b>Canada</b>	All components of this product are included on the Domestic Substances List (DSL).

# RPS-70-9 Epoxy Coating

## SAFETY DATA SHEET

<b>China</b>	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).
<b>Europe</b>	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
<b>Japan</b>	One or more components of this product are not listed on the Inventory of Existing and New Chemical Substances (ENCS).
<b>Korea</b>	One or more components of this product are not listed on the Existing Chemicals List (ECL).
<b>New Zealand</b>	One or more components of this product are not included on the New Zealand Inventory.
<b>Philippines</b>	One or more components in this product are not listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
<b>United States &amp; Puerto Rico</b>	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or not required to be listed.

### 16. Other Information

**Date Prepared or Revised:** November 2021  
**Supersedes:** July 2020  
**Contact Simpson Strong-Tie Environmental Health and Safety at** [EHS@strongtie.com](mailto:EHS@strongtie.com).

### Abbreviations

**ACGIH:** American Conference of Governmental Industrial Hygienists  
**CAS No.:** Chemical Abstract Service Registry Number  
**CERCLA:** Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)  
**HPR:** Hazardous Product Regulations (Canada)  
**GHS:** Globally Harmonized System of Classification and Labeling of Chemicals  
**HMIS:** Hazardous Materials Identification System  
**IARC:** International Agency for Research on Cancer  
**IATA:** International Air Transport Association  
**IMDG:** International Maritime Dangerous Goods code  
**NIOSH:** National Institute of Occupational Safety and Health (U.S.)  
**NFPA:** National Fire Protection Association (US)  
**NTP:** National Toxicology Program (US)  
**PEL:** Permissible Exposure Limit  
**SARA:** Superfund Amendments and Reauthorization Act (U.S. EPA)  
**STEL:** Short Term Exposure Limit (15 minute Time Weighted Average)  
**STOT:** Specific Target Organ Toxicity (GHS Classification)  
**TLV:** Threshold Limit Value  
**TSCA:** Toxic Substances Control Act (U.S.)  
**TWA:** Time Weighted Average (exposure for 8-hour workday)  
**VOC:** Volatile Organic Compounds  
**WHMIS:** Canadian Workplace Hazardous Materials Information System

### Full Text of H – Phrases Under Section 3

**H351:** Suspected of causing cancer.

### Disclaimer

Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

### Internal

#### FOR INTERNAL USE ONLY

A Component 70-9: XCOM3B	B Component 70-9: XCOM3A XCORR
-----------------------------	--------------------------------------

**1. Identification**

**Product Identification**

**Product Identifier:** **B Component RPS-70-9**  
**Recommended Use:** RPS-70-9 Epoxy Coating is a protective coating for use with steel, concrete and wood.  
**Use Restrictions:** For industrial use only. To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at [strongtie.com](http://strongtie.com).

**Company Identification**

**Company:** Simpson Strong-Tie Company Inc.  
**Address:** 5956 W. Las Positas Blvd.  
 Pleasanton, CA 94588 USA  
**Phone:** 1-800-999-5099  
**Website:** [www.strongtie.com](http://www.strongtie.com)  
**Emergency:** 1-800-535-5053 (US/Canada)  
 1-352-323-3500 (International)

For most current SDS, please visit our website at [www.strongtie.com/sds](http://www.strongtie.com/sds)

**2. Hazard Identification**

**General Information**

RPS-70-9 Epoxy Coating is a 100% solids, two part system (2A:1B mix) designed to protect steel, wood, and concrete surfaces in commercial and industrial settings. It is available in brown, limestone, light gray, brick red, and white. The two parts of this product have been assessed individually according to the Globally Harmonized System (GHS). The mixed product can be assumed to carry the hazards of each component until the product has been fully cured. This Safety Data Sheet covers hazards and responses for Component B. See Component A Safety Data Sheet for complete product information.

**Component B GHS Classification**

**Product Classification according to HazCom2012 (GHS)**

<b>Physical Hazards:</b>	Flammable Liquids	Category 4	H227: Combustible liquid
<b>Health Hazards</b>	Acute Toxicity, Oral	Category 4	H302: Harmful if swallowed
	Acute Toxicity, Dermal	Category 4	H312: Harmful in contact with skin
	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns and eye damage
	Serious Eye Damage/Irritation	Category 1	H318: Causes severe eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
	Reproductive Toxicity	Category 2	H361: May cause damage to fertility or the unborn child
<b>Environmental Hazards:</b>	Acute Environmental Hazard	Category 1	H400: Very toxic to aquatic life
	Chronic Environmental Hazard	Category 1	H410: Very toxic to aquatic life with long lasting effects

**Main Symptoms:** Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. Long term exposure may cause chronic effects.

**GHS Label Elements**



**Contains:** Amines; Phenols; Fatty acids, c18-unsatd.  
**Signal Word:** **DANGER!**  
**Hazard Statements:** H227: Combustible liquid.  
 H302: Harmful if swallowed.  
 H312: Harmful if in contact with skin.  
 H314: Causes severe skin burns and eye damage.  
 H318: Causes severe eye damage.  
 H317: May cause an allergic skin reaction.



	H361:	Suspected of damaging fertility or the unborn child.
	H400:	Very toxic to aquatic life.
	H410:	Very toxic to aquatic life with long lasting effects.
<b>Precautionary Statements:</b>		
<b>Prevention:</b>	P201:	Obtain special instructions before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P210:	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
	P261:	Avoid breathing dust, mist, or vapor.
	P264:	Wash thoroughly after handling.
	P270:	Do not eat, drink, or smoke when using this product.
	P271:	Use only outdoor or in a well-ventilated area.
	P272:	Contaminated clothing should not be allowed out of the workplace.
	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/clothing/eye protection/face protection.
<b>Response:</b>	P301+P330+P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P312:	Call a POISON CENTER/doctor if you feel unwell.
	P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P363:	Wash contaminated clothing before reuse.
	P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P308+P313:	If exposed or concerned: Get medical attention/advice.
	P370+P378:	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
	P391:	Collect spillage.
<b>Storage:</b>	P403+P233+P235:	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
	P405:	Store locked up.
<b>Disposal:</b>	P501:	Dispose of contents/container in accordance with local/regional regulations.

**Supplemental Label Information:** None known.

**Hazards Not Otherwise Classified (HNOC)**

The above hazards are for the uncured B component of RPS-70-9. Upon combination with the A component, an innocuous solid which does not present any immediate hazards is formed. Upon grinding or cutting through the cured product, the following hazards may apply. Ensure that good work practices, and the necessary precautionary measures, are taken to maintain safe use of the product.



Chronic Health

<b>Health Hazard:</b>	Carcinogenicity	Category 1A
<b>OSHA Hazard:</b>	Combustible Dust	
<b>Hazard Statements:</b>	May cause cancer. Can form explosive air-dust mixtures, avoid creating dust.	
<b>Precautionary Statements:</b>	Do not breathe dust. Do not allow dust to build up on surfaces.	

**3. Composition Information**

**General Information**

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

**List of abbreviations and symbols:**

Classification: Global Harmonized System Classifications

*The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.*

**Composition – All concentrations are in percent by weight unless otherwise indicated.**

Chemical Name	Weight %	CAS Number	EC Number
Polymeric Cycloaliphatic Amines <b>Classifications:</b> Acute Tox. 4: H302, Skin Corr. 1B: H314	10-30	135108-88-2	603-894-6
Tetraethylenepentamine <b>Classifications:</b> Acute Tox. 4: H302+H312, Skin Corr. 1B: H314, Eye Corr. 1: H318, Aquatic 2: H401+H411	1-10	112-57-2	203-986-2
Nonylphenol <b>Classifications:</b> Acute Tox. 4: H302, Skin Corr. 1B: H314, Repr. 2 : H361, Aquatic 1: H400+H410	1-10	84852-15-3	284-325-5
Diethylenetriamine <b>Classifications:</b> Acute Tox. 4: H302+H312, Skin Corr. 1B: H314, Eye Corr. 1: H318, Skin Sens. 1 : H317	1-5	111-40-0	203-865-4
Bisphenol-A <b>Classifications:</b> Eye Corr. 1: H318, Skin Sens. 1: H317, Repr. 2: H361, STOT SE 3: H335	1-5	80-05-7	201-245-8
Fatty acids, C18-unsatd. Dimers <b>Classifications:</b> Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, STOT SE 3: H335	1-5	68410-23-1	614-452-7
Crystalline Silica, Quartz <b>Classifications:</b> Carc. 1A: H350, STOT RE 2: H373	< 1	14808-60-7	238-878-4

#### 4. First-Aid Measures

##### General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

##### Routes of Exposure

**Eye Contact:** Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, **consult a physician immediately.**

**Skin Contact:** Remove contaminated clothing and product; wash affected area with soap and water. If redness, burning, or swelling persists, **consult a physician.**

**Ingestion:** Rinse mouth. If you feel unwell, **consult a physician.**

**Inhalation:** Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

##### Most Important Symptoms

Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. Rash / dermatitis. Irritation or burns to the gastrointestinal tract and respiratory system. Permanent eye damage including blindness could result.

#### 5. Fire-Fighting Measures

**Suitable Extinguishing Media:** Water fog, carbon dioxide, dry chemical powder, aqueous foam.

**Additional Information:** None known.

**Hazards during Fire-Fighting:** Irritating and toxic fumes may be produced at high temperature. Hazardous gases/vapors produced are carbon monoxide, carbon dioxide, oxides of nitrogen, cyanide, aldehydes, and miscellaneous hydrocarbons.

**Fire-Fighting Procedures:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

#### 6. Accidental Release Measures

##### Personal Precautions

**Non-emergency personnel:** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

**Emergency personnel:** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

##### Clean-Up Methods

# RPS-70-9 Epoxy Coating

## SAFETY DATA SHEET

- Small spills (uncured):** Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.
- Large spills (uncured):** Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water.
- Cured Material:** Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measure; do not allow dust to build up.

### Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and Storage

### Handling

Wear appropriate personal protective equipment. Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid prolonged exposure. Provide adequate ventilation. Avoid breathing dust, mist, or vapors. When in use do not eat, drink, or smoke. Wash thoroughly after handling. Wash contaminated clothing before reuse. Pregnant women should not work with the product, if there is the least risk of exposure. Do not empty into drains, avoid release to the environment. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products, the products must be properly installed and used in accordance with the installation instructions and design limits provided by Simpson Strong-Tie.

### Storage

Store in a closed container away from incompatible materials (Section 10 of the SDS). Keep in original container. Keep container tightly closed. Store in a cool, dry place out of direct sunlight, between 40-95°F (4-35°C). Keep away from heat and sources of ignition. Protect from physical damage.

## 8. Exposure Controls / Personal Protection

### Personal Protective Equipment

- Protective Measure:** Wear appropriate personal protective equipment.
- Eye Protection:** Wear chemical splash goggles or safety glasses with side shield.
- Hand Protection:** Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
- Skin and Body Protection:** Wear long sleeve shirts/long pants and other clothing as required to minimize contact.
- Respirator Protection:** A respirator is not required during normal use of this product in properly ventilated areas. An approved respirator should be worn whenever workplace conditions warrant respirator use.
- General Hygiene:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### Engineering Controls

If exposure limits have not been established, maintain airborne levels to an acceptable level. When using indoors good general ventilation should be used. Provide eyewash station and emergency shower.

### Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Diethylenetriamine* (CAS 111-40-0)	N/E	1 ppm	1 ppm
Tetraethylenepentamine* (CAS 112-57-2)	1 ppm	1ppm	1 ppm (aerosol)
Quartz (CAS 14808-60-7)	$\frac{10}{\%SiO_2 + 2} \text{ mg}/m^3$	0.025 mg/m <sup>3</sup> (respirable)	0.05 mg/m <sup>3</sup> (respirable)

\*Skin Designation: Material can be absorbed through the skin.

## 9. Physical and Chemical Properties

- |                        |         |                                |              |
|------------------------|---------|--------------------------------|--------------|
| <b>Physical State:</b> | Liquid  | <b>Freezing/Melting Point:</b> | N/E          |
| <b>Form:</b>           | Liquid  | <b>Boiling Point:</b>          | N/E          |
| <b>Color:</b>          | Amber   | <b>Flash Point:</b>            | 175°F (79°C) |
| <b>Odor:</b>           | Ammonia | <b>Evaporation Rate:</b>       | N/E          |

# RPS-70-9 Epoxy Coating

## SAFETY DATA SHEET

<b>Odor Threshold:</b>	N/E	<b>Specific Gravity:</b>	0.99
<b>pH:</b>	N/E	<b>Viscosity:</b>	N/E
<b>Flammability:</b>	N/E	<b>U/L Flammability:</b>	N/E
<b>Vapor Pressure:</b>	N/E	<b>Vapor Density:</b>	N/E
<b>Solubility:</b>	Slight	<b>Kow:</b>	N/E
<b>Decomposition:</b>	N/E	<b>VOC(A+B):</b>	12 g/L

### 10. Stability and Reactivity

<b>Reactivity:</b>	This product is stable and non-reactive under normal conditions.
<b>Chemical Stability:</b>	Stable under normal storage conditions.
<b>Condition to Avoid:</b>	High heat and open flame.
<b>Substances to Avoid:</b>	Oxidizing agents and acids.
<b>Hazardous Reactions:</b>	Hazardous polymerization will not occur.
<b>Decomposition Products:</b>	Carbon dioxide, carbon monoxide, oxides of nitrogen and other organic compounds.

### 11. Toxicological Information

#### Likely Routes of Exposure

<b>Ingestion:</b>	Harmful if swallowed. Causes digestive tract burns.
<b>Inhalation:</b>	Prolonged inhalation may cause mild respiratory irritation.
<b>Skin contact:</b>	Causes skin burns. May cause an allergic skin reaction. Harmful in contact with skin.
<b>Eye contact:</b>	Causes severe eye damage.
<b>Symptoms:</b>	Symptoms include burns, rash, redness, itching, tearing, swelling, and blurred vision; shortness of breath, discomfort in the chest, or coughing.

#### Information on Toxicological Effects

##### Acute Effects

**Toxicity:** Harmful if swallowed. Harmful in contact with skin.

Component	Estimate
RPS-70-9 Component B Toxicity Estimate	
<b>Acute, Oral, LD50</b>	800
<b>Acute, Dermal, LD50</b>	1700

<b>Skin corrosion/irritation:</b>	Causes severe skin burns and eye damage.
<b>Eye damage/eye irritation:</b>	Causes serious eye damage.
<b>Respiratory sensitization:</b>	No data available.
<b>Skin sensitization:</b>	May cause skin sensitization by contact.
<b>Aspiration hazard:</b>	No data available.
<b>Specific target organ toxicity Single exposure:</b>	No data available.

##### Chronic Effects

<b>Germ cell mutagenicity:</b>	The available data does not indicate that any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity:</b>	This component contains a chemical that is considered a carcinogen in respirable form. Exposure to this carcinogen is only likely when grinding or cutting cured product. Ensure good work practice and use of personal protective equipment as needed to control exposure to processing dust. Components of this product are suspected of damaging fertility or the unborn child.
<b>Reproductive toxicity:</b>	Components of this product are suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity Repeated exposure:</b>	No data available.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Quartz (CAS 14808-60-7)	< 1	1	KNOWN	A2	CA65
Bisphenol-A (CAS 80-05-7)	1-5	---	---	---	CA65
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected CA65 – California Prop 65					

**Further Information**

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

**12. Ecological Information**

**General Information**

Information given is based on data on the components and the ecotoxicology of similar products. The product is classified as very toxic to aquatic life with long lasting effects. Avoid release to the environment.

**Supporting Data**

Component	Estimate
RPS-70-9 Component B Toxicity Estimate	
<b>Aquatic, Fish, LC50</b>	5 mg/l, 96 hours
<b>Aquatic, Crustacea, EC50</b>	2 mg/l, 48 hours

**Persistence and degradability:** No data available.  
**Bioaccumulative potential:** No data available for the product.  
**Mobility in soil:** No data available.

**Other Adverse Effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

**13. Disposal Considerations**

**Waste Disposal of Substance:** Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

**Container Disposal:** Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**Disposal of Cured Product:** Chip or grind off surface. Solid material does not need special disposal consideration.

**14. Transportation Information**

**UN number:** UN2735  
**UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Polyamindoamine), 8, II, Marine Pollutant  
**Precautions:** Marine Pollutant  
**Required Labels:** 8  
**ERG Code (IATA):** 8L  
**EmS (IMDG):** F-A, S-B

**Additional Information**

**Special precautions for user:** Read safety instructions, SDS and emergency procedures before handling.  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Not Applicable

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

**15. Regulatory Information**

**United States**

**Federal Regulations:** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):**  
 Nonyl Phenol (CAS 84852-15-3) LISTED

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed.  
**CERCLA Hazardous Substance List (40 CFR 302.4):** Not listed.

# RPS-70-9 Epoxy Coating

## SAFETY DATA SHEET

### Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:				
Immediate	Delayed	Fire	Pressure	Reactivity
Yes	Yes	Yes	No	No

SARA 302 Extremely hazardous substance: No

SARA 311/312 Hazardous chemical: Yes

### SARA 313 (TRI reporting):

Component	CAS	% In Blend (approx.)
Nonyl Phenol	84852-15-3	1-5
Bisphenol A	80-05-7	< 1

### US. California Proposition 65:

**WARNING:** This product can expose you to chemicals which are known to the State of California to cause cancer, reproductive harm, or other birth defects. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Quartz (CAS 14808-60-7)	< 1	1	KNOWN	A2	CA65 (Carcinogenic)
Bisphenol-A (CAS 80-05-7)	1-5	---	---	---	CA65 (Reproductive)

IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 - Not classifiable as to carcinogenicity 4 - Probably not carcinogenic  
 NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen  
 ACGIH - A1 - Confirmed carcinogen A2 - Suspected carcinogen A3 - Animal carcinogen A4 - Not classified A5 - Not suspected  
 CA65 - California Prop 65

### Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

### International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work.

This product is not subject to or not applicable for any of the following International Regulations: **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

### International Inventories

<b>Australia</b>	One or more components of this product are not listed on the Australian Inventory of Chemical Substances (AICS).
<b>Canada</b>	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
<b>China</b>	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)
<b>Europe</b>	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
<b>Japan</b>	One or more components in this product are not listed on the Inventory of Existing and New Chemical Substances (ENCS).
<b>Korea</b>	All components of this product are included on the Existing Chemicals List (ECL)
<b>New Zealand</b>	One or more components of this product have an unknown status on the New Zealand Inventory. Contact Simpson Strong-Tie Environmental Health and Safety if the status of this product on the inventory is desired.
<b>Philippines</b>	All components in this product are listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
<b>United States &amp; Puerto Rico</b>	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

**16. Other Information**

Date Prepared or Revised: November 2021  
Supersedes: July 2020  
Contact Simpson Strong-Tie Environmental Health and Safety at [EHS@strongtie.com](mailto:EHS@strongtie.com).

**Abbreviations**

**ACGIH:** American Conference of Governmental Industrial Hygienists  
**CAS No.:** Chemical Abstract Service Registry Number  
**CERCLA:** Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)  
**HPR:** Hazardous Product Regulations (Canada)  
**EPA:** Environmental Protection Agency (U.S.)  
**GHS:** Globally Harmonized System of Classification and Labeling of Chemicals  
**HMIS:** Hazardous Materials Identification System  
**IARC:** International Agency for Research on Cancer  
**IATA:** International Air Transport Association  
**IMDG:** International Maritime Dangerous Goods code  
**NIOSH:** National Institute of Occupational Safety and Health (U.S.)  
**NFPA:** National Fire Protection Association (US)  
**NTP:** National Toxicology Program (US)  
**PEL:** Permissible Exposure Limit  
**SARA:** Superfund Amendments and Reauthorization Act (U.S. EPA)  
**STEL:** Short Term Exposure Limit (15 minute Time Weighted Average)  
**STOT:** Specific Target Organ Toxicity (GHS Classification)  
**TLV:** Threshold Limit Value  
**TSCA:** Toxic Substances Control Act (U.S.)  
**TWA:** Time Weighted Average (exposure for 8-hour workday)  
**VOC:** Volatile Organic Compounds  
**WHMIS:** Canadian Workplace Hazardous Materials Information System

**Full Text of H – Phrases Under Section 3**

**H315:** May cause skin irritation.  
**H319:** Causes serious eye irritation.  
**H335:** May cause respiratory irritation.  
**H350:** May cause cancer.  
**H373:** May cause damage to organs through repeated exposure or prolonged contact.  
**H401:** Toxic to aquatic life.  
**H411:** Toxic to aquatic life with long lasting effects.

**Disclaimer**

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2021 Simpson Strong-Tie Company Inc.

**Internal**

**FOR INTERNAL USE ONLY**

A Component 70-9 :	B Component 70-9:
XCOM3B	XCOM3A
	XCORR