

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET

1. Identification

Product Identification

Product Identifier: A Component RPS-792LPL
Recommended Use: RPS-792LPL is a two-component, long pot life epoxy bonding agent for use for the maintenance of concrete in warm weather application.
Use Restrictions: For industrial use only. To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588 USA
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada) / 1-352-323-3500 (International)
For most current SDS, please visit our website at www.strongtie.com/sds.

2. Hazard Identification

General Information

RPS-792LPL Long Pot Life Epoxy Bonding Agent is a two part system (2:1 mix). The two parts of this product have been assessed according to Globally Harmonized System (GHS). The product is for use for concrete maintenance in warm weather situations, and can be used on both damp and dry concrete. The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. The fully cured product will be amber in color and is considered nonhazardous. This Safety Data Sheet covers hazards and responses for Component A. See the Component B Safety Data Sheet for complete product information.

Component A GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Skin Corrosion/Irritation	Category 2	H315: Causes skin irritation
	Serious Eye Damage/Irritation	Category 2	H319: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Chronic Environmental Hazard	Category 2	H411: Toxic to aquatic life with long lasting effects

Main Symptoms: Irritant effects. May cause rash/allergic reaction to the skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision.

GHS Label Elements



Contains: Bisphenol-A Based Epoxy Resin, Alkyl (C12-C14) glycidyl ether

Signal Word: **WARNING**

Hazard Statements:

H315:	Causes skin irritation.
H319:	Causes serious eye irritation.
H317:	May cause an allergic skin reaction.
H411:	Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention:	P201:	Obtain special instructions before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P261:	Avoid breathing mist or vapor.
	P264:	Wash hands thoroughly after handling.
	P272:	Contaminated work clothing should not be allowed out of the workplace.
	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET

SIMPSON

Strong-Tie

Response:	P302+P352:	IF ON SKIN: Wash with plenty of water.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364:	Take off contaminated clothing and wash before re-use.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P391:	Collect Spillage.
Storage:	P403+P235:	Store in a well-ventilated place. Keep cool.
	P405:	Store locked up.
Disposal:	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

Hazards Not Otherwise Classified (HNOC)

None known.

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classification: Globally Harmonized System Classifications

The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

Composition – All concentrations are in percent by weight unless otherwise indicated.

Chemical Name	Weight %	CAS Number	EC Number
Bisphenol-A Based Epoxy Resin	75-95	25068-38-6	500-033-5
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens.1: H317, Aquatic Chronic 2: H411			
Alkyl (C12-C14) Glycidyl Ether	1-25	68609-97-2	271-846-8
Classifications: Skin Irrit. 2: H315, Skin Sens. 1: H317			

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

Eye Contact:	Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, consult a physician immediately.
Skin Contact:	Remove contaminated clothing and product, immediately wash affected area with soap and water. Do not apply greases or ointments. If rash or irritation persists consult a physician.
Ingestion:	Rinse mouth immediately. Do not induce vomiting. Consult a physician.
Inhalation:	Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, consult a physician.

Most Important Symptoms

Irritant effects. Sensitization. Symptoms include itching, burning, redness, tearing, and blurred vision.

5. Fire-Fighting Measures

Suitable Extinguishing Media:	Extinguish with foam, carbon dioxide, dry powder, or water fog.
Additional Information:	None known.
Hazards during Fire-Fighting:	Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C). Do not allow run-off from fire-fighting to enter drains or water courses.
Fire-Fighting Procedures:	Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool

containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Non-emergency personnel: Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or open flames). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

Small spills (uncured): Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.

Large spills (uncured): Stop the flow of material, if possible without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas. Keep combustibles away from spilled material.

Cured Material: Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measures; do not allow dust to build up.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Pregnant women should not work with the product, if there is the least risk of exposure. When using, do not eat, drink or smoke. Do not breathe dust, mist or vapor. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products, the products must be properly installed and used in accordance with the design limits provided by Simpson Strong-Tie.

Storage

Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a cool, dry place out of direct sunlight, between 40-95°F (4-35°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Protect against physical damage. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure: Wear appropriate personal protective equipment.

Eye Protection: Wear chemical splash goggles or safety glasses with side shield.

Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.

Skin and Body Protection: Wear long sleeve shirt/long pants and other clothing as required to minimize contact.

Respirator Protection: A respirator is not required during normal use of this product in properly ventilated areas. Approved respirators should be worn when workplace conditions warrant respirator use.

General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended. Ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

Exposure Limits

No exposure limits noted for components.

9. Physical and Chemical Properties

Physical State:	Liquid	Freezing/Melting Point:	N/E
Form:	Paste	Boiling Point:	>428°F (>220°C)
Color:	Clear Amber	Flash Point:	>250°F (>121°C)
Odor:	Sweet	Evaporation Rate:	N/A
Odor Threshold:	N/E	Specific Gravity:	1.13
pH:	N/E	VOC (A+B):	0 g/L
Flammability:	N/E	U/L Flammability:	N/E
Vapor Pressure:	Not Volatile	Vapor Density:	N/E
Solubility:	Insoluble	Kow:	N/E
Decomposition:	N/E	Viscosity:	N/E

10. Stability and Reactivity

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Oxidizing agents, acids, organic bases, and amines.
Hazardous Reactions:	Hazardous polymerization will not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion:	Ingestion may cause irritation to the gastrointestinal tract.
Inhalation:	This material is a viscous liquid to semi-solid which does not easily form vapors.
Skin contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Symptoms:	Irritant effects. Sensitization. Symptoms include itching, burning, redness and tearing.

Information on Toxicological Effects

Acute Effects

Toxicity: Not expected to be acutely toxic.

Component	Estimate
RPS-792LPL Component A Toxicity Estimate	
Acute, Oral, LD50	>9000
Acute, Dermal, LC50	>2000

Skin corrosion/irritation:	Causes skin irritation.
Eye damage/eye irritation:	Causes serious eye irritation.
Respiratory sensitization:	No data available.
Skin sensitization:	May cause an allergic skin reaction.
Aspiration hazard:	No data available.
Specific target organ toxicity	
Single exposure:	No data available.

Chronic Effects

Germ cell mutagenicity:	The available data does not indicate that any components of this product present at greater than 0.1% is mutagenic or genotoxic.
Carcinogenicity:	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity:	No data available.
Specific target organ toxicity	
Repeated exposure:	No data available.

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. The product is classified as toxic to aquatic life with long lasting effects. Avoid release to the environment.

Supporting Data

Component	Estimate
RPS-792LPL Component A Toxicity Estimate	
Aquatic , Fish, LC50	50 mg/l, 96 hours
Aquatic , Crustacea, EC50	5 mg/l, 48 hours
Aquatic , Algae, EC50	800 mg/l, 72 hours

Persistence and degradability: This product is not expected to be readily biodegradable.

Bioaccumulative potential: No data available for this product.

Mobility in soil: This product is insoluble in water and is non-volatile.

Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Considerations

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal of Cured Product: Chip or grind off surface. If you are grinding or cutting set product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Solid material does not need special disposal consideration.

14. Transportation Information

RPS-792LPL Component A is not regulated for ground transportation by the USDOT; check specific requirements for other regions and other shipping methods.

UN number: UN3082

UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorohydrin Resin), 9, III, Marine Pollutant

Transportation Class: 9

Precautions: Other Hazard

Packing Group: III

Environment Hazard: Yes

Required Labels: 9

ERG Code (IATA): 9L

EmS (IMDG): F-A, S-F

Additional Information

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

This substance/mixture is not intended to be transported in bulk.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET



CERCLA Hazardous Substance List (40 CFR 302.4):

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:				
Immediate	Delayed	Fire	Pressure	Reactivity
Yes	Yes	No	No	No

SARA 302 Extremely hazardous substance: No
 SARA 311/312 Hazardous chemical: Yes
 SARA 313 (TRI reporting): Not regulated.

California Proposition 65:

WARNING: This product can expose you to chemicals which are known to the State of California to cause cancer, reproductive harm, or other birth defects. For more information, go to www.P65Warnings.ca.gov.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Oxirane, 2-(phenoxyethyl)- (CAS 122-60-1)	Trace	2B	---	A3	CA65 (Carcinogenic)
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 - Not classifiable as to carcinogenicity 4 - Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH - A1 - Confirmed carcinogen A2 - Suspected carcinogen A3 - Animal carcinogen A4 - Not classified A5 - Not suspected CA65 - California Prop 65					

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
China	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)
Europe	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
Japan	One or more components in this product are not listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	All components of this product are included on the Existing Chemicals List (ECL)
New Zealand	All components of this product are included on the New Zealand Inventory.
Philippines	All components in this product are listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

16. Other Information

Date Prepared or Revised: December 2021

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET



Supersedes: May 2020
Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com.

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HPR:	Hazardous Product Regulations (Canada)
DOT:	Department of Transportation (U.S.)
EPA:	Environmental Protection Agency (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2021 Simpson Strong-Tie Company Inc

Internal

FOR INTERNAL USE ONLY

A Component 792LPL: XCOM3B	B Component 792LPL: XCOM3B XCORR
-------------------------------	--

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET



1. Identification

Product Identification

Product Identifier: B Component RPS-792LPL
Recommended Use: RPS-792LPL is a two-component, long pot life epoxy bonding agent for use for the maintenance of concrete in warm weather application.
Use Restrictions: For industrial use only. To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada)
1-352-323-3500 (International)

For most current SDS, please visit our website at www.strongtie.com/sds.

2. Hazard Identification

General Information

RPS-792LPL Long Pot Life Epoxy Bonding Agent is a two part system (2:1 mix). The two parts of this product have been assessed according to Globally Harmonized System (GHS). The product is for use for concrete maintenance in warm weather situations, and can be used on both damp and dry concrete. The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. The fully cured product will be amber in color and is considered nonhazardous. This Safety Data Sheet covers hazards and responses for Component B. See the Component A Safety Data Sheet for complete product information.

Component B GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Acute Toxicity, Oral	Category 4	H302: Harmful if swallowed
	Acute Toxicity, Dermal	Category 4	H312: Harmful in contact with skin
	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns and eye damage
	Serious Eye Damage/Irritation	Category 1	H318: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Reproductive Toxicity	Category 2	H361: Suspected of damaging fertility or the unborn child
	Acute Environmental Hazard	Category 1	H400: Very toxic to aquatic life
	Chronic Environmental Hazard	Category 1	H410: Very toxic to aquatic life with long lasting effects

Main Symptoms: Damage to the eyes and skin. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. May cause rash/allergic reaction to the skin. Symptoms include burns, stinging, tearing, redness, swelling, and blurred vision. Long term exposure may cause chronic effects.

GHS Label Elements



Contains: Amines, Phenols
Signal Word: DANGER!
Hazard Statements:
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H332: Harmful if inhaled.
H314: Causes severe skin burns and eye damage.

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET



	H318:	Causes serious eye damage.
	H317:	May cause an allergic skin reaction.
	H361:	Suspected of damaging fertility or the unborn child.
	H400:	Very toxic to aquatic life.
	H410:	Very toxic to aquatic life with long lasting effects.
Precautionary Statements:		
Prevention:	P201:	Obtain special instructions before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P261:	Avoid breathing mist or vapor.
	P264:	Wash hands thoroughly after handling.
	P270:	Do not eat, drink, or smoke when using this product.
	P271:	Use only outdoor or in a well-ventilated area.
	P272:	Contaminated clothing should not be allowed out of the workplace.
	P273:	Avoid release to environment.
	P280:	Wear protective gloves/clothing/eye protection/face protection.
Response:	P301+P330+P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303+P361+P353:	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P363:	Wash contaminated clothing before reuse.
	P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P308+P313:	If exposed or concerned: Get medical attention/advice.
	P312:	Call a poison center/doctor if you feel unwell.
	P391:	Collect spillage.
Storage:	P403+P233+P235:	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
	P405:	Store locked up.
Disposal:	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

Hazards Not Otherwise Classified (HNOC)

None known.

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classification: Globally Harmonized System Classifications

The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

Composition – All concentrations are in percent by weight unless otherwise indicated.

Chemical Name	Weight %	CAS Number	EC Number
Methyleneoxide, polymer with benzenamine, hydrogenated Classifications: Acute Tox. 4: H302, Skin Corr. 1B: H314	20-70	125108-88-2	603-894-6
Fatty acids, C18-unsat., dimers, reactions products with polyethylenepolyamines Classifications: Skin Irrit. 2: H315, Eye Dam. 1: H318, Skin Sens. 1: H317	1-10	68410-23-1	614-452-7
Nonyl phenol Classifications: Acute Tox. 4: H302, Skin Corr. 1B: H314, Repr. 2: H361, Aquatic 1: H400+H410	1-10	84852-15-3	284-325-5
Tetraethylenepentamine Classifications: Skin Corr. 1B: H314, Eye Dam. 1: H318, Aquatic Chronic 2: H411	1-10	112-57-2	203-986-2
Tris-2,4,6-(dimethylaminomethyl)phenol Classifications: Acute Tox. 4: H302, Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317	1-10	90-72-2	202-013-9

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET

SIMPSON

Strong-Tie

Chemical Name	Weight %	CAS Number	EC Number
Bis(dimethylaminomethyl)phenol	1-5	71074-89-0	275-162-0
Classifications: Acute Tox. 4: H302+H312, Skin Corr. 1B: H314, Eye Dam. 1: H318, STOT SE 3: H335			
Triethylenetetramine	< 1	112-24-3	203-950-6
Classifications: Acute Tox. 4: H302+H312, Skin Corr. 1B: H314, Skin Sens. 1: H317, Aquatic Chronic 3: H412			

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

Eye Contact: Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If you experience redness, burning, blurred vision, or swelling **consult a physician immediately.**

Skin Contact: Remove contaminated clothing and product, immediately wash affected area with soap and water. Do not apply greases or ointments. If rash or irritation occurs **consult a physician.**

Ingestion: Rinse mouth immediately. Do not induce vomiting. **Consult a physician.**

Inhalation: Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

Most Important Symptoms

Damage to the eyes and skin. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. Rash/allergic reaction to the skin. Symptoms include burns, stinging, tearing, redness, swelling, and blurred vision.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Additional Information: Can form explosive air-dust mixtures, avoid creating dust.

Hazards during Fire-Fighting: During a fire, gases hazardous to health may be formed.

Fire-Fighting Procedures: Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Non-emergency personnel: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

Small spills (uncured): Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.

Large spills (uncured): Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water.

Cured Material: Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust. Take precautionary measures; do not allow dust to build up.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. Pregnant women should not work with the product, if there is the least risk of exposure. When using, do not eat, drink or smoke. Do not breathe dust, mist or vapor. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices. To obtain optimal performance from Simpson Strong-Tie products, the products must be properly installed and used in accordance with the design limits provided by Simpson Strong-Tie.

Storage

Store locked up. Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a cool, dry place out of direct sunlight, between 40-95°F (4-35°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Protect against physical damage. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure:	Wear appropriate personal protective equipment.
Eye Protection:	Wear chemical splash goggles or safety glasses with side shield.
Hand Protection:	Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection:	Wear long sleeve shirt/long pants and other clothing as required to minimize contact. In case of dust production, dust-proof clothing. Avoid contact with unhardened cement products, if contact occurs wash immediately with soap and water.
Respirator Protection:	Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of dust are expected to exceed exposure limits.
General Hygiene:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended. Ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Tetraethylenepentamine* (CAS 112-57-2)	1 ppm	1 ppm	1 ppm (aerosol)

*Skin Designation: Material can be absorbed through the skin.

9. Physical and Chemical Properties

Physical State:	Liquid	Freezing/Melting Point:	N/E
Form:	Liquid	Boiling Point:	N/E
Color:	Dark Amber	Flash Point:	266°F (130°C)
Odor:	Ammonia	Evaporation Rate:	N/E
Odor Threshold:	N/E	Specific Gravity:	0.95
pH:	N/E	VOC (A+B):	0 g/L
Flammability:	N/E	U/L Flammability:	N/E
Vapor Pressure:	N/E	Vapor Density:	N/E
Solubility:	Slight	Kow:	N/E
Decomposition:	N/E	Viscosity:	N/E

10. Stability and Reactivity

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Oxidizing agents and acids.
Hazardous Reactions:	Hazardous polymerization will not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion: Harmful if swallowed. Causes digestive tract burns.
Inhalation: This material is a viscous liquid to semi-solid which does not easily form vapors.
Skin contact: Harmful in contact with skin. Causes skin burns. May cause an allergic skin reaction.
Eye contact: Causes serious eye damage.
Symptoms: Damage to the eyes and skin. Severe irritation or burns to the gastrointestinal tract and respiratory system. Rash. Symptoms include stinging, tearing, redness, swelling of the eyes, and blurred vision.

Information on Toxicological Effects

Acute Effects

Toxicity: Harmful if swallowed. Harmful in contact with skin.

Component	Estimate
RPS-792LPL Component B Toxicity Estimate	
Acute, Oral, LD50	453
Acute, Dermal, LD50	1809

Skin corrosion/irritation: Causes severe skin burns and eye damage.
Eye damage/eye irritation: Causes severe eye damage.
Respiratory sensitization: No data available.
Skin sensitization: May cause skin sensitization by contact.
Aspiration hazard: No data available.
**Specific target organ toxicity
Single exposure:** No data available.

Chronic Effects

Germ cell mutagenicity: The available data does not indicate that any components of this product present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity: This product is not considered a carcinogen by IARC, ACGIH, NTP, or OSHA
Reproductive toxicity: Components of this product are suspected of damaging fertility or the unborn child.
**Specific target organ toxicity
Repeated exposure:** No data available.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (Approx.)	IARC Monographs	NTP	ACGIH	Other
Nonyl Phenol (84852-15-3)	1-10	---	---	---	Limited evidence of reproductive toxicity (NOAEL >2000 ppm)
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected CA65 – California Prop 65					

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with certain pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. This material is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment

RPS-792LPL Long Pot Life Epoxy Bonding Agent
SAFETY DATA SHEET



Supporting Data

Component	Species	Test Result
Nonylphenol (CAS 84852-15-3)		
Aquatic , Fish, LC50	Winter Flounder	0.017 mg/l, 96 hours
Aquatic , Crustacea, EC50	Clam	0.0379 mg/l, 48 hours

Persistence and degradability: No data available for the product.
Bioaccumulative potential: No data available for the product.
Mobility in soil: No data available.

Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Considerations

Waste Disposal of Substance: Do not allow material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal of Cured Product: Chip or grind off surface. If you are grinding or cutting set product, ensure good work practice and use of personal protective equipment as needed to control respirable dust. Solid material does not need special disposal consideration.

14. Transportation Information

UN number: UN2735
UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Nonyl Phenol), 8, II, Marine Pollutant
Transportation Class: 8
Precautions: Corrosive, Other Hazard
Packing Group: II
Environment Hazard: Yes
Required Labels: 8
ERG Code (IATA): 8L
EmS (IMDG): F-A, S-B

Additional Information

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):
 Nonyl Phenol (CAS 84852-15-3) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.
CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:				
Immediate	Delayed	Fire	Pressure	Reactivity
Yes	Yes	No	No	No

RPS-792LPL Long Pot Life Epoxy Bonding Agent

SAFETY DATA SHEET



SARA 302 Extremely hazardous substance: No
SARA 311/312 Hazardous chemical: Yes
SARA 313 (TRI reporting):

Component	CAS	% In Blend (approx.)
Nonylphenol	84852-15-3	1-10

California Proposition 65:

WARNING: This product can expose you to chemicals which are known to the State of California to cause cancer, reproductive harm, or other birth defects. For more information, go to www.P65Warnings.ca.gov.

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified and labeled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work.

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
China	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)
Europe	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
Japan	All components in this product are listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	All components of this product are included on the Existing Chemicals List (ECL).
New Zealand	All components of this product are included on the New Zealand Inventory.
Philippines	All components in this product are listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.

16. Other Information

Date Prepared or Revised: December 2021
Supersedes: May 2020
Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com.

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HPR:	Hazardous Product Regulations (Canada)
DOT:	Department of Transportation (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HEPA:	High-Efficiency Particulate Air
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer

RPS-792LPL Long Pot Life Epoxy Bonding Agent**SAFETY DATA SHEET**

IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Full Text of H – Phrases Under Section 3

H315:	May cause skin irritation.
H319:	Causes serious eye irritation.
H335:	May cause respiratory irritation.
H411:	Toxic to aquatic life with long lasting effects.
H412:	Harmful to aquatic life with long lasting effects.

Disclaimer

Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2021 Simpson Strong-Tie Company Inc.

Internal**FOR INTERNAL USE ONLY**

A Component 792LPL: XCOM3B	B Component 792LPL: XCOM3B XCORR
-------------------------------	--