Custom-Order Nail Worksheet



Instructions for Ordering Custom Nails

Simpson Strong-Tie offers a wide variety of custom-order nail options through our distribution network. Provide a print with complete specifications or complete this worksheet and have your Simpson Strong-Tie dealer send it to us for a price quote and lead time estimate. Minimum quantities may apply.

What is your Application	n?			
Step 1: Choose Material				
Aluminum (Model No. SPEC NAIL NF)		Type 304 Stainless Steel (Model No. SPEC NAIL 304SS)		
Copper (Model No. SPEC NAIL NF)		Type 316 Stainless Steel (Model No. SPEC NAIL 316SS)		
Silicon Bronze (Model No. SPEC NAIL NF)		Other		
Monel (Model No. SPEC	C NAIL NF)			
Step 2: Choose Head Type		Step 8: Choose Point Type		
Brad	Headless	Chisel	Sheared	
Casing	Pyramid	Diamond	Other	
Clipped	Other			
Step 3: Choose Head SURFACE		Step 9: Choose Color / Finish (Optional)		
Checker Pattern	Flat / Smooth	Brown	Sienna	Passivated
Circle Pattern	Other	Gray	Tan	Other
Step 4: Specify Head Size (inches)		Redwood	White	
(Some head diameters not possible in some materials)		Step 10: Choose Washer Type and size (Optional)		
Step 5: Specify Length (inches)		EPDM	Stainless Washer with bonded EPDI	
(Length range ½" – 7")		3⁄8"	5/8"	
Step 6: Specify Diameter (inches or gauge)		5⁄8"	11/8"	
		Other	Other	
(Diameter range 0.049" - 0.238	8")			
Step 7: Choose Shank Type		Step 11: Choose Packaging		
Annular Ring	Spiral	1 lb. Box	25 lb. Bucke	et
Smooth	Other	5 lb. Box	Other	

Fasteners will be manufactured to the tolerances specified in ASTM F1667 unless otherwise specified.