



NO CURING BLANKETS? NO PROBLEM



LITHIUMCURE 1000

EXTERIOR CONCRETE CURING AGENT

SINAK LithiumCure 1000 is a zero VOC Curing Agent, Water-Cure Equivalent type, used to cure freshly placed concrete. LithiumCure 1000 creates an internal membrane deep within the concrete substrate, resulting in improved hydration, elimination of slab curl and improved abrasion resistance.

LithiumCure 1000 is recommended for use on exterior, colored, stamped, and textured concrete. LithiumCure 1000 is certified NSF-61 Potable Water safe and tested to exceed the performance of ASTM C-309 & ASTM C-1315.

LithiumCure 1000 permanently penetrates the concrete substrate and does not leave a film or residue. LithiumCure 1000 allows for the installation of sealers, line striping, traffic coatings in as soon as 5 days after concrete placement.

LithiumCure 1000 is available as a Type 1, 1-D, and 2 Class A cure.



ANSI/NSF-61
POTABLE WATER CERTIFIED



ELIMINATE SLAB CURL
CRAZING & CRACKING



COMPATIBLE WITH ALL SEALERS & COATINGS



IMPROVES
ABRASION RESISTANCE



SEAL 5 DAYS AFTER CONCRETE PLACEMENT