



VC-5™

VAPOR EMISSION CONTROL

SINAK VC-5™ is a ready-to-use, zero VOC Vapor Emission and Alkalinity Control System that eliminates flooring failures due to moisture, moisture vapor, and alkalinity emanating from or through the concrete. VC-5™ is proven to eliminate costly delays from moisture remediation and saves 7-21 days from the average construction schedule. VC-5™ provides long-term protection for all finished flooring and is listed as UL® GREENGUARD Gold Certified, super compliant with SCAQMD and contributes to LEED credits.



FEATURES & BENEFITS

- 20-YEAR LABOR, MATERIAL AND ADHESIVE BOND WARRANTY
- COMPATIBLE WITH ALL ADHESIVE AND FLOORING SYSTEMS
- UL® GREENGUARD GOLD CERTIFIED
- CONTRIBUTES TO LEED V4 CREDITS
- SAVES 7-21 DAYS FROM THE CONSTRUCTION SCHEDULE PER CONCRETE POUR

VC-5™ is designed for use on all structural and lightweight concrete to receive finished flooring, roofing, or coatings. VC-5™ warrants all subsequent materials with a 20-year non-prorated labor, material, and adhesive bond warranty. VC-5™ allows mechanical surface profiling up to ¼" amplitude. VC-5™ ensures compatibility and bond of all flooring adhesives, floor coverings, roofing systems, and surface treatments.

Use of VC-5™ allows for any flooring, coating, or roofing installation seven days after concrete placement. VC-5™ eliminates cure related cracking, crazing, and slab curl. VC-5™ is designed to replace all curing methods and Moisture Vapor Emission control systems while offering rapid slab access for accelerated construction schedules.



WHERE TO USE VC-5™

- STRUCTURAL & LIGHTWEIGHT CONCRETE
- RUBBER TILES & SHEETING
- VINYL COMPOSITION TILES
- SHEET VINYL
- CARPETS
- LAMINATE FLOORING
- HARDWOOD
- SPORT FLOORING
- EPOXY & URETHANE COATINGS
- UNDERLAYMENTS & RESURFACING SYSTEMS
- HOT & COLD APPLIED ROOFING
- ENGINEERED FLOORING