



PS-209 ELASTOMERIC SEALANT

Commercial Product Data Sheet

PS-209 Elastomeric Sealant is a flexible moisture-curing, self-levelling sealant designed for roofing applications where sealing membrane terminations, adhering dissimilar materials, and excellent low temperature performance characteristics are required. PS-209 will not shrink or lose volume in joint or surface applications and will not damage expanded polystyrene or other solvent-sensitive construction materials.

Contact Siplast for information on approved product uses.

USES: SEALANT

Standards	ASTM D920, Type S, Grade P, Class 25																			
Shelf Life	1 year (When Stored at 70°F (21°C) at 50% RH)																			
VOC Content	<19 g/L (ASTM D2369, EPA Method 24)																			
Service Temp. Range	-40°F – 200°F (-40°C – 93°C)																			
Coverage	Linear Feet per 28 oz Cartridge Width <table border="1"> <tr> <td></td> <td>1/8"</td> <td>1/4"</td> <td>3/8"</td> </tr> <tr> <td>Depth</td> <td>1/8"</td> <td>288</td> <td>145</td> <td>95</td> </tr> <tr> <td></td> <td>1/4"</td> <td></td> <td>71</td> <td>58</td> </tr> <tr> <td></td> <td>3/8"</td> <td></td> <td></td> <td>32</td> </tr> </table>		1/8"	1/4"	3/8"	Depth	1/8"	288	145	95		1/4"		71	58		3/8"			32
	1/8"	1/4"	3/8"																	
Depth	1/8"	288	145	95																
	1/4"		71	58																
	3/8"			32																

PRODUCT INFORMATION

Application

Refer to the applicable Siplast Technical Guide for detailed application information. Note that PS-209 is a self-levelling product and should be applied accordingly.



Storage and Handling

All Siplast sealant products should be stored on a clean, flat surface. Care should be taken that cartridges are not crushed or punctured. All roofing products should be stored in a dry, cool place out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation. Storage under high-temperature/humidity conditions will significantly reduce the shelf life.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 45 in x 48 in (114 cm x 122 cm) wooden pallet
 Cartridges Per Carton: 12
 Cartons Per Pallet: 40
 Weight Per Carton: 40 lb (18.1 kg)