

# PS-715 NS ELASTOMERIC SEALANT

## Commercial Product Data Sheet



PS-715 NS Elastomeric Sealant is a moisture-curing, non-slump sealant designed for roofing applications where dynamic joint movement, adhering dissimilar materials, and excellent low temperature durability are required. PS-715 NS will not damage expanded polystyrene or other solvent-sensitive construction materials.

Contact Siplast for information on approved product uses.

### USES: SEALANT

Standards	Canadian Spec CAN 19, 13-M82																
Color	Limestone Gray																
Shelf Life	1 year																
VOC Content	<15 g/L																
Service Temp. Range	40°F – 200°F (4°C – 93°C)																
Coverage	Linear Feet per 28 oz Cartridge Width <table border="1"> <thead> <tr> <th></th> <th>1/8"</th> <th>1/4"</th> <th>3/8"</th> </tr> </thead> <tbody> <tr> <th>Depth 1/8"</th> <td>288</td> <td>145</td> <td>95</td> </tr> <tr> <th>1/4"</th> <td></td> <td>71</td> <td>58</td> </tr> <tr> <th>3/8"</th> <td></td> <td></td> <td>32</td> </tr> </tbody> </table>		1/8"	1/4"	3/8"	Depth 1/8"	288	145	95	1/4"		71	58	3/8"			32
	1/8"	1/4"	3/8"														
Depth 1/8"	288	145	95														
1/4"		71	58														
3/8"			32														

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed application information.



#### Storage and Handling

All Siplast sealant products should be stored on a clean, flat surface. Care should be taken that cartridges are not crushed or punctured. All roofing products should be stored in a dry, cool place out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation. Storage under high-temperature/humidity conditions will significantly reduce the shelf life.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Primary Packaging: Cartridges  
 Pallet: 45 in x 48 in (114 cm x 122 cm) wooden pallet  
 Cartridges Per Carton: 12  
 Cartons Per Pallet: 40  
 Weight Per Carton: 40 lb (18.1 kg)

#### Listings, Approvals, & Certifications



Current copies of all Siplast Commercial Product Data Sheets & Safety Data Sheets are posted on our website at [www.siplast.com](http://www.siplast.com)  
 Rev Date 3/2023