



### USES: SEALANT

|                     |                                                                                                                                                                                                                                                                                                                          |      |      |      |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|-------|------|-----|-----|----|------|--|----|----|------|--|--|----|
| Standards           | Canadian Spec CAN 19, 13-M82                                                                                                                                                                                                                                                                                             |      |      |      |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
| Color               | Limestone Gray                                                                                                                                                                                                                                                                                                           |      |      |      |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
| Shelf Life          | 1 year                                                                                                                                                                                                                                                                                                                   |      |      |      |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
| VOC Content         | <15 g/L                                                                                                                                                                                                                                                                                                                  |      |      |      |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
| Service Temp. Range | 40°F – 200°F<br>(4°C – 93°C)                                                                                                                                                                                                                                                                                             |      |      |      |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
| Coverage            | <div>Linear Feet per 28 oz Cartridge<br/>Width</div> <table><tr><td></td><td>1/8"</td><td>1/4"</td><td>3/8"</td></tr><tr><td rowspan="3">Depth</td><td>1/8"</td><td>288</td><td>145</td><td>95</td></tr><tr><td>1/4"</td><td></td><td>71</td><td>58</td></tr><tr><td>3/8"</td><td></td><td></td><td>32</td></tr></table> |      | 1/8" | 1/4" | 3/8" | Depth | 1/8" | 288 | 145 | 95 | 1/4" |  | 71 | 58 | 3/8" |  |  | 32 |
|                     | 1/8"                                                                                                                                                                                                                                                                                                                     | 1/4" | 3/8" |      |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
| Depth               | 1/8"                                                                                                                                                                                                                                                                                                                     | 288  | 145  | 95   |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
|                     | 1/4"                                                                                                                                                                                                                                                                                                                     |      | 71   | 58   |      |       |      |     |     |    |      |  |    |    |      |  |  |    |
|                     | 3/8"                                                                                                                                                                                                                                                                                                                     |      |      | 32   |      |       |      |     |     |    |      |  |    |    |      |  |  |    |

## PS-715 NS ELASTOMERIC SEALANT

### Commercial Product Data Sheet

PS-715 NS Elastomeric Sealant is a moisture-curing, non-slump sealant designed for roofing applications where dynamic joint movement, adhering dissimilar materials, and excellent low temperature durability are required. PS-715 NS will not damage expanded polystyrene or other solvent-sensitive construction materials.

Contact Siplast for information on approved product uses.

### PRODUCT INFORMATION

#### Application

Refer to the applicable Siplast Technical Guide for detailed application information.



#### Storage and Handling

All Siplast sealant products should be stored on a clean, flat surface. Care should be taken that cartridges are not crushed or punctured. All roofing products should be stored in a dry, cool place out of direct exposure to the elements. Material should be handled so that it remains dry prior to and during installation. Storage under high-temperature/humidity conditions will significantly reduce the shelf life.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

#### Packaging

Primary Packaging: Cartridges  
Pallet: 45 in x 48 in (114 cm x 122 cm) wooden pallet  
Cartridges Per Carton: 12  
Cartons Per Pallet: 40  
Weight Per Carton: 40 lb (18.1 kg)