



PARABASE FS

Commercial Product Data Sheet

Parabase FS is a non-porous fiberglass base sheet designed for use under guaranteed Siplast Roof Systems in certain nailable applications. Parabase FS consists of a lightweight random fibrous glass mat impregnated and coated with a specifically formulated, high quality, oxidized asphalt, and a polyolefin film backing.

Contact Siplast for information on approved product uses.


**USES:
BASE PLY
BASE SHEET**

PRODUCT INFORMATION

Standards	ASTM D4601, Type II
Roll Length	Min: 108 ft (32.9 m)
Roll Width	Avg: 3.0 ft (0.91 m)
Coverage	3.0 Squares (27.9 m ²)
Coverage Weight Per Square	Min: 20 lb (0.9 kg/m ²)
Thickness	Avg: 47 mils (1.2 mm) Min: 39 mils (1.0 mm)
Laying Lines	3 in (76 mm) & 12.5 in (317.5 mm) Line Color: Yellow
Top Surfacing	Silica Parting Agent
Back Surfacing	Polyolefin Film

Application

Refer to the applicable Siplast Technical Guide for detailed application information and slope limitations. Parabase FS is lapped 3 inches (76 mm) side and end.



Storage and Handling

All Siplast roll roofing products should be stored on end on a clean, flat surface. Rolls should not be dropped on ends or edges or stored in a leaning position. Deformation resulting from these actions will make proper installation difficult. All roofing products should be stored in a dry place out of direct exposure to the elements and should not be double stacked. Material should be handled so that it remains dry prior to and during installation.

See product packaging and the Safety Data Sheet for specific information on the safe handling of this product.

Packaging

Pallet: 40 in x 48 in (102 cm x 122 cm) wooden pallet
Rolls Per Pallet: 20
Pallets Per Truckload: 18
Minimum Roll Weight: 60 lb (27.2 kg)

Listings, Approvals, & Certifications

