

Product	Description	Purpose	Application Method	Unit	Size	Coverage	Minimum Coverage Weight Per Square
PC-227 Elastomeric Roof Coating	100% acrylic, white roof coating with asphalt bleed blocking properties.	Roof coating for use in finished system protection and for providing increased energy efficiency.	Spray, brush, or roller	Pail or drum	5 gallon pail 55 gallon drum	See product data sheet	
PS-304 Elastomeric Sealant	Moisture-curing, non-slump, gun-grade sealant.	Sealant for use where finished membrane terminates at flanged metal components.	Professional caulking gun	Pail	Sixteen - 10.3 fluid ounce cartridges.	See product data sheet	
Paratherm Polyisocyanurate Roof Insulation	Rigid roof insulation board composed of a closed cell polyisocyanurate foam core bonded to fiberglass facers.	High thermal value insulation board for use over metal, nailable, and non-nailable roof decks.	Parafast Fasteners, hot asphalt, or approved adhesives	Board	4' x 4' (1.22 m x 1.22 m) or 4' x 8' (1.22 m x 2.44 m) boards. Thicknesses of 1" (25 mm) to 4" (102 mm).	See product data sheet	
Siplast Wood Fiberboard	General purpose wood fiberboard insulation panel.	Coverboard with Paratherm polyisocyanurate insulation, or for certain re-cover applications.	Parafast Fasteners, hot asphalt, or approved adhesives	Board	4' x 4' (1.22 m x 1.22 m) or 4' x 8' (1.22 m x 2.44 m) boards. Thicknesses of ½" (12.5 mm) to 1" (25 mm).	See product data sheet	
Paraslope	Asphalt encapsulated compressible aggregate.	Corrective material designed to address drainage problems in isolated areas without removing the existing membrane.	See product data sheet	Bag	3 cubic ft	Min. 21.5 board ft	Min. 24 lb