

Product	Description	Purpose	Application Method	Unit	Size	Coverage	Minimum Coverage Weight Per Square
Parabase	Asphalt coated fiberglass base sheet meeting ASTM D 4601, Type II	Mechanically fastened underlayment ply.	Mechanically fastened	Roll	3 ft (0.91 m) x 108 ft (59.9 m)	3 sq	24 lb
Parabase FS	Asphalt coated fiberglass base sheet meeting ASTM D 4601, Type II with polyolefin film backing.	Mechanically fastened underlayment ply.	Mechanically fastened	Roll	3 ft (0.91 m) x 108 ft (59.9 m)	3 sq	24 lb
Parabase Plus	Elastomeric asphalt coated fiberglass base sheet.	Mechanically fastened underlayment ply.	Mechanically fastened	Roll	3.28 ft (1 m) x 102 ft (31.2 m)	3 sq	30 lb
Paravent FS	Asphalt coated fiberglass base sheet with perforations of approximately 1.5" diameter and polyolefin film backing.	Apply dry to roof deck prior to application of membrane to provide controlled spot bonding.	Dry	Roll	3 ft (0.91 m) x 108 ft (59.9 m)	3 sq	24 lb
Paraglas	Asphalt coated fiberglass mat meeting ASTM D 2178, Type IV.	Ply felt for conventional built-up application, or as an underlayment ply.	Asphalt or mechanically fastened	Roll	3 ft (0.91 m) x 180 ft (59.9 m)	5 sq	12 lb