

Product	Description	Purpose	Application Method	Unit	Size	Coverage	Minimum Coverage Weight Per Square
Irex 30	High-melt, high ductility asphalt sheet, random glass mat-reinforced.	First ply of Veral composite, lapped minimum 3 inches side and end.	PA-100 Asphalt	Roll	3.28 ft (1 m) x 34 ft (10.36 m)	1 sq	72 lb
Irex 40	High-melt, high ductility asphalt sheet, random glass mat-reinforced.	First ply of Veral composite, lapped minimum 3 inches side and end.	PA-100 Asphalt or torch	Roll	3.28 ft (1 m) x 34 ft (10.36 m)	1 sq	85 lb
Irex HT	High-melt, high ductility asphalt sheet, glass mat/glass scrim-reinforced.	First ply of Veral composite, lapped minimum 3 inches side and end. For high tensile requirements.	PA-100 Asphalt or torch	Roll	3.28 ft (1 m) x 34 ft (10.36 m)	1 sq	85 lb
Irex PR	High-melt, high ductility asphalt sheet, fiberglass scrim/polyester mat reinforced.	First ply of Veral composite, lapped 4 inches side and end.	Mechanically fastened	Roll	3.28 ft (1 m) x 34 ft (10.36 m)	1 sq	85 lb