

Product Information Reference Chart

Product	Description	Purpose	Application Method	Unit	Size	Coverage	Minimum Coverage Weight Per Square
Veral Aluminum	Aluminum-clad asphalt elastomer sheet, glass mat/glass scrim reinforced.	Top ply of Veral composite, lapped 3 inches side and end.	PA-100 Asphalt or torch	Roll	3.28 ft. (1 m) x 33.5 ft.	1 sq.	92 lbs.
Veral Copper	Copper-clad asphalt elastomer sheet, glass mat/glass scrim reinforced.	Top ply of Veral composite, lapped 3 inches side and end.	Torch	Roll	3.28 ft. (1 m) x 25.25 ft.	$\frac{3}{4}$ sq.	109 lbs.
Veral Polar White Spectra	Aluminum-clad asphalt elastomer sheet, glass mat/glass scrim reinforced, polypropylene film backing, factory finished with Kynar 500™ two-coat, high-performance fluorocarbon color system.	Top ply of Veral composite, lapped 3 inches side and end.	Torch	Roll	3.28 ft. (1 m) x 33.5 ft.	1 sq.	97 lbs.
Veral Stainless Steel	Stainless-steel-clad asphalt elastomer sheet, glass mat/glass scrim reinforced.	Top ply of Veral composite, lapped 3 inches side and end.	PA-100 Asphalt or torch	Roll	3.28 ft. (1 m) x 33.5 ft.	1 sq.	105 lbs.