

Poly Fix® Part A

Version 1 pg. 1

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

<p>1.1 Trade Name (as labeled): Synonyms: CAS No:</p> <p>1.2 Product Use:</p> <p>1.3 Company Name: Company Address: Company Address Cont: Business Phone: Website:</p> <p>1.4 Emergency Telephone Number:</p> <p>Date of Last Revision: Date of Current Revision:</p>	<p>Poly Fix® Part A N/A Mixture Ultra Low Viscosity Polymer Concrete Repair Binder SpecChem 1511 Baltimore Ave; Suite 600 Kansas City, MO 64108 (816) 968-5600 www.specchemllc.com</p> <p>VelocityEHS 1-(800)255-3924 (North America) +1-813-248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)</p> <p>June 26, 2019 May 30, 2024</p>
--	--

SECTION 2 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is a clear to amber colored liquid with a petroleum distillate odor.


Health Hazards: May cause skin, eye, and respiratory system irritation. May be an aspiration hazard. Inhalation may cause drowsiness or dizziness

Flammability Hazards: This product is a non-flammable liquid.

Reactivity Hazards: None.

Environmental Hazards: The environmental effects of this product have not been investigated, however release may cause long term adverse environmental effects.

US DOT Symbols: Not Regulated



EU and GHS Symbols:

Signal Word: Danger

GHS Ratings:

Inhalation Toxicity	Acute Tox. 4	Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation.
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days.
Respiratory sensitizer	1	Respiratory sensitizer.
Skin sensitizer	1	Skin sensitizer.

Poly Fix® Part A

Version 1

pg. 2

Carcinogen 2 Limited evidence of human or animal carcinogenicity.
 Reproductive Toxicity 2

GHS Hazards

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.

GHS Precautions

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.
- P285 In case of inadequate ventilation wear respiratory protection.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment (see Section 4 of the SDS).
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P302+P352 IF ON SKIN: Wash with soap and water.
- P304+P340 IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
- P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.
- P337+P313 Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
- P405 Store locked up.
- P501 Dispose of contents/container according to Section 13 of the SDS.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	WT%	CAS No.
4,4'-methylenediphenyl diisocyanate	50-70%	101-68-8

Poly Fix® Part A

Version 1

pg. 3

Benzene, 1,1'-methylenebis [isocyanato-,homopolymer]	10-30%	39310-05-9
Diphenylmethane-2,4'-diisocyanate	5-10%	5873-54-1
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	<40%	6846-50-0
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).		

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

SECTION 4 – FIRST AID MEASURES

Inhalation:	Remove to fresh air if effects occur. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Consult a physician or transport to a medical facility.
Eye Contact:	Immediately flush eyes with large quantities of water for at least 15 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.
Skin Contact:	Wash immediately and thoroughly with soap and flowing water. Remove contaminated clothing while washing. Seek medical attention if irritation persists. An MDI skin decontamination study demonstrated that cleaning very soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water.
Ingestion:	If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.
Notes to Physician:	No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Cholinesterase inhibition has been noted in human exposure but is not of benefit in determining exposure and is not correlated with signs of exposure. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

Poly Fix® Part A

Version 1

pg. 4

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point: 230° C (446° F)

Flammable Properties: Product is not considered a fire hazard, but will burn if ignited.
NFPA Flammability Class: III B (Combustible liquid).

Suitable Extinguishing Media: Carbon dioxide, dry chemical, water fog or fine spray. Alcohol resistant foams are preferred, general purpose synthetic foams or protein foams may function, but will not be as effective.

Unsuitable Extinguishing Media: Do not use direct water stream, as it may spread fire.

Unusual Fire and Explosion Hazards: Product reacts with water. Reaction may produce heat and/or gases. This reaction may be violent. Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides, isocyanates, hydrogen cyanide and other unidentified toxic and/or irritating compounds.

Fire Fighting: Stay upwind and keep people away. Isolate fire and deny unnecessary entry. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out. Contain fire water run-off if possible, as it may cause environmental damage. Review section 6 and section 12 of this SDS.

Protection of Firefighters: Wear positive pressure self-contained breathing apparatus (SCBA) and approved protective clothing (helmet, coat, trousers, boots and gloves). If contact is likely, use full chemical resistant fire fighting clothing with SCBA.

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

Personal Precautions: Put on appropriate personal protective equipment (see section 8).

Environmental Precautions: Prevent spilled material from contact with soil, drains and sewers.

Methods for Containment: Contain by diking with sand, earth or other suitable material.

Methods for Clean-up: Absorb spill with an inert material, use non-sparking tools to place into labeled waste container for disposal.

SECTION 7 - HANDLING AND STORAGE

Handling: Wear appropriate personal protective equipment (see section 8). Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Do not ingest. Avoid prolonged or repeated contact

Poly Fix® Part A

Version 1 pg. 5

with skin. May cause allergic skin reaction, persons with a history of skin sensitization should not be employed in any process in which this product is used. Wash thoroughly with soap and water after handling. Do not handle or store near flame, heat or strong oxidants. Keep away from sources of ignition and hot metal surfaces.

Storage: Store original unopened containers in a sheltered area between 60°F and 80°F (15°C and 27°C) at atmospheric pressure. Do not store in direct sunlight. Keep containers closed when not in use.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Parameters:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
4,4'-methylenediphenyl diisocyanate 101-68-8	Not Established	0.005 ppm TWA (listed under Methylene bisphenyl isocyanate (MDI))	NIOSH: 0.005 ppm TWA (listed under Methylene bisphenyl isocyanate); 0.05 mg/m ³ TWA 0.020 ppm Ceiling (10 min); 0.2 mg/m ³ Ceiling (10 min)

Engineering Controls: General mechanical ventilation is sufficient for most conditions. Control airborne levels below the exposure guidelines, if established.
Local exhaust ventilation may be necessary for some operations.
General Hygiene Considerations: Wash thoroughly after handling and before eating, drinking or smoking.
Eye/face Protection: Use chemical safety glasses, splash-proof eye goggles or goggles with full faceshield.
Skin Protection: Use neoprene, nitrile/butadiene rubber or other impermeable chemical resistant gloves to prevent skin irritation. If potential for skin contact is present, wear impervious, long-sleeved, body covering clothing and rubber boots.
Respiratory Protection: If exposure may or does exceed occupational exposure limits, respiratory irritation is experienced, or during spray application, use a properly fitted MSHA/NIOSH approved respirator fitted with organic vapor cartridges and particulate pre-filters. If the respirator is the sole means of protection, use a full-face supplied air respirator. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use an approved positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). If sanding or grinding on cured material, use above respirator fitted with HEPA filters or a dust mask.
Contaminated Gear: Remove contaminated clothing and shoes while washing. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties:
Appearance (Physical State and Color): Clear to pale yellow

Poly Fix® Part A

Version 1

pg. 6

Odor: Mild
Odor Threshold: No data available
pH: No data available
Melting/Freezing Point: No data available
Boiling Point: Not data available
Flash Point: Flash Point: 230°C (446°F)
Evaporation Rate: No data available
Flammability (Solid; Gas): No data available
Upper/Lower Flammability or Explosion Limits: No data available
Vapor Pressure (mm Hg @ 20°C (68° F): No data available
Vapor Density: No data available
Relative Density: No data available
Specific Gravity: 1.0 – 1.2
Solubility in Water: No data available
Weight per Gallon: No data available
Partition Coefficient (n-octanol/water): No data available
Auto-Ignition Temperature: No data available
Decomposition Temperature: No data available
Viscosity: No data available
9.2 Other Information: No data available

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability: Stable under recommended storage conditions (see Section 7).
Conditions to Avoid: Avoid temperatures above 450 deg F (230 deg C), potential violent decomposition may occur. Avoid contact with water, as material reacts with water, releasing carbon dioxide which can cause rapid pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.

Incompatible Materials: Strong acids, bases, or oxidizing agents. Avoid unintended contact with amines, alcohols, water, moist air and metals such as aluminum, brass, copper, tin, zinc and galvanized metals.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides, isocyanates, hydrogen cyanide and other unidentified toxic and/or irritating compounds.

Hazardous polymerization will not occur.

SECTION 11 – TOXICOLOGY INFORMATION

Information on likely routes of : No data is available on the product itself exposure

Acute toxicity
Components:

Poly Fix® Part A

Version 1

pg. 7

Suspected Cancer Agent: Ingredients within this product are found on one or more of the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are considered to be cancer-causing agents by these agencies.

Irritancy: Skin, eye, respiratory irritant.

Sensitization to the Product: This product is not expected to cause skin sensitization.

Germ Cell Mutagenicity: This product contains ingredients that are suspected to be a germ cell mutagenic.

Reproductive Toxicity: This product is not expected to be a human reproductive toxicant.

Components:

4,4'-Methylenediphenyl diisocyanate:

Acute oral toxicityComponents : LD50 (Rat, male): > 10,000 mg/kg
method: OECD Test Guideline 401

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Acute oral toxicityComponents : LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance of mixture has no acute oral toxicity

Acute inhalation toxicity - : Acute toxicity estimate: 1.49 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method:

2,2,4-trimethyl-1,3-pentanediol diisobutyrate:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.12 mg/l Exposure time: 6 h

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Components:

4,4'-Methylenediphenyl diisocyanate:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg
Method: OECD Test Guideline 402

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg
Method: OECD Test Guideline 402

Diphenylmethane-2,4' – diisocyanate:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg
Metod: OECD Test Guideline 402

Acute toxicity (other routes of administration) : No data available

Poly Fix® Part A

Version 1

pg. 8

Skin corrosion/irritation

Components:

4,4'-Methylenediphenyl diisocyanate:

Species: Rabbit

Method: OECD test Guideline 404

Result: Irritating to skin

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Species: Rabbit

Result: Skin irritation

GLP: yes

Diphenylmethane-2,4' – diisocyanate:

Species: Rabbit

Assessment: Irritant

Method: OECD Test Guideline 404

Result: Irritating to skin.

2,2,4-trimethyl-1,3-pentanediol diisobutyrate:

Species : Guinea pig

Exposure time : 24 h

Result : slight skin irritation

Serious eye damage/eye irritation

Components:

4,4'-Methylenediphenyl diisocyanate:

Species: Rabbit

Result: Mild eye irritation

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Species: Rabbit

Result: Mild eye irritation

Method: OECD Test Guideline 405

GLP: yes

Diphenylmethane-2,4' – diisocyanate:

Species: Humans

Result: Irritation to eyes, reversing within 7 days

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

Remarks: Mild eye irritation

Respiratory or skin sensitization

Components:

4,4'-Methylenediphenyl diisocyanate:

Poly Fix® Part A

Version 1

pg. 9

Exposure routes: Skin
Species: Mouse
Method: OECD Test Guideline 429
Result: May cause sensitisation by skin contact

Exposure routes: Respiratory Tract
Species: Guinea pig
Result: May cause sensitisation by inhalation

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:
Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: May cause sensitisation by skin contact

Exposure routes: Respiratory Tract
Species: Guinea pig
Result: May cause sensitisation by inhalation.

Diphenylmethane-2,4' – diisocyanate:
Exposure routes: Skin
Species: Mouse
Assessment: May cause sensitisation by skin contact.
Result: Causes sensitisation.

Exposure routes: Respiratory Tract
Species: Guinea pig
Assessment: May cause sensitisation by inhalation
Result: Causes sensitisation.

2,2,4-trimethyl-1,3-pentanediol diisobutyrate:
Test Type: Skin Sensitization
Species: Guinea pig
Result: non-sensitizing

Components:

4,4'-Methylenediphenyl diisocyanate:
Assessment: May cause sensitisation by inhalation and skin contact

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:
Assessment: May cause sensitisation by inhalation and skin contact.

Diphenylmethane-2,4' – diisocyanate:
Assessment: Mild eye irritation

Germ cell mutagenicity

Components:

Poly Fix® Part A

Version 1

pg. 10

4,4'-Methylenediphenyl diisocyanate:

Genotoxicity in vitro : Concentration: 200 ug/plate
 Metabolic activation: with and without metabolic activation
 Method: Directive 67/548/EEC, Annex, B. 13/14
 Result: negative

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Genotoxicity in vitro : Concentration: ca 50 ug/plate
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Diphenylmethane-2,4' – diisocyanate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Components:

4,4'-Methylenediphenyl diisocyanate:

Genotoxicity in vivo : Application Route: inhalation
 Exposure time: 3 Weeks
 Dose: 118 mg/m3
 Method: OECD Test Guideline 474
 Result: negative

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Genotoxicity in vitro : Application Route: inhalation
 Exposure time: 3 Weeks
 Dose: 118 mg/m3
 Method: OECD Test Guideline 474
 Result: negative

Diphenylmethane-2,4' – diisocyanate:

Genotoxicity in vitro : Application Route: inhalation
 Exposure time: 3 Weeks
 Dose: 118 mg/m3
 Method: OECD Test Guideline 474
 Result: negative

Components:

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Germ cell mutagenicity- Assessment : Arimal testing did not show any mutagenic effects.

Germ cell mutagenicity- Assessment :

No data available

Components:

2,2,4-trimethyl-1,3-pentanediol diisobutyrate

Poly Fix® Part A

Version 1

pg. 11

Germ cell mutagenicity : Not classified based on available information

Carcinogenicity

Components:

4,4'-Methylenediphenyl diisocyanate:

Species: Rat, (male and female)

Application Route: Inhalation

Exposure time: 24 mouth(s)

Dose: 1 mg/m³

Frequency of Treatment: 5 daily

Method: OECD Test Guideline 453

Result: positive

Target Organs: Lungs

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Species: Rat, (male and female)

Application Route: Inhalation

Exposure time: 24 mouth(s)

Dose: 1 mg/m³

Frequency of Treatment: 5 daily

Method: OECD Test Guideline 453

Result: negative

Diphenylmethane-2,4' – diisocyanate:

Species: Rat, (male and female)

Application Route: Inhalation

Exposure time: 24 mouth(s)

Dose: 1 mg/m³

Frequency of Treatment: 5 daily

Method: OECD Test Guideline 453

Result: positive

Target Organs: Lungs

Carcinogenicity-
Assessment : No Data Available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable. Possible or confirmed human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP

Poly Fix® Part A

Version 1

pg. 12

Reproductive toxicity

Components:

Diphenylmethane-2,4' – diisocyanate:

Effect on fertility : Species: Rat, female
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: Animal testing did not show any effects on fertility

Species: Rat, male and female
Application Route: Inhalation
Method: OECD Test Guideline 414
Result Animal testing did not show any effects on fertility

Components:

4,4'-Methylenediphenyl diisocyanate:

Effects on fertility : Species: Rat, female
development : Application Route: Inhalation
General Toxicity Maternal: No observed adverse effect level: 4
Mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Species: Rat, female
Application Rout: Inhalation
General Toxicity Maternal: No observed adverse effect level: 4
Mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

Components:

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Reproductive toxicity - : No evidence of adverse effects on sexual function and fertility,
or on development, based on animal experiments.

2,2,4-trimethyl-1,3-pentanediol diisobutyrate:

Effects on fetal development: Species: Rabbit
Application Route: Oral
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Reproductive toxicity - Assessment: Some evidence of
adverse effects on development, based on animal
experiments.

STOT – single exposure

Components:

Poly Fix® Part A

Version 1

pg. 13

4,4'-Methylenediphenyl diisocyanate:
Exposure routes: inhalation
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:
Exposure routes: inhalation (dust/mist/fume)
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

Diphenylmethane-2,4' – diisocyanate:
Exposure routes: Inhalation
Target Organs: Respiratory system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

STOT – single exposure

No data available

Repeated dose toxicity

Components:

4,4'-Methylenediphenyl diisocyanate:
Species: Rat, male and female
: 0.2 mg/m³
Exposure time: 2 yr
Number of exposures: 5 d
Method: OECD Test Guideline 453

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:
Species: Rat, male and female
: 0.2 mg/m³
Exposure time: 2 yr
Number of exposures: 5 d
Method: OECD Test Guideline 453

Diphenylmethane-2,4' – diisocyanate:
Species: Rat, male and female
: 0.2 mg/m³
Exposure time: 2 yr
Number of exposures: 5 d
Method: OECD Test Guideline 453

Components:

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:
Repeated dose toxicity - : No adverse effect has been observed in chronic toxicity tests.
Assessment

Poly Fix® Part A

Version 1

pg. 14

Diphenylmethane-2,4' – diisocyanate:
Repeated dose toxicity - : Mild eye irritation
Assessment

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Product:

Remarks: No data available

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2,4-trimethyl-1,3-pentanediol diisobutyrate:

Toxicity to fish : NOEC (Fish):>= 6 mg/l
Exposure time: 96 h
Remarks: (limit of solubility in fresh water)

4,4'-Methylenediphenyl diisocyanate:

Toxicity to fish : LC50 (Brachydanio reio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 202

Benzene 1,1'-methylenedis[isocyanato-, homopolymer:

Toxicity to fish : LC50 (Brachydanio reio (zebrafish)): > 1,000 mg/l

Poly Fix® Part A

Version 1

pg. 15

Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

2,2,4-trimethyl-1,3-pentanediol diisobutyrate:

Toxicity to daphnia and other:
 aquatic invertebrates
 NOEC (Daphnia): >- 1.46 mg/l
 Exposure time: 48 h
 Remarks: (limit of solubility in fresh water)

Diphenylmethane-2,4' – diisocyanate:

Toxicity to daphnia and other:
 aquatic invertebrates
 LC50 (Brachydanio reio (zebrafish)): > 1,000 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

Components:
2,2,4-trimethyl-1,3-pentanediol diisobutyrate:

Toxicity to algae:
 EC50 (Chlorella pyrenoidosa): > 7.49
 Exposure time: 72 h
 Remarks: (limit of solubility in fresh water)

Benzene 1,1'-methylenedis[isocyanato-, homopolymer

Toxicity to algae:
 EC50 (Desmodesmus subspicatus
 (Scenedesmus subspicatus)): > 1,640 mg/l
 Exposure Time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity): no data available

Components:
Benzene 1,1'-methylenedis[isocyanato-, homopolymer

Toxicity to fish (Chronic:GLP:no toxicity)

Components:
2,2,4-trimethyl-1,3-pentanediol diisobutyrate:

Toxicity to daphnia and other : EC50 (Daphnia): >1.3 mg/l
 Aquatic invertebrates : Exposure time: 21 d
 (Chronic toxicity) : Remarks: (limit of solubility in fresh water)

4,4'-Methylenediphenyl diisocyanate:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): >= 10 mg/l

Poly Fix® Part A

Version 1

pg. 16

 Aquatic invertebrates
 (Chronic toxicity)

 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

Benzene 1,1'-methylenedis[isocyanato-, homopolymer

 Toxicity to daphnia and other
 Aquatic invertebrates
 (Chronic toxicity)

 : NOEC (Daphnia magna (Water flea)): ≥ 10 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

Diphenylmethane-2,4' – diisocyanate:

 Toxicity to daphnia and other
 Aquatic invertebrates
 (Chronic toxicity)

 : NOEC (Daphnia magna (Water flea)): ≥ 10 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 211

M-Factor (Acute aquatic toxicity):

no data available

Components:

Benzene 1,1'-methylenedis[isocyanato-, homopolymer

Toxicity to microorganisms

 : EC50 (activated sludge): > 100 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 209

Diphenylmethane-2,4' – diisocyanate:

Toxicity to microorganisms

 : EC50 (activated sludge): > 100 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 209
Components:

4,4'-Methylenediphenyl diisocyanate:

 Toxicity to soil dwelling
 organisms

 : NOEC (Eisenia fetida (earthworms)): $\geq 1,000$ mg/kg
 Exposure time: 336 h
 Method: OECD Test Guideline 207

Benzene 1,1'-methylenedis[isocyanato-, homopolymer

 Toxicity to soil dwelling
 organisms

 : EC50 (Eisenia fetida (earthworms)): $> 1,000$ mg/kg
 Exposure time: 336 h

Poly Fix® Part A

Version 1

pg. 17

Method: OECD Test Guideline 207

Diphenylmethane-2,4' – diisocyanate:
Toxicity to soil dwelling organisms :

NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg
Exposure time: 336 h
Method: OECD Test Guideline 207

Plant Toxicity :

No data available

Sediment toxicity :

No data available

Toxicity to terrestrial organisms :

No data available

Ecotoxicology Assessment
Acute aquatic toxicity :

No data available

Chronic aquatic toxicity :

No data available

Toxicity Data on Soil :

No data available

Other organisms relevant to the environment :

No data available

Persistence and degradability

Components:

4,4'-Methylenediphenyl diisocyanate:

Biodegradability :

Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0%
Exposure time: 28 d
Method: Inherent Biodegradability:Modified MITI Test (II)

Benzene 1,1'-methylenedis[isocyanato-, homopolymer

Biodegradability :

Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0%
Exposure time: 28 d
Method: Inherent Biodegradability:Modified MITI Test (II)

Poly Fix® Part A

Version 1

pg. 18

Diphenylmethane-2,4' – diisocyanate
 Biodegradability : Inoculum: Domestic sewage
 Concentration: 30 mg/l
 Result: Not biodegradable
 Biodegradation 0%
 Exposure time: 28 d
 Method: Inherent Biodegradability: Modified MITI Test (II)
 2,2,4-trimethyl-1,3-pentanediol diisobutyrate:
 Biodegradability: Biodegradation: 70.73 %
 Exposure time: 28 d
 Method: Ready Biodegradability: CO2 Evolution Test

ThOD: 2.40 g/g

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Components:

4,4'-Methylenediphenyl diisocyanate:
 Stability in water : Degradation half life (DT50): 20 hrs (25 °C)
 Method: No information available
 Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential

Components:

4,4'-Methylenediphenyl diisocyanate:
 Bioaccumulation : Species: Cyprinus carpio (Carp)
 Bioconcentration factor (BCF): 200
 Remarks: Bioaccumulation is unlikely

Poly Fix® Part A

Version 1

pg. 19

Benzene 1,1'-methylenedis[isocyanato-, homopolymer

Bioaccumulation : Species: Cyprinus carpio (Carp)
 Bioconcentration factor (BCF):200
 Remarks: Bioaccumulation is unlikely
 2,2,4-trimethyl-1,3-pentanediol diisobutyrate:
 Distribution among environmental compartments: log
 Koc: 2.69 - 3.6; Method: QSAR model

Diphenylmethane-2,4' – diisocyanate

Bioaccumulation : Species: Cyprinus carpio (Carp)
 Bioconcentration factor (BCF): 200
 Remarks: Bioaccumulation is unlikely
 2,2,4-trimethyl-1,3-pentanediol diisobutyrate:
 Bioaccumulation: Species: Fish
 Bioconcentration factor (BCF): 1.95
 Species: Fish
 Bioconcentration factor (BCF): 183 - 194

Components:

4,4'-Methylenediphenyl diisocyanate:

Partition coefficient: n- : log Pow: 4.51 (20 °C)
 octanol/water pH: 7
 Method: OECD Test Guideline 117

Benzene 1,1'-methylenedis[isocyanato-, homopolymer

Partition coefficient: n- : log Pow: 8.56 (20 °C)
 octanol/water

Diphenylmethane-2,4' – diisocyanate

Partition coefficient: n- : log Pow: 4.51 (20 °C)
 pH: 7
 Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Distribution among

Environmental compartments : No data available

Stability in soil

: 2,2,4-trimethyl-1,3-pentanediol diisobutyrate:
 Distribution among environmental compartments: log
 Koc: 2.69 - 3.6; Method: QSAR model

Other adverse effects

Environmental fate and pathways : No data available

Poly Fix® Part A

Version 1 pg. 20

Results of PBT and vPvB assessment	:	No data available
Endocrine disrupting potential	:	No data available
Adsorbed organic bound halogens (AOX)	:	No data available
Hazardous to the ozone layer Ozone-Depletion Potential	:	Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone – CAA Section 602 Class I Substances Remarks: This product neither contains, nor was Manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B)
Additional ecological Information – Product	:	No data available
Global warming potential (GWP) ppppp	:	No data available

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with federal, state and local regulations. The preferred method for disposal of uncontaminated product is by recycling, reclaiming, incineration or other thermal destruction device using a licensed and permitted waste disposal contractor.

SECTION 14 - TRANSPORTATION INFORMATION

<u>14.1 U.S. Department of Transportation (DOT) Shipping Regulations:</u>	
<i>This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.</i>	
UN Identification Number:	Not Regulated
Proper Shipping Name:	None
Hazard Class Number and Description:	None
Packing Group:	None
DOT Label(s) Required:	None
North American Emergency Response Guidebook Number:	None
<u>14.2 Environmental Hazards:</u>	
Marine Pollutant:	Not Regulated
<u>14.3 Special Precaution for User:</u>	None
<u>14.4 International Air Transport Association Shipping Information (IATA):</u>	
	Not regulated as dangerous goods

Poly Fix® Part A

Version 1

pg. 21

14.5 International Maritime Organization**Shipping Information (IMO):**

UN Identification Number:	Not regulated as dangerous goods
Proper Shipping Name:	None
Hazard Class Number and Description:	None
Packing Group:	None
EMS-No:	None

Special Notes: *This product is not regulated according to US DOT regulations when in individual containers of less than 11111 lbs (5039.5 kgs).*

SECTION 15 – REGULATORY INFORMATION

USA Federal: This SDS has been prepared in compliance with the Occupational Safety and Health Act (OSHA)

Hazard Communication Standard (29 CFR 1910.1200). This product is considered to be a hazardous chemical under that standard. The specific chemical identity and/or exact percentage of any proprietary ingredient(s) may be withheld as a trade secret, pursuant to the standard.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): To the best of our knowledge, this product contains the following chemicals which are known to the State of California to cause cancer or reproductive toxicity at levels which require warning under this statute:
- None

Massachusetts Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:
26447-40-5 Diphenylmethane Diisocyanate (MDI) Mixed Isomers < 70 %
101-68-8 4,4'-Diphenylmethane Diisocyanate (MDI) 50 to 70 %

New Jersey Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:
26447-40-5 Diphenylmethane Diisocyanate (MDI) Mixed Isomers < 70 %

Pennsylvania Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:
101-68-8 4,4'-Diphenylmethane Diisocyanate (MDI) 50 to 70 %

USA Resource Conservation and Recovery Act (40 CFR 261): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:
- None

USA Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 302 Extremely Hazardous Substances Threshold Planning Quantities (TPQs): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:
- None

Poly Fix® Part A

Version 1

pg. 22

USA Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 302 Hazardous Substances Reportable Quantities (RQs): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

101-68-8 4,4'-Diphenylmethane Diisocyanate (MDI) 50 to 70 %

USA Toxic Substances Control Act (TSCA) - section 12(b): To the best of our knowledge, this product contains the following chemicals above the de minimus concentration(s) which requires notification to the Environmental Protection Agency (EPA) per 40 CFR 707, subpart D, if any person intends to export:
 - None

Country	Regulation	All Components Listed
Australia	Australian inventory of Chemical Substances (AICS)	Yes
Canada	Canada Domestic Substance List	Yes
Canada	Canada Non-Domestic Substance List (NDSL)	No
China	China Inventory of Existing Chemical Substances	Yes
EU	EU REACH List of Registered Intermediates	No
EU	EU REACH List of Pre-Registered Substances	No
EU	EU REACH List of Registered Substances	No
Japan	Japanese Existing and New Chemical Substance List	Yes
South Korea	South Korea Existing Chemicals Inventory	Yes
Philippines	Philippines Inventory of Chemicals and Chemical	No
USA	USA TSCA Inventory List Section 8(b)	Yes

SECTION 16 – OTHER INFORMATION

Date of Printing: May 30,2024

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET

Poly Fix® Part B

Version 1

pg. 23

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

1.1 Trade Name (as labeled):	Poly Fix® Part B
Synonyms:	N/A
1.2 Product Use:	Polyurea Repair Product
1.3 Company Name:	SpecChem
Company Address:	1511 Baltimore Ave; Suite 600
Company Address Cont:	Kansas City, MO 64108
Business Phone:	(816) 968-5600
Website:	www.specchemllc.com
1.4 Emergency Telephone Number:	VelocityEHS 1-(800)255-3924 (North America) +1-813-248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)
Date of Last Revision:	June 27, 2019
Date of Current Revision:	May 30, 2024

SECTION 2 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is a clear to amber colored liquid with a petroleum distillate odor.

Health Hazards: May cause skin, eye, and respiratory system irritation. May be an aspiration hazard. Inhalation may cause drowsiness or dizziness

Flammability Hazards: This product is a non-flammable liquid.

Reactivity Hazards: None.

Environmental Hazards: The environmental effects of this product have not been investigated, however release may cause long term adverse environmental effects.

US DOT Symbols: Not Regulated



EU and GHS Symbols:

Signal Word: Danger

2.1 EU Labeling and Classification:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

EU HAZARD CLASSIFICATION OF INGREDIENTS PER DIRECTIVE 1272/2008/EC:
Index Number:

500-033-5 is listed in Annex I 603-074-00-8

265-199-0 is listed in Annex I 649-356-00-4

Substances not listed either individually or in group entries must be self classified.

Poly Fix® Part B

Version 1

pg. 24

Components Contributing to Classification:

2.2 Label Elements:

GHS Hazard Classifications:

Bisphenol A Diglycidyl Ether Resin

Skin Irritation Category 2

Skin Sensitization Category 1

Eye Irritant Category 2

Germ Cell Mutagenicity Category 2

Chronic Aquatic Toxicity Category 2

Flammable Liquid Category 3

Carcinogenicity Category 1B

STOT – SE Category 3 (Respiratory System,
Central Nervous System)

Aspiration Toxicity Category 1

Reproductive Toxicity Category 2

Hazard Statements:

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H341 Suspected of causing genetic defects

H411 Toxic to aquatic life with long lasting
effects

H350 May cause cancer

H335 May cause respiratory irritation

H336 May cause drowsiness or dizziness

H304 May be fatal if swallowed and enters
airways

H361d Suspect of damaging the unborn child

Precautionary Statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions
have been read and understood.

P210 Keep away from heat/sparks/open
flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/Bond container and receiving
equipment.

P241 Use explosion-proof
electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against
static discharge.

P261 Avoid breathing
dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated
area.

P272 Contaminated clothing should not be
allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye
protection/face protection.

Poly Fix® Part B

Version 1

pg. 25

Response Statements:

P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P311 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370+P378 In case of fire: Use dry sand, dry chemical or alcohol resistant foam for extinction.
P391 Collect spillage.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Storage Statements:

Disposal Statements:

2.3 Health Hazards or Risks From Exposure:

Symptoms of Overexposure by Route of Exposure:

The most significant routes of overexposure for this product are by contact with skin or eyes. The symptoms of overexposure are described in the following paragraphs.

Acute:

Inhalation: May cause respiratory tract irritation. May cause headaches, drowsiness, or dizziness.

Skin Contact: May cause moderate irritation to skin. Repeated exposure may cause skin dryness or cracking.

Eye Contact: Vapours and direct contact to the eyes may be irritating.

Ingestion: May cause lung damage if aspirated.

Chronic: Repeated exposure may cause skin dryness or cracking..

Target Organs:

Acute: Skin, Eyes, Respiratory System, Central Nervous System

Chronic: Skin.

Poly Fix® Part B

Version 1

pg. 26

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	WT%	CAS No.	EINECS No.	Hazard Classification
Proprietary component A	<50%	NA	NA	Eye Irrit. 2A
Bisphenol A Diglycidyl Ether Resin	<1%	25068-38-6	500-033-5	Flam. Liq. 3; Skin Irrit. 2; Carc. 1B, Muta. 1B; STOT SE 3; ASP. Tox. 1, Aquatic Chronic 2
2,2,4-trimethyl-1,3-pentaned diisobutyrate	>%40	229-934-9	6846-50-0	Rep Tox. 2

Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers). Specific chemical identities and exact percentages may have been withheld as a trade secret of CBI in compliance with 29 CFR 1910.1200 (i).

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

SECTION 4 – FIRST AID MEASURES
4.1 Description of First Aid Measures:

Eye Contact:	If product enters the eyes, flush with plenty of water or eye wash solution for several minutes. Remove contacts if present and easy to do. Seek medical attention if irritation persists.
Skin Contact:	Wash skin thoroughly with soap and water after handling. Seek medical attention if irritation develops and persists.
Inhalation:	If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.
Ingestion:	If product is swallowed, call physician or poison center immediately. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

Medical Conditions Generally Aggravated

By Exposure: Pre-existing skin, respiratory system or eye problems may be aggravated by prolonged contact.

4.2 Symptoms and Effects Both Acute and Delayed: Exposure to skin and eyes may cause irritation.

4.3 Recommendations to Physicians: Treat symptoms and eliminate overexposure.

SECTION 5 – FIRE FIGHTING MEASURES
5.1 Fire Extinguishing Materials:

Poly Fix® Part B

Version 1

pg. 27

Use the following fire extinguishing materials:

Water Spray:	Yes
Foam:	Yes
Halon:	Yes
Carbon Dioxide:	Yes
Dry Chemical:	Yes
Other:	Any "C" Class

5.2 Unusual Fire and Explosion Hazards:

Irritating and toxic fumes may be produced at high temperatures. Use of water may result if the formation of a toxic aqueous solution. Do not allow run-off from fire fighting to enter drains or water courses.

Explosive Sensitivity to Mechanical Impact:	No
Explosive Sensitivity to Static Discharge:	No

5.3 Special Fire-Fighting Procedures:

- Incipient fire responders should wear eye protection.
- Structural firefighters must wear Self-Contained Breathing Apparatus (SCBA) and full protective equipment.
- Isolate materials not yet involved in the fire and protect personnel.
- Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray.
- If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas.

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Use cautious judgment when cleaning up spill. Wear suitable protective clothing, gloves, and eye/face protection.

6.2 Environmental Precautions:

Construct a dike to prevent spreading. Keep out of sewers, storm drains, surface waters, and soils.

6.3 Spill and Leak Response:

Small Spills:

- Collect material via broom or mop. Place in tightly sealed containers for proper disposal.
- Approach spill areas with caution.
- If liquid was introduced, create a dike or trench to contain material.
- Soak up with absorbent material such as clay, sand or other suitable non-reactive material.

Large Spills:

- Place in leak-proof containers. Seal tightly for proper disposal.

Poly Fix® Part B

Version 1 pg. 28

- Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling:

To prevent eye contact under the foreseeable conditions of use, wear appropriate safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling. Do not handle or store near heat, sparks, or flame.

7.2 Storage and Handling Practices:

Keep away from incompatible materials. Keep container closed when not in use and store in well ventilated area.

7.3 Specific Uses:

Epoxy Sealer.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Parameters:

Ingredients	CAS No.	OSHA PEL	NIOSH PEL
Proprietary component A	NA	None Established	None Established
Bisphenol A Diglycidyl Ether Resin	25068-38-6	Not Listed	Not Listed

8.2 Exposure Controls:

Ventilation and Engineering Controls:

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

Respiratory Protection:

Not required for properly ventilated areas. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

Eye Protection:

Safety glasses or goggles are required.

Poly Fix® Part B

Version 1

pg. 29

Hand Protection:

If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards. Chemical resistant gloves are required to prevent skin contact.

Body Protection:

If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards. Use body protect appropriate to task being performed.

If necessary, refer to appropriate Standards of Canada, or appropriate standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties:

Appearance (Physical State and Color): Black

Odor: Petroleum distillate odor

Odor Threshold: No data available

pH: No data available

Melting/Freezing Point: No data available

Boiling Point: 300°F (148.9°C)

Flash Point: 277°F (136°C)

Evaporation Rate: No data available

Flammability (Solid; Gas): Not applicable

Upper/Lower Flammability or Explosion Limits: No data available

Vapor Pressure (mm Hg @ 20°C (68° F): No data available

Vapor Density: No data available

Relative Density: No data available

Specific Gravity: 0.97

Solubility in Water: Not miscible

Weight per Gallon: 7.75 lbs/gal

Partition Coefficient (n-octanol/water): No data available

Auto-Ignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: 30-50 cP

9.2 Other Information: No data available

Poly Fix® Part B

Version 1 pg. 30

SECTION 10 – STABILITY AND REACTIVITY

10.1 Reactivity: This product is not reactive.
10.2 Stability: Stable under conditions of normal storage and use.
10.3 Possibility of Hazardous Reactions: Will not occur.
10.4 Conditions to Avoid: Heat, open flame or other sources of ignition.
10.5 Incompatible Substances: Strong oxidizing agents.
10.6 Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide and other decomposition products can occur during combustion if not use according to specifications.

SECTION 11 – TOXICOLOGY INFORMATION

11.1 Information on Toxicological Effects:
Toxicity Data:

Bisphenol A Diglycidyl Ether Resin	25068-38-6	LD50 Oral – Rat	13,600 mg/kg
Proprietary component A		LD50 oral - rat	>3000 mg/kg
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	6846-50-0	LD50 Oral (Rat):	> 2,000 mg/kg
		LC50 Inhalation (Rat)	> 0.12 mg/l
		Dermal (Rabbit)	>2,000 mg/kg

Suspected Cancer Agent: Ingredients within this product are not found on one or more of the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are not considered to be cancer-causing agents by these agencies.
Irritancy: Skin, eye irritant.
Sensitization to the Product: This product is expected to cause skin sensitization.
Germ Cell Mutagenicity: This product contains ingredients that are suspected to be a germ cell mutagenic.
Reproductive Toxicity: No data available.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 Toxicity:

Bisphenol A Diglycidyl Ether Resin	25068-38-6	LC50 – Rainbow Trout	<10 mg/l – 96h
		EC50 – Algae	<10 mg/l – 96h
2,2,4-trimethyl-1,3-pentane diisobutyrate	6846-50-0	NOEC (Fish)	>= 6 mg/l
		NOEC (daphnid)	>=1.46 mg/l
		EC50 Chronic toxicity (Daphnia)	> 1.3 mg/l
		NOEC Chronic toxicity (Daphnia)	0.7 mg/l
		EC50 – Algae (Chlorella pyrenoidosa)	> 7.49 mg/l

12.2 Persistence and Degradability: No specific data available on this product.
12.3 Bioaccumulative Potential: No specific data available on this product.

Poly Fix® Part B

Version 1 pg. 31

<p>12.4 Mobility in Soil:</p> <p>12.5 Results of PBT and vPvB Assessment:</p> <p>12.6 Other Adverse Effects:</p> <p>12.7 Water Endangerment Class:</p>	<p>No specific data available on this product.</p> <p>No specific data available on this product.</p> <p>No data available</p> <p>At present, there are no ecotoxicological assessments for this product.</p>
--	---

SECTION 13 – DISPOSAL CONSIDERATIONS

<p><u>13.1 Waste Treatment Methods:</u></p> <p><u>13.2 EU Waste Code:</u></p>	<p>Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Australia, EU Member States and Japan.</p> <p>Not determined</p>
--	--

SECTION 14 - TRANSPORTATION INFORMATION

14.1 U.S. Department of Transportation (DOT) Shipping Regulations:
This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

UN Identification Number:	Not Regulated
Proper Shipping Name:	None
Hazard Class Number and Description:	None
Packing Group:	None
DOT Label(s) Required:	None
North American Emergency Response Guidebook Number:	None
<u>14.2 Environmental Hazards:</u>	
Marine Pollutant:	
14.3 Special Precaution for User:	None
<u>14.4 International Air Transport Association Shipping Information (IATA):</u>	
<u>Shipping Information (IMO):</u>	
UN Identification Number:	Not Regulated
Proper Shipping Name:	None
Hazard Class Number and Description:	None
Packing Group:	None
EMS-No:	None
Special Notes:	This product is not regulated according to Canadian TDG regulations.

SECTION 15 – REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations Specific for the Substance or Mixture:

Poly Fix® Part B

Version 1

pg. 32

United States Regulations:

U.S. SARA Reporting Requirements:

The components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA 311/312:

Acute Health: Yes; Chronic Health: Yes; Fire: Yes; Reactivity: No

U.S. CERCLA Reportable Quantity:

Not Applicable

U.S. TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory or are exempted from listing.

Other U.S. Federal Regulations:

None known

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

This product does not contain ingredients on the Proposition 65 Lists.

15.2 Canadian Regulations:

Canadian DSL/NDSL Inventory Status:

Components are DSL Listed, NDSL Listed and/or are exempt from listing

Other Canadian Regulations:

Not applicable

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian WHMIS Classification and Symbols:

All components are listed or exempt.

15.3 European Economic Community Information:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives. See Section 2 for Details.

Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 Australian Information for Product:

Components of this product are listed on the International Chemical Inventory list.

15.5 Japanese Information for Product:

Japanese Minister of International Trade and Industry (MITI) Status: The components of this product are not listed as Class I specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

15.6 International Chemical Inventories:

Listing of the components on individual country Chemical Inventories is as follows:

Australian Inventory of Chemical Substances (AICS): Listed

Korean Existing Chemicals List (ECL): Listed

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed

U.S. TSCA: Listed

Poly Fix® Part B

Version 1

pg. 33

SECTION 16 – OTHER INFORMATION

Date of Printing: June 27, 2019

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET