

## General Purpose Polymer-Modified Concrete Repair Mortar

A general purpose polymer-modified concrete repair mortar for concrete floors, walls, precast, tilt-up and masonry surfaces. SpecPatch 30 can be used for horizontal, vertical, and overhead applications to provide a durable repair that can be shaped by shaving or sanding.



### ✓ Benefits

- Can be featheredged
- Repairs up to 2" in thickness per lift (4" in isolated areas)
- Designed for interior & exterior repairs
- Can be shaped
- Excellent durability and adhesion
- Dries to natural concrete gray
- One component - Just add water



## Usage

- Interior and exterior use
- Horizontal, vertical and overhead repairs
- Fill small holes, spalled areas

## Packaging

- 50 lb bag
- Coverage: approx 20 sq-ft @ 1/4"

## TYPICAL TEST DATA

Test data based on 5.0 pints water

Set Time at 70°F (ASTM C-266)

Initial Set	30-40 min
Final Set	60 min
<b>Compressive Strength (ASTM C-109)</b>	
1 Day	1200 psi
7 Days	5000 psi
28 Days	6500 psi
<b>Freeze-Thaw (ASTM C-672)</b>	
Scaling Resistance	25 cycles = 0% loss
<b>Slant Shear Bond Strength (ASTM C-882)</b>	
7 Days	1680 psi
<b>Flexural Strength (ASTM C-348)</b>	
28 Days	650 psi
<b>Yield</b>	
Yield per bag	.43 cu-ft