


Pattern Number: **1505****Madera Flagstone**

8" to 24" rock sizes - 1-3/4" to 2" relief
 1/2" to 1" mortar joint, large irregular stone

**Spec Formliners, Inc.**

Impressive on Concrete

CONCRETE0.50 to 1.00"
Mortar Joint1.75" to 2.00"
ReliefRock Sizes:
8.0" to 24.0"Visit **www.specformliners.com** for application guides and technical information
ThermoSpec™
 SINGLE OR MULTI-USE PLASTIC

Property	HIPS	ABS
Tensile D638	3700	5300
IFlexural D7905	-	9300
Hardness D786	-	105
Material Weights - lbs/ft²		
0.070 MIL	0.110 MIL	0.150 MIL
0.393	0.621	0.843
Thicknesses Available		
0.070, 0.090, 0.110, 0.145, 0.155, 0.180		

ElastoSpec Lite™ Semi-Elastomeric
 MULTI-USE MATERIAL


Property	ASTM	Rating
Shore A/D	D2240	40D/90A
Tensile	D412	1900 psi
Elongation	D412	300%
Tear Strength	D2370	23 MPa
Material Weights - lbs/ft²		
Varies by Pattern		
Maximum Thickness		
1/4" + Relief		

ElastoSpec™ 100% Solid Urethane
 BONDED TO 3/4" PLYWOOD

Property	ASTM	Rating
Shore A	D2240	55-65
Tensile	D412	1400 psi
Elongation	D638	600%
Tear Strength	D624	200 pli
Material Weights - lbs/ft²		
Varies by Pattern		
Maximum Thickness		
1-1/8" + Relief		

Call for ThermoSpec™ Standard Panel Sizes on this pattern. Custom Sizes and Art Panels available

ElastoSpec™ Customized Panel Sizes and Art Panels





Spec Formliners, Inc.

Impressive on Concrete

Pattern Number: **1505**

Madera Flagstone

8" to 24" rock sizes - 1-3/4" to 2" relief
1/2" to 1" mortar joint, large irregular stone



Note: Panels match top and bottom, side to side and rotated 180°.