

DWC

DWC1.525GA

Product Description

Coating

1.5 FURRING CHANNEL 25 GA
G40
*Also available in G60 &
G90 coating

Physical Properties

Design Thickness (in) 0.0188
Web depth (in) 1.25
Leg width (in) 0.5
Height (in) 1.5
Yield Strength (ksi) 33



Gross Section Properties

Cross Sectional Area (A)	0.095
Weight of Member (lb/ft)	0.324
Moment of Inertia (Ix)	0.031
Radius of Gyration (Rx)	0.572
Gross Moment of Inertia (Iy)	0.052
Gross Radium of Gyration (Ry)	0.742

Effective Section Properties

Moment of Inertia for deflection (Ixe)	0.029
Section Modulus (Sxe)	0.034
Allowable Bending moment (Ma)	56.73
Allowable shear force (Va)	261

ASTM & Code Standards

- AISI S100-012
- Structural framing is produced to meet or exceed ASTM C955
- Galvanized sheet steel meets or exceeds requirements of ASTM A1003

Note

Standard stock lengths are 10' and 12' - Available in other lengths upon request.

Mill Steel Framing LEED Green Credits

- MR Credit 2** • ConstructionWaste Management - Mill Steel Framing steel framing is 100% recyclable
- MR Credit 4** • Recycled Content - Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
- MR Credit 5** • Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
- V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)
- Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

