

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

DWC

DWC1.525GAG90

Product Description

Coating

	G90 coa
Physical Properties	
Design Thickness (in)	0.0188
Web depth (in)	1.25
Leg width (in)	0.5
Height (in)	1.5
Viold Strongth (ksi)	22

1.5 FURRING CHANNEL 25 GA G90 G90 *Also available in G60 & G90 coating

De

Web depth (in)	1.25
Leg width (in)	0.5
Height (in)	1.5
Yield Strength (ksi)	33

Gross Section Properties	
Cross Sectional Area (A)	0.095
Weight of Member (lb/ft)	0.324
Moment of Inertia (lx)	0.031
Radius of Gyration (Rx)	0.572
Gross Moment of Inertia (ly)	0.052
Gross Radium of Gyration (Ry)	0.742

Effective Section Properties	
Moment of Inertia for deflection (lxe)	0.029
Section Modulus (Sxe)	0.034
Allowable Bending moment (Ma)	56.73
Allowable shear force (Va)	261

Note

Standard stock lengths are 10' and 12' - Available in other lengths upon request.

ASTM & Code Standards

- AISI S100-012
- Structural framing is produced to meet or exceed ASTM C955
- Galvanized sheet steel meets or exceeds requirements of ASTM A1003

Mill Steel Framing LEED Green Credits

MR Credit 2	 ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
MR Credit 4	 Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)



