

## Flat Strapping 2STRAPPING18GAG90

**Product Description**  
 Coating: 2" STRAPPING 18 GA G90  
 G90  
 \*Also available in G60 & G90 coating

**Physical Properties**  
 Design Thickness (in): 0.0451  
 Minimum Thickness (in): 0.0428  
 Strap Width (in): 2  
 Yield Strength (ksi): 33



**Note**  
 Standard stock length is 10' - Available in other lengths upon request.

- ASTM & Code Standards**
- Structural framing is produced to meet or exceed ASTM C955
  - Drywall framing is produced to meet or exceed ASTM C645
  - Galvanized sheet steel meets or exceeds requirements of A653 and A1003

### Mill Steel Framing LEED Green Credits

- MR Credit 2** • ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
- MR Credit 4** • Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
- MR Credit 5** • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
- V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)  
 • Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

