

Flat Strapping 4STRAPPING16GA

Product Description

Coating

4" STRAPPING 16 GA

G40

*Also available in G60 & G90 coating

Physical Properties

| | |
|------------------------|--------|
| Design Thickness (in) | 0.0566 |
| Minimum Thickness (in) | 0.0538 |
| Strap Width (in) | 4 |
| Yield Strength (ksi) | 33 |



Note

Standard stock length is 10' - Available in other lengths upon request.

ASTM & Code Standards

- Structural framing is produced to meet or exceed ASTM C955
- Drywall framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of A653 and A1003

Mill Steel Framing LEED Green Credits

- MR Credit 2** • ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
- MR Credit 4** • Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
- MR Credit 5** • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
- V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)
- Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

