

## Flat Strapping 6STRAPPING12GA

### Product Description

Coating

6" STRAPPING 12 GA

G40

\*Also available in G60 & G90 coating

### Physical Properties

|                        |        |
|------------------------|--------|
| Design Thickness (in)  | 0.1017 |
| Minimum Thickness (in) | 0.0966 |
| Strap Width (in)       | 6      |
| Yield Strength (ksi)   | 33     |



### Note

Standard stock length is 10' - Available in other lengths upon request.

### ASTM & Code Standards

- Structural framing is produced to meet or exceed ASTM C955
- Drywall framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of A653 and A1003

## Mill Steel Framing LEED Green Credits

- MR Credit 2** • ConstructionWaste Management - Mill Steel Framing steel framing is 100% recyclable
- MR Credit 4** • Recycled Content - Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
- MR Credit 5** • Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
- V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)
- Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

