

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Flat Strapping 8STRAPPING14GAG90

Product Description 8" STRAPPING 14 GA G90

Coating G90

*Also available in G60 &

G90 coating

Physical Properties

Design Thickness (in)0.0713Minimum Thickness (in)0.0677Strap Width (in)8Yield Strength (ksi)33



Note

Standard stock length is 10' - Available in other lengths upon request.

ASTM & Code Standards

- Structural framing is produced to meet or exceed ASTM C955
- Drywall framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of A653 and A1003

Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

- $\bullet \ \mathsf{ConstructionWaste} \ \mathsf{Management} \ \mathsf{-} \ \mathsf{Mill} \ \mathsf{Steel} \ \mathsf{Framing} \ \mathsf{steel} \ \mathsf{framing} \ \mathsf{is} \ \mathsf{100\%} \ \mathsf{recyclable}$
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

• Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

V4 MR Credits • Building Product Disclosure and Optimization EPD (1 point)

• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

