

Flat Strapping

10STRAPPING-12GAG90

Product Description

10" STRAPPING 12 GA G90
COATED

Coating

G90
*Also available in G60 & G90 coating

Physical Properties

Design Thickness (in)	0.1017
Minimum Thickness (in)	0.0966
Strap Width (in)	10
Yield Strength (ksi)	33



Note

Standard stock length is 10' - Available in other lengths upon request.

ASTM & Code Standards

- Structural framing is produced to meet or exceed ASTM C955
- Drywall framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of A653 and A1003

Mill Steel Framing LEED Green Credits

- | | |
|----------------------|--|
| MR Credit 2 | • ConstructionWaste Management - Mill Steel Framing steel framing is 100% recyclable |
| MR Credit 4 | • Recycled Content - Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content |
| MR Credit 5 | • Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas |
| V4 MR Credits | • Building Product Disclosure and Optimization EPD (1 point) |
| | • Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point) |

