

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

ProTRAK®

250PDT125-18

1-1/4" leg G40

2 1/2" ProTrak®20 (18mil)

| Product Descript | ion |
|------------------|-----|
|------------------|-----|

Coating

Physical Properties

| Design Thickness (in) | 0.019 |
|------------------------|---------|
| Minimum Thickness (in) | 0.01805 |
| Web Width (in) | 2.5 |
| Flange Width (in) | 1.25 |
| Yield Strength (ksi) | 50 |

| Gross Section Properties | |
|-------------------------------|-------|
| Cross Sectional Area (A) | 0.095 |
| Moment of Inertia (lx) | 0.102 |
| Radius of Gyration (Rx) | 1.038 |
| Gross Moment of Inertia (ly) | 0.015 |
| Gross Radium of Gyration (Ry) | 0.4 |

| Effective Section Properties | |
|--|-------|
| Effective Area (Ae) | 0.029 |
| Moment of Inertia for deflection (lxe) | 0.073 |
| Section Modulus (Sxe) | 0.034 |
| Allowable Bending moment (Ma) | 1029 |
| Allowable shear force in web (U)(Vag) | 248 |

| Torsional Properties | |
|---|---------|
| St. Venant torsion constant (J x 1000) | 0.01143 |
| Warping constant (Cw) | 0.017 |
| Distance from shear center to neutral axis (Xo) | -0.77 |
| Radii of gyration (Ro) | 1.353 |
| Torsional flexural constant (Beta) | 0.676 |

ASTM & Code Standards

- AISI S100-07 & S220-11
- Meets or exceeds ASTM C645 & C754
- ASTM E119, E72, & E90
- ATI CCRR-0207
- LA RR 26019

Section Properties Table Notes

- Calculated properties are based on AISI S100-12, North American Specification for Design of Cold-Formed Steel Structural Members and AISI S220-15, North American Standard for Cold-Formed Steel Framing -NonStructural Members.
- 2. Effective Properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- 3. Tabulated gross properties including torsional properties are based on fullunreduced cross section of the studs, away from punchouts.
- 4. For deflection calculations, use the effective moment of inertia.
- 5. Allowable moment includes cold-work of forming.
- Allowable moment is taken as the lowest value based on loacl or distortional buckling. Distortional buckling strength is based on a k-phi = 0.

Mill Steel Framing LEED Green Credits

MR Credit 2
MR Credit 4
ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
Building Product Disclosure and Optimization EPD (1 point)
Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

