

Slotted Track

362SLOTTEDSLIP14GAG90

Product Description

Slotted Slip Track



Physical Properties

| | 20ga | 18ga | 16ga | 14ga |
|--------------------|----------------|-----------------|-----------------|-----------------|
| Gauge | 20ga | 18ga | 16ga | 14ga |
| Material Thickness | .033 min gauge | .0428 min gauge | .0538 min gauge | .0677 min gauge |
| Coating Weight | G60 | G60 | G60 | G60 |
| Yield | 33 min yield | 33 min yield | 50 min yield | 50 min yield |

Notes

Available in 2-1/2" - 10" web. Available in 2-1/2" - 3" leg.
Standard stock lengths are 10' — Available in other lengths upon request.

ASTM & Code Standards

- Structural framing meets or exceeds ASTM C955
- Drywall framing meets or exceeds ASTM C645
- Galvanized sheet steel meets or exceeds ASTM A653 & A1003

Mill Steel Framing LEED Green Credits

- MR Credit 2** • ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
- MR Credit 4** • Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
- MR Credit 5** • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
- V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)
- Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

