

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Slotted Track

362SLOTTEDSLIP18GAG90

Product Description

Slotted Slip Track



| Physical Properties | | | | |
|---------------------|----------------|-----------------|-----------------|-----------------|
| Gauge | 20ga | 18ga | 16ga | 14ga |
| Material Thickness | .033 min gauge | .0428 min gauge | .0538 min gauge | .0677 min gauge |
| Coating Weight | G60 | G60 | G60 | G60 |
| Yield | 33 min yield | 33 min yield | 50 min yield | 50 min yield |

Notes

Available in 2-1/2" - 10" web. Available in 2-1/2" - 3" leg. Standard stock lengths are 10' — Available in other lengths upon request.

ASTM & Code Standards

- Structural framing meets or exceeds ASTM C955
- Drywall framing meets or exceeds ASTM C645
- Galvanized sheet steel meets or exceeds ASTM A653 & A1003

Mill Steel Framing LEED Green Credits

| MR Credit 2 | ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable |
|---------------|--|
| MR Credit 4 | • Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer |
| | and 6.8% pre-consumer recycled content |
| MR Credit 5 | • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas |
| V4 MR Credits | Building Product Disclosure and Optimization EPD (1 point) |
| | • Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point) |

