

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Structural Stud

600S300-97G90

12 GA GALV 6.00" WEB X 3.00" FLANGE C-STUD .097 MIN GAUGE G-90 COATED

Product	Description
---------	-------------

Coating

_	
Physical Properties	
Design Thickness (in)	0.1017
Minimum Thickness (in)	0.0966
Web Width (in)	6.0000
Flange Width (in)	3.0000
Stiffening Lip (in)	0.6250
Yield Strength (ksi)	50.0000


Gross Section Properties	
Cross Sectional Area (A)	1.271
Weight of Member (lb/ft)	4.32
Section Modulus (Sx)	2.461
Moment of Inertia (lx)	7.383
Radius of Gyration (Rx)	2.410
Gross Moment of Inertia (ly)	1.454
Gross Radium of Gyration (Ry)	1.070

G90

Effective Section Properties	
Moment of Inertia for deflection (lxe)	7.281
Section Modulus (Sxe)	2.248
Allowable Bending moment (Ma)	67.29
Allowable shear force in web (U)(Vag)	10472
Allowable shear at punch (Vanet)	3806

Torsional Properties	
St. Venant torsion constant (J x 1000)	4.381
Warping constant (Cw)	10.776
Distance from shear center to neutral axis (Xo)	-2.241
Radii of gyration (Ro)	3.461
Torsional flexural constant (Beta)	0.581

Punch Out



ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

Mill Steel Framing LEED Green Credits

MR Credit 2	 ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
MR Credit 4	Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

