

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

Structural Stud 1200S200-97G90

12 GA GALV 12.00" WEB X 2.00" **Product Description**

FLANGE C-STUD .097 MIN GAUGE

G90

Coating G90

Physical Properties

Design Thickness (in) 0.1017 Minimum Thickness (in) 0.0966 Web Width (in) 12.0000 Flange Width (in) 2.0000 Stiffening Lip (in) 0.6250 Yield Strength (ksi) 50.0000




Gross Section Properties	
Cross Sectional Area (A)	1.677
Weight of Member (lb/ft)	5.71
Section Modulus (Sx)	5.071
Moment of Inertia (lx)	30.428
Radius of Gyration (Rx)	4.259
Gross Moment of Inertia (ly)	0.635
Gross Radium of Gyration (Ry)	0.615

Effective Section Properties	
Moment of Inertia for deflection (lxe)	30.177
Section Modulus (Sxe)	4.660
Allowable Bending moment (Ma)	139.52
Allowable shear force in web (U)(Vag)	8147
Allowable shear at punch (Vanet)	7411

Torsional Properties	
St. Venant torsion constant (J x 1000)	5.783
Warping constant (Cw)	19.150
Distance from shear center to neutral axis (Xo)	-0.987
Radii of gyration (Ro)	4.415
Torsional flexural constant (Beta)	0.950

Punch Out



ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4 ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable

• Recycled Content - Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

· Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

• Building Product Disclosure and Optimization EPD (1 point) V4 MR Credits

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

