

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

# Structural Stud 800S300-68

Product Description 14 GA GALV 8.00" WEB X 3.00"

FLANGE C-STUD .068 MIN GAUGE

G60

**Physical Properties** 

Coating

Design Thickness (in)0.0713Minimum Thickness (in)0.0677Web Width (in)8.0000Flange Width (in)3.0000Stiffening Lip (in)0.6250Yield Strength (ksi)50.0000




Gross Section Properties	
Cross Sectional Area (A)	1.050
Weight of Member (lb/ft)	3.57
Section Modulus (Sx)	2.596
Moment of Inertia (lx)	10.384
Radius of Gyration (Rx)	3.145
Gross Moment of Inertia (ly)	1.179
Gross Radium of Gyration (Ry)	1.060

Effective Section Properties	
Moment of Inertia for deflection (lxe)	10.084
Section Modulus (Sxe)	2.145
Allowable Bending moment (Ma)	64.22
Allowable shear force in web (U)(Vag)	4221
Allowable shear at punch (Vanet)	3367

Torsional Properties	
St. Venant torsion constant (J x 1000)	1.779
Warping constant (Cw)	14.888
Distance from shear center to neutral axis (Xo)	-2.055
Radii of gyration (Ro)	3.904
Torsional flexural constant (Beta)	0.723

### **Punch Out**



# ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### **Notes**

- Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

## Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

**V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)

• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

