

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

## **Structural Stud**

1200	S200-68
------	---------

Product Description	14 GA GALV 12.00" WEB x 2.00" FLANGE C-STUD    .068 MIN GAUGE
Coating	G60
Physical Properties	
Design Thickness (in)	0.0713
Minimum Thickness (in)	0.0677
Web Width (in)	12.0000
Flange Width (in)	2.0000
Stiffening Lip (in)	0.6250
Yield Strength (ksi)	50.0000

Gross Section Properties	
Cross Sectional Area (A)	1.192
Weight of Member (lb/ft)	4.06
Section Modulus (Sx)	3.659
Moment of Inertia (lx)	21.955
Radius of Gyration (Rx)	4.291
Gross Moment of Inertia (ly)	0.479
Gross Radium of Gyration (Ry)	0.634

Effective Section Properties	
Moment of Inertia for deflection (lxe)	20.865
Section Modulus (Sxe)	2.963
Allowable Bending moment (Ma)	88.72
Allowable shear force in web (U)(Vag)	2771
Allowable shear at punch (Vanet)	2771

Torsional Properties	
St. Venant torsion constant (J x 1000)	2.020
Warping constant (Cw)	14.176
Distance from shear center to neutral axis (Xo)	-1.017
Radii of gyration (Ro)	4.456
Torsional flexural constant (Beta)	0.948

**Punch Out** 

# 

#### ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

### Mill Steel Framing LEED Green Credits

MR Credit 2	<ul> <li>ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable</li> </ul>
MR Credit 4	Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

