

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

# **Structural Stud**

**Product Description** 

3625162-54
16 GA GALV 3.62" WEB x 1.62"
FLANGE C-STUD .054 MIN GAUGE

G60

0.0566 0.0538 3.6250 1.6250 0.5000 50.0000


Coating		
Physical Properties		
Design Thickness (in)		
Minimum Thickness (in)		
Web Width (in)		
Flange Width (in)		
Stiffening Lip (in)		
Yield Strength (ksi)		

Gross Section Properties		
Cross Sectional Area (A)	0.422	
Weight of Member (lb/ft)	1.44	
Section Modulus (Sx)	0.482	
Moment of Inertia (lx)	0.873	
Radius of Gyration (Rx)	1.438	
Gross Moment of Inertia (ly)	0.154	
Gross Radium of Gyration (Ry)	0.605	

Effective Section Properties	
Moment of Inertia for deflection (lxe)	0.873
Section Modulus (Sxe)	0.444
Allowable Bending moment (Ma)	13.28
Allowable shear force in web (U)(Vag)	3372
Allowable shear at punch (Vanet)	1016

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.451
Warping constant (Cw)	0.457
Distance from shear center to neutral axis (Xo)	-1.283
Radii of gyration (Ro)	2.020
Torsional flexural constant (Beta)	0.597

### **Punch Out**



## ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

# **Mill Steel Framing LEED Green Credits**

MR Credit 2	<ul> <li>ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable</li> </ul>
MR Credit 4	<ul> <li>Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer</li> </ul>
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

